



Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/10/2015

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium
Product code : SG-2004-01561

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
2700 Post Oak Boulevard
Houston, TX 77056 - USA
T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280 - Contains gas under pressure; may explode if heated
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated
OSHA-H01 - May displace oxygen and cause rapid suffocation
Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, face protection, protective gloves, protective clothing
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P403 - Store in a well-ventilated place
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG21 - Open valve slowly

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|---------------------|--------------------|------------------|---|
| Helium | (CAS No) 7440-59-7 | 96.81 - 99.99997 | Compressed gas, H280 |
| Acetone | (CAS No) 67-64-1 | 0.00001 - 1.1 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| METHYL ETHYL KETONE | (CAS No) 78-93-3 | 0.00001 - 1.1 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Methyl alcohol | (CAS No) 67-56-1 | 0.00001 - 0.99 | Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 4 (Inhalation:vapour), H332 STOT SE 1, H370 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : None known.

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation.

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment consistent with the site emergency plan.
- Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

- Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
- Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

- For containment : Try to stop release if safe to do so.
- Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.
- Incompatible products : None known.
- Incompatible materials : None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Acetone (67-64-1) | | |
|-------------------|-------------------------------------|------------------------|
| ACGIH | ACGIH TWA (ppm) | 500 ppm |
| ACGIH | ACGIH STEL (ppm) | 750 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

| Methyl alcohol (67-56-1) | | |
|--------------------------|-------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 260 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |

8.2. Exposure controls

- Appropriate engineering controls : Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
- Hand protection : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------------|---|
| Eye protection | : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. |
| Skin and body protection | : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing. |
| Respiratory protection | : None necessary during normal and routine operations. See Sections 5 & 6. |
| Thermal hazard protection | : None necessary during normal and routine operations. |
| Environmental exposure controls | : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. |
| Other information | : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|------------------------------------|
| Physical state | : Gas |
| Appearance | : Clear, colorless gas. |
| Color | : Colorless |
| Odor | : No data available |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : Not applicable - not flammable |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : See Section 2.1 and 2.2 |
| Explosion limits | : Not applicable - not flammable |
| Explosive properties | : Not applicable - not flammable. |
| Oxidizing properties | : None. |
| Vapor pressure | : No data available |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Molecular mass | : Not applicable for gas-mixtures. |
| Relative gas density | : Lighter than air |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None known.

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Helium (7440-59-7) | |
|----------------------------|--|
| LC50 inhalation rat (ppm) | 820000 ppm/4h |
| Acetone (67-64-1) | |
| LC50 inhalation rat (mg/l) | 50100 mg/m ³ (Exposure time: 8 h) |
| LC50 inhalation rat (ppm) | 29811.91 ppm/4h |
| ATE US (gases) | 29811.910 ppmV/4h |
| ATE US (vapors) | 50.100 mg/l/4h |
| ATE US (dust, mist) | 50.100 mg/l/4h |
| Methyl alcohol (67-56-1) | |
| LD50 oral rat | 5628 mg/kg |
| LD50 dermal rabbit | 17100 mg/kg |
| LC50 inhalation rat (mg/l) | 3.273 mg/l/4h |
| LC50 inhalation rat (ppm) | 2501 ppm/4h |
| ATE US (oral) | 5628.000 mg/kg body weight |
| ATE US (dermal) | 17100.000 mg/kg body weight |
| ATE US (gases) | 2501.000 ppmV/4h |
| ATE US (vapors) | 3.273 mg/l/4h |
| ATE US (dust, mist) | 3.273 mg/l/4h |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.
Symptoms/injuries after skin contact : Adverse effects not expected from this product.
Symptoms/injuries after eye contact : Adverse effects not expected from this product.
Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
Symptoms/injuries upon intravenous administration : Not known.
Chronic symptoms : Adverse effects not expected from this product.

SECTION 12: Ecological information

12.1. Toxicity

| Acetone (67-64-1) | |
|-------------------|--|
| LC50 fish 1 | 4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Acetone (67-64-1) | |
|--------------------------|--|
| EC50 Daphnia 2 | 12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Methyl alcohol (67-56-1) | |
| LC50 fish 1 | 28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 fish 2 | > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |

12.2. Persistence and degradability

| Helium (7440-59-7) | |
|-------------------------------|--|
| Persistence and degradability | No ecological damage caused by this product. |

12.3. Bioaccumulative potential

| Helium (7440-59-7) | |
|---------------------------|--|
| Log Pow | Not applicable for inorganic gases. |
| Bioaccumulative potential | No ecological damage caused by this product. |
| Acetone (67-64-1) | |
| BCF fish 1 | 0.69 |
| Log Pow | -0.24 |
| Methyl alcohol (67-56-1) | |
| BCF fish 1 | < 10 |
| Log Pow | -0.77 |

12.4. Mobility in soil

| Helium (7440-59-7) | |
|--------------------|--|
| Ecology - soil | No ecological damage caused by this product. |

12.5. Other adverse effects

| | |
|------------------------------|--|
| Effect on ozone layer | : No known effects from this product. |
| Effect on the global warming | : No known ecological damage caused by this product. |

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------|--|
| Waste treatment methods | : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. |
| Waste disposal recommendations | : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. |

SECTION 14: Transport information

Department of Transportation (DOT)

| | |
|--------------------------------|---------------------------------|
| In accordance with DOT | |
| Transport document description | : UN1956 Compressed gas, n.o.s. |
| UN-No.(DOT) | : UN1956 |
| Proper Shipping Name (DOT) | : Compressed gas, n.o.s. |
| Hazard labels (DOT) | : 2.2 - Non-flammable gas |



| | |
|---|---|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 302;305 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 314;315 |
| DOT Symbols | : G - Identifies PSN requiring a technical name |

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 306;307 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 150 kg |
| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. |
| Other information | : No supplementary information available. |

TDG

No additional information available

Transport by sea

| | |
|-----------------------------|--------------------------|
| UN-No. (IMDG) | : 1956 |
| Proper Shipping Name (IMDG) | : COMPRESSED GAS, N.O.S. |
| Class (IMDG) | : 2 - Gases |

Air transport

| | |
|-----------------------------|--------------------------|
| UN-No. (IATA) | : 1956 |
| Proper Shipping Name (IATA) | : COMPRESSED GAS, N.O.S. |
| Class (IATA) | : 2 |

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|---|--|
| Helium (7440-59-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Acetone (67-64-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| Methyl alcohol (67-56-1) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | |
| SARA Section 313 - Emission Reporting | 1.0 % |

15.2. International regulations

CANADA

| | |
|---|---|
| Helium (7440-59-7) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class A - Compressed Gas |
| Acetone (67-64-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| Methyl alcohol (67-56-1) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

EU-Regulations

No additional information available

National regulations

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Helium (7440-59-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Acetone (67-64-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on the Canadian IDL (Ingredient Disclosure List)

Methyl alcohol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
 Listed on the Korean ECL (Existing Chemicals List)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Japanese Poisonous and Deleterious Substances Control Law
 Listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

Methyl alcohol (67-56-1)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
|---|---|---|---|----------------------------------|
| No | Yes | No | No | |

Helium (7440-59-7)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Acetone (67-64-1)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania - RTK (Right to Know) List

Methyl alcohol (67-56-1)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
 U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

| | |
|-----------------------|---|
| Indication of changes | : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012. |
| Other information | : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. |

Acetone (0.00001% - 1.10%), Methyl Alcohol (0.00001% - 0.99%), Methyl Ethyl Ketone (0.00001% - 1.10 %) in Helium

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

| | |
|----------------------------------|---|
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4 |
| Compressed gas | Gases under pressure Compressed gas |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Gas 1 | Flammable gases Category 1 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Liquefied gas | Gases under pressure Liquefied gas |
| STOT SE 1 | Specific target organ toxicity (single exposure) Category 1 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H220 | Extremely flammable gas |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H370 | Causes damage to organs |

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.