

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : 10 Components in Isobutane  
 Product code : SG-2011-02966

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

#### 1.3. Details of the supplier of the safety data sheet

Air Liquide  
 9811 Katy Freeway, Suite 100  
 Houston, TX 77024 - USA  
 T 1-800-819-1704  
[www.us.airliquide.com](http://www.us.airliquide.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Gas 1 H220 - Extremely flammable gas  
 Liquefied gas H280 - Contains gas under pressure; may explode if heated

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS04

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas  
 H280 - Contains gas under pressure; may explode if heated  
 OSHA-H01 - May displace oxygen and cause rapid suffocation  
 CGA-HG01 - May cause frostbite  
 CGA-HG04 - May form explosive mixtures with air

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
 P271 - Use only outdoors or in a well-ventilated area  
 P280 - Wear eye protection, face protection, protective gloves, protective clothing  
 P302 - IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area, Get immediate medical advice/attention  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P308+P313 - If exposed or concerned: Get medical advice/attention  
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely  
 P381 - Eliminate all ignition sources if safe to do so  
 P403 - Store in a well-ventilated place  
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations  
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)  
 CGA-PG05 - Use a back flow preventive device in the piping  
 CGA-PG06 - Close valve after each use and when empty  
 CGA-PG10 - Use only with equipment rated for cylinder pressure  
 CGA-PG14 - Approach suspected leak area with caution  
 CGA-PG21 - Open valve slowly

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Isobutane	(CAS No) 75-28-5	1 - 99.9999	Flam. Gas 1, H220 Liquefied gas, H280
Propylene	(CAS No) 115-07-1	0.00001 - 20	Flam. Gas 1, H220 Liquefied gas, H280
Propane	(CAS No) 74-98-6	0.00001 - 20	Flam. Gas 1, H220 Liquefied gas, H280
Isobutylene	(CAS No) 115-11-7	0.00001 - 15	Flam. Gas 1, H220 Liquefied gas, H280
trans-2-Butene	(CAS No) 624-64-6	0.00001 - 10	Flam. Gas 1, H220 Liquefied gas, H280
n-Butane	(CAS No) 106-97-8	0.00001 - 10	Flam. Gas 1, H220 Liquefied gas, H280
1-Butene	(CAS No) 106-98-9	0.00001 - 10	Flam. Gas 1, H220 Liquefied gas, H280
cis-2-Butene	(CAS No) 590-18-1	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
Ethane	(CAS No) 74-84-0	0.00001 - 5	Flam. Gas 1, H220 Liquefied gas, H280
1-Pentene	(CAS No) 109-67-1	0.00001 - 2	Flam. Liq. 1, H224 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Isopentane	(CAS No) 78-78-4	0.00001 - 2	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after skin contact : May cause frostbite.
- Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is flammable.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture.
Reactivity	: None known.

### 5.3. Advice for firefighters

Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate ventilation.
------------------	--------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment consistent with the site emergency plan.
Emergency procedures	: Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

#### 6.1.2. For emergency responders

Protective equipment	: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures	: Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe.

### 6.2. Environmental precautions

Try to stop release if safe to do so.

### 6.3. Methods and material for containment and cleaning up

For containment	: Try to stop release if safe to do so.
Methods for cleaning up	: Dispose of this material and its container in accordance with local regulations.

### 6.4. Reference to other sections

See also Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools.
Hygiene measures	: Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.
Incompatible products	: None known.
Incompatible materials	: Oxidizing materials. Air.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>trans-2-Butene (624-64-6)</b>		
ACGIH	ACGIH TWA (ppm)	250 ppm
<b>n-Butane (106-97-8)</b>		
ACGIH	ACGIH STEL (ppm)	1000 ppm
<b>1-Butene (106-98-9)</b>		
ACGIH	ACGIH TWA (ppm)	250 ppm
<b>Isobutane (75-28-5)</b>		
ACGIH	ACGIH STEL (ppm)	1000 ppm
<b>Isopentane (78-78-4)</b>		
ACGIH	ACGIH TWA (ppm)	600 ppm
<b>Propane (74-98-6)</b>		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
<b>Ethane (74-84-0)</b>		
ACGIH	ACGIH TWA (ppm)	1000 ppm
<b>cis-2-Butene (590-18-1)</b>		
ACGIH	ACGIH TWA (ppm)	250 ppm
<b>Propylene (115-07-1)</b>		
ACGIH	ACGIH TWA (ppm)	500 ppm
<b>Isobutylene (115-11-7)</b>		
DNEL	DNEL	≈

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: No data available
Explosive properties	: Without adequate ventilation formation of explosive mixtures may be possible.
Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: No Data Available
Relative gas density	: Heavier than air
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Oxidizing materials. Air.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>trans-2-Butene (624-64-6)</b>	
LC50 inhalation rat (ppm)	150307.38 ppm/4h
<b>n-Butane (106-97-8)</b>	
LC50 inhalation rat (mg/l)	658 g/m <sup>3</sup> (Exposure time: 4 h)
LC50 inhalation rat (ppm)	276789.28 ppm/4h
<b>1-Butene (106-98-9)</b>	
LC50 inhalation rat (ppm)	500000 ppm/4h
<b>Isobutane (75-28-5)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	276713.11 ppm/4h

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Isopentane (78-78-4)</b>	
LC50 inhalation rat (ppm)	94859.36 ppm/4h
ATE US (gases)	94859.360 ppmV/4h
ATE US (vapors)	280.000 mg/l/4h

<b>Propane (74-98-6)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	282800 ppm/4h

<b>Ethane (74-84-0)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h
ATE US (vapors)	658.000 mg/l/4h
ATE US (dust, mist)	658.000 mg/l/4h

<b>cis-2-Butene (590-18-1)</b>	
LC50 inhalation rat (ppm)	150307.38 ppm/4h

<b>1-Pentene (109-67-1)</b>	
LC50 inhalation rat (ppm)	61002.99 ppm/4h
ATE US (gases)	61002.990 ppmV/4h

<b>Propylene (115-07-1)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h
LC50 inhalation rat (ppm)	49957.23 ppm/4h

<b>Isobutylene (115-11-7)</b>	
LC50 inhalation rat (ppm)	239620.46 ppm/4h
ATE US (gases)	239620.460 ppmV/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Propylene (115-07-1)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : May cause frostbite.

Symptoms/injuries after eye contact : Contact with the product may cause cold burns or frostbite.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

## SECTION 12: Ecological information

### 12.1. Toxicity

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Isopentane (78-78-4)</b>	
EC50 Daphnia 1	2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

<b>trans-2-Butene (624-64-6)</b>	
Persistence and degradability	No data available.
<b>n-Butane (106-97-8)</b>	
Persistence and degradability	No data available.
<b>1-Butene (106-98-9)</b>	
Persistence and degradability	Not readily biodegradable.
<b>Isobutane (75-28-5)</b>	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
<b>Isopentane (78-78-4)</b>	
Persistence and degradability	No data available.
<b>Propane (74-98-6)</b>	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
<b>Ethane (74-84-0)</b>	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.
<b>cis-2-Butene (590-18-1)</b>	
Persistence and degradability	No data available.
<b>Propylene (115-07-1)</b>	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.

### 12.3. Bioaccumulative potential

<b>trans-2-Butene (624-64-6)</b>	
Log Pow	2.32
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>n-Butane (106-97-8)</b>	
Log Pow	2.89
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>1-Butene (106-98-9)</b>	
Log Pow	2.4
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>Isobutane (75-28-5)</b>	
BCF fish 1	1.57 - 1.97
Log Pow	2.76
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>Isopentane (78-78-4)</b>	
Log Pow	3.2 - 3.3
Log Kow	Not applicable for gas-mixtures.
Bioaccumulative potential	No data available.
<b>Propane (74-98-6)</b>	
Log Pow	2.36
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>Ethane (74-84-0)</b>	
Log Pow	1.81
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.
<b>cis-2-Butene (590-18-1)</b>	
Log Pow	2.33
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propylene (115-07-1)	
Log Pow	1.77
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

### 12.4. Mobility in soil

trans-2-Butene (624-64-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
n-Butane (106-97-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
1-Butene (106-98-9)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Isobutane (75-28-5)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Isopentane (78-78-4)	
Mobility in soil	No data available.
Propane (74-98-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Ethane (74-84-0)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
cis-2-Butene (590-18-1)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Propylene (115-07-1)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

### 12.5. Other adverse effects

Effect on ozone layer	: No known effects from this product.
Effect on the global warming	: No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air.
Waste disposal recommendations	: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at <a href="http://www.cganet.com">www.cganet.com</a> for more guidance on suitable disposal methods.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT	
Transport document description	: UN3161 Liquefied gas, flammable, n.o.s.
UN-No.(DOT)	: UN3161
Proper Shipping Name (DOT)	: Liquefied gas, flammable, n.o.s.
Hazard labels (DOT)	: 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

### TDG

Transport document description	: UN3161 LIQUEFIED GAS, FLAMMABLE, N.O.S., 2.1
UN-No. (TDG)	: UN3161
TDG Proper Shipping Name	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gas.

### Transport by sea

UN-No. (IMDG)	: 3161
Proper Shipping Name (IMDG)	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG)	: 2 - Gases

### Air transport

UN-No. (IATA)	: 3161
Proper Shipping Name (IATA)	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IATA)	: 2

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>trans-2-Butene (624-64-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>n-Butane (106-97-8)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>1-Butene (106-98-9)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Isobutane (75-28-5)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Isopentane (78-78-4)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Propane (74-98-6)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>Ethane (74-84-0)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>cis-2-Butene (590-18-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory
<b>1-Pentene (109-67-1)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Propylene (115-07-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

## 15.2. International regulations

### CANADA

#### trans-2-Butene (624-64-6)

Listed on the Canadian DSL (Domestic Substances List)

#### n-Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

#### 1-Butene (106-98-9)

Listed on the Canadian DSL (Domestic Substances List)

#### Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

#### Isopentane (78-78-4)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid
----------------------	---------------------------------------

#### Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

#### Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

#### cis-2-Butene (590-18-1)

Listed on the Canadian DSL (Domestic Substances List)

#### 1-Pentene (109-67-1)

Listed on the Canadian DSL (Domestic Substances List)

#### Propylene (115-07-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

### EU-Regulations

No additional information available

### National regulations

#### trans-2-Butene (624-64-6)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **n-Butane (106-97-8)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Canadian IDL (Ingredient Disclosure List)

### **1-Butene (106-98-9)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **Isobutane (75-28-5)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **Isopentane (78-78-4)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **Propane (74-98-6)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **Ethane (74-84-0)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **cis-2-Butene (590-18-1)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **1-Pentene (109-67-1)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### **Propylene (115-07-1)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

#### trans-2-Butene (624-64-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### n-Butane (106-97-8)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### 1-Butene (106-98-9)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Isobutane (75-28-5)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Isopentane (78-78-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Propane (74-98-6)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Ethane (74-84-0)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### cis-2-Butene (590-18-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### 1-Pentene (109-67-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Propylene (115-07-1)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

- Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
- Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

# 10 Components in Isobutane

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 1	Flammable liquids Category 1
Liquefied gas	Gases under pressure Liquefied gas
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

*This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.*