



# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/26/2015

Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen  
Product code : SG-2005-02964

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

#### 1.3. Details of the supplier of the safety data sheet

Air Liquide  
9811 Katy Freeway, Suite 100  
Houston, TX 77024 - USA  
T 1-800-819-1704  
[www.us.airliquide.com](http://www.us.airliquide.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Compressed gas H280 - Contains gas under pressure; may explode if heated

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated  
OSHA-H01 - May displace oxygen and cause rapid suffocation

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection, face protection, protective gloves, protective clothing  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P403 - Store in a well-ventilated place  
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations  
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)  
CGA-PG05 - Use a back flow preventive device in the piping  
CGA-PG06 - Close valve after each use and when empty  
CGA-PG10 - Use only with equipment rated for cylinder pressure  
CGA-PG14 - Approach suspected leak area with caution  
CGA-PG21 - Open valve slowly

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Nitrogen	(CAS No) 7727-37-9	97.9001 - 99.99996	Compressed gas, H280
Acetone	(CAS No) 67-64-1	0.00001 - 1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl alcohol	(CAS No) 67-56-1	0.00001 - 0.9999	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 4 (Inhalation:vapour), H332 STOT SE 1, H370
Acetaldehyde	(CAS No) 75-07-0	0.00001 - 0.05	Flam. Liq. 1, H224 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Isoprene	(CAS No) 78-79-5	0.00001 - 0.05	Flam. Liq. 1, H224 Muta. 2, H341 Carc. 1B, H350 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Adverse effects not expected from this product.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.
- Symptoms/injuries after skin contact : Adverse effects not expected from this product.
- Symptoms/injuries after eye contact : Adverse effects not expected from this product.
- Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.
- Symptoms/injuries upon intravenous administration : Not known.
- Chronic symptoms : Adverse effects not expected from this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : None known.

#### 5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.

Emergency procedures : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

##### 6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.

Emergency procedures : Evacuate and limit access. Ventilate area.

#### 6.2. Environmental precautions

Try to stop release if safe to do so.

#### 6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if safe to do so.

Methods for cleaning up : Dispose of this material and its container in accordance with local regulations.

#### 6.4. Reference to other sections

See also Sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area.

Incompatible products : None known.

Incompatible materials : None known.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	500 ppm
ACGIH	ACGIH STEL (ppm)	750 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Methyl alcohol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methyl alcohol (67-56-1)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.
Hand protection	: Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection.
Eye protection	: Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing.
Respiratory protection	: None necessary during normal and routine operations. See Sections 5 & 6.
Thermal hazard protection	: None necessary during normal and routine operations.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Other information	: Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable - not flammable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: See Section 2.1 and 2.2
Explosion limits	: Not applicable - not flammable
Explosive properties	: Not applicable - not flammable.
Oxidizing properties	: None.
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: Not applicable for gas-mixtures.
Relative gas density	: Similar to air
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

No additional information available

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

None known.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

None known.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Nitrogen (7727-37-9)</b>	
LC50 inhalation rat (ppm)	820000 ppm/4h
<b>Acetaldehyde (75-07-0)</b>	
LC50 inhalation rat (ppm)	13300 ppm/4h
<b>Isoprene (78-79-5)</b>	
LD50 dermal rat	> 1 ml/kg
LC50 inhalation rat (mg/l)	180 mg/l/4h
LC50 inhalation rat (ppm)	64597.09 ppm/4h
ATE US (gases)	64597.090 ppmV/4h
ATE US (vapors)	180.000 mg/l/4h
ATE US (dust, mist)	180.000 mg/l/4h
<b>Acetone (67-64-1)</b>	
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup> (Exposure time: 8 h)
LC50 inhalation rat (ppm)	29811.91 ppm/4h
ATE US (gases)	29811.910 ppmV/4h
ATE US (vapors)	50.100 mg/l/4h
ATE US (dust, mist)	50.100 mg/l/4h
<b>Methyl alcohol (67-56-1)</b>	
LD50 oral rat	5628 mg/kg
LD50 dermal rabbit	17100 mg/kg
LC50 inhalation rat (mg/l)	3.273 mg/l/4h
LC50 inhalation rat (ppm)	2501 ppm/4h
ATE US (oral)	5628.000 mg/kg body weight
ATE US (dermal)	17100.000 mg/kg body weight
ATE US (gases)	2501.000 ppmV/4h
ATE US (vapors)	3.273 mg/l/4h
ATE US (dust, mist)	3.273 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified

Isoprene (78-79-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May displace oxygen and cause rapid suffocation.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

## SECTION 12: Ecological information

### 12.1. Toxicity

Isoprene (78-79-5)	
LC50 fish 1	32.5 - 50.15 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	140 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 1000 mg/l (Exposure time: 96 h - Species: Scenedesmus quadricauda)
LC50 fish 2	58.75 - 95.32 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Acetone (67-64-1)	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Methyl alcohol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

### 12.2. Persistence and degradability

Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.
Isoprene (78-79-5)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	3.2 - 4.5 (at 20 °C)

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
BCF fish 1	0.69
Log Pow	-0.24
Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

### 12.4. Mobility in soil

Nitrogen (7727-37-9)	
Ecology - soil	No ecological damage caused by this product.

### 12.5. Other adverse effects

- Effect on ozone layer : No known effects from this product.
- Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Waste treatment methods : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.
- Waste disposal recommendations : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at [www.cganet.com](http://www.cganet.com) for more guidance on suitable disposal methods.

## SECTION 14: Transport information

### Department of Transportation (DOT)

- In accordance with DOT
- Transport document description : UN1956 Compressed gas, n.o.s.
- UN-No.(DOT) : UN1956
- Proper Shipping Name (DOT) : Compressed gas, n.o.s.
- Hazard labels (DOT) : 2.2 - Non-flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 302;305
- DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
- DOT Symbols : G - Identifies PSN requiring a technical name
- DOT Packaging Exceptions (49 CFR 173.xxx) : 306;307
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Other information : No supplementary information available.

### TDG

- Transport document description : UN1956 COMPRESSED GAS, N.O.S., 2.2
- UN-No. (TDG) : UN1956
- TDG Proper Shipping Name : COMPRESSED GAS, N.O.S.

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Primary Hazard Classes : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gas.

### Transport by sea

UN-No. (IMDG) : 1956  
Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.  
Class (IMDG) : 2 - Gases

### Air transport

UN-No. (IATA) : 1956  
Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.  
Class (IATA) : 2

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Nitrogen (7727-37-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Isoprene (78-79-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting : 0.1 %

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag : T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

#### Methyl alcohol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting : 1.0 %

### 15.2. International regulations

#### CANADA

#### Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification : Class A - Compressed Gas

#### Isoprene (78-79-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification : Class B Division 2 - Flammable Liquid  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

#### Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification : Class B Division 2 - Flammable Liquid  
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects  
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### EU-Regulations

No additional information available

### National regulations

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Nitrogen (7727-37-9)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### Isoprene (78-79-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Japanese ISHL (Industrial Safety and Health Law)  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Japanese Pollutant Release and Transfer Register Law (PRTR Law)  
 Listed on the Canadian IDL (Ingredient Disclosure List)

### Acetone (67-64-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on the Canadian IDL (Ingredient Disclosure List)

### Methyl alcohol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Japanese Poisonous and Deleterious Substances Control Law  
 Listed on the Canadian IDL (Ingredient Disclosure List)

## 15.3. US State regulations

### Isoprene (78-79-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

### Methyl alcohol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	

### Nitrogen (7727-37-9)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Isoprene (78-79-5)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

# Acetaldehyde (0.00001% - 0.050%), Isoprene (0.00001% - 0.050%), Acetone (0.00001% - 1.00%), Methanol (0.00001% - 0.9999%) in Nitrogen

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### Methyl alcohol (67-56-1)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

- Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
- Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Liquefied gas	Gases under pressure Liquefied gas
Muta. 2	Germ cell mutagenicity Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H370	Causes damage to organs
H411	Toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

*This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.*