



n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/25/2015

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane
Product code : SG-2004-03254

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Details of the supplier of the safety data sheet

Air Liquide
9811 Katy Freeway, Suite 100
Houston, TX 77024 - USA
T 1-800-819-1704
www.us.airliquide.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | | |
|-------------------------------|--------|--|
| Flam. Gas 1 | H220 - | Extremely flammable gas |
| Compressed gas | H280 - | Contains gas under pressure; may explode if heated |
| Acute Tox. 3 (Inhalation:gas) | H331 - | Toxic if inhaled |
| STOT SE 3 | H335 - | May cause respiratory irritation |

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated
H331 - Toxic if inhaled
H335 - May cause respiratory irritation
CGA-HG04 - May form explosive mixtures with air
CGA-HG11 - Symptoms may be delayed
CGA-HG16 - Extended exposure to gas reduces the ability to smell sulfides.

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P261 - Avoid breathing gas
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, face protection, protective gloves, protective clothing
P284 - Wear respiratory protection. Consult respiratory device supplier's product information for the selection of the appropriate device.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P307+P311 - If exposed: Call a poison center/doctor
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381 - Eliminate all ignition sources if safe to do so
P403 - Store in a well-ventilated place
P405 - Store locked up

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
CGA-PG05 - Use a back flow preventive device in the piping
CGA-PG06 - Close valve after each use and when empty
CGA-PG10 - Use only with equipment rated for cylinder pressure
CGA-PG14 - Approach suspected leak area with caution
CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug
CGA-PG21 - Open valve slowly
CGA-PG29 - Do not depend on odor to detect presence of gas

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|------------------|--------------------|-------------------|---|
| Ethane | (CAS No) 74-84-0 | 0.0001 - 85.75998 | Flam. Gas 1, H220 Liquefied gas, H280 |
| Hydrogen Sulfide | (CAS No) 7783-06-4 | 14.24 - 40 | Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400 |
| Propane | (CAS No) 74-98-6 | 0.00001 - 40 | Flam. Gas 1, H220 Liquefied gas, H280 |
| n-Butane | (CAS No) 106-97-8 | 0.00001 - 19.9999 | Flam. Gas 1, H220 Liquefied gas, H280 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Apply artificial respiration with bag or mask if breathing stopped. Get immediate medical advice/attention.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. Toxic if inhaled.

Symptoms/injuries after skin contact : Adverse effects not expected from this product.

Symptoms/injuries after eye contact : Adverse effects not expected from this product.

Symptoms/injuries after ingestion : Ingestion is not considered a potential route of exposure.

Symptoms/injuries upon intravenous administration : Not known.

Chronic symptoms : Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|---|
| Fire hazard | : This product is flammable. |
| Explosion hazard | : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. May form flammable/explosive vapor-air mixture. |
| Reactivity | : None known. |

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Firefighting instructions | : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. |
| Protection during firefighting | : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--------------------------------|
| General measures | : Ensure adequate ventilation. |
|------------------|--------------------------------|

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | : Wear protective equipment consistent with the site emergency plan. |
| Emergency procedures | : Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind. |

6.1.2. For emergency responders

| | |
|----------------------|--|
| Protective equipment | : Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection. |
| Emergency procedures | : Evacuate and limit access. Ventilate area. Remove ignition sources. Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering atmospheres of unknown contaminant concentration until proven to be safe. |

6.2. Environmental precautions

Try to stop release if safe to do so.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| For containment | : Try to stop release if safe to do so. |
| Methods for cleaning up | : Dispose of this material and its container in accordance with local regulations. |

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|--|
| Additional hazards when processed | : Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Handle empty containers with care because residual vapors are flammable. In use, may form flammable vapor-air mixture. |
| Precautions for safe handling | : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only non-sparking tools. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------|---|
| Technical measures | : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. |
| Storage conditions | : Do not expose to temperatures exceeding 52°C (125°F). Keep container closed when not in use. Protect cylinder from physical damage. Store in well ventilated area. Store locked up. |
| Incompatible products | : None known. |
| Incompatible materials | : Oxidizing materials. Air. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| n-Butane (106-97-8) | | |
|------------------------------|-------------------------------------|------------------------|
| ACGIH | ACGIH STEL (ppm) | 1000 ppm |
| Hydrogen Sulfide (7783-06-4) | | |
| ACGIH | ACGIH TWA (ppm) | 1 ppm |
| ACGIH | ACGIH STEL (ppm) | 5 ppm |
| OSHA | OSHA PEL (Ceiling) (ppm) | 20 ppm |
| Propane (74-98-6) | | |
| ACGIH | ACGIH TWA (ppm) | 1000 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| Ethane (74-84-0) | | |
| ACGIH | ACGIH TWA (ppm) | 1000 ppm |

8.2. Exposure controls

| | |
|----------------------------------|---|
| Appropriate engineering controls | : Ensure exposure is below occupational exposure limits. Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider work permit system e.g. for maintenance activities. Alarm detectors should be used when toxic gases may be released. |
| Hand protection | : Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand Protection. |
| Eye protection | : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection. |
| Skin and body protection | : Wear suitable protective clothing, e.g. - lab coats, coveralls or flame resistant clothing. |
| Respiratory protection | : Wear a respirator when performing non-routine tasks not limited to line breaking or sampling. Wear a respirator during routine operations if determined to be necessary during a process-specific review. Consult respirator suppliers' product information or their representatives for the selection of the appropriate respirator. |
| Thermal hazard protection | : None necessary during normal and routine operations. |
| Environmental exposure controls | : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. |
| Other information | : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Gas |
| Appearance | : Clear, colorless gas. |
| Color | : Colorless |
| Odor | : Rotten eggs. Sulfide-like |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : See Section 2.1 and 2.2 |
| Explosion limits | : No data available |
| Explosive properties | : Without adequate ventilation formation of explosive mixtures may be possible. |
| Oxidizing properties | : None. |
| Vapor pressure | : No data available |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Molecular mass | : Not applicable for gas-mixtures. |

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------|---------------------|
| Relative gas density | : Heavier than air |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |

9.2. Other information

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Oxidizing materials. Air.

10.6. Hazardous decomposition products

Under normal conditions of storage and use hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Toxic if inhaled.

| n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane | |
|---|---|
| ATE US (gases) | 1078.788 ppmV/4h |
| n-Butane (106-97-8) | |
| LC50 inhalation rat (mg/l) | 658 g/m ³ (Exposure time: 4 h) |
| LC50 inhalation rat (ppm) | 276789.28 ppm/4h |
| Hydrogen Sulfide (7783-06-4) | |
| LC50 inhalation rat (mg/l) | 0.99 mg/l (Exposure time: 1 h) |
| LC50 inhalation rat (ppm) | 356 ppm/4h |
| ATE US (gases) | 356.000 ppmV/4h |
| ATE US (vapors) | 0.990 mg/l/4h |
| ATE US (dust, mist) | 0.990 mg/l/4h |
| Propane (74-98-6) | |
| LC50 inhalation rat (mg/l) | 658 mg/l/4h |
| LC50 inhalation rat (ppm) | 282800 ppm/4h |
| Ethane (74-84-0) | |
| LC50 inhalation rat (mg/l) | 658 mg/l/4h |
| LC50 inhalation rat (ppm) | 820000 ppm/4h |
| ATE US (gases) | 820000.000 ppmV/4h |
| ATE US (vapors) | 658.000 mg/l/4h |
| ATE US (dust, mist) | 658.000 mg/l/4h |

Skin corrosion/irritation : Not classified

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|--|
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : May cause respiratory irritation. |
| Specific target organ toxicity (repeated exposure) | : Not classified |
| Aspiration hazard | : Not classified |
| Symptoms/injuries after inhalation | : May cause respiratory irritation. Toxic if inhaled. |
| Symptoms/injuries after skin contact | : Adverse effects not expected from this product. |
| Symptoms/injuries after eye contact | : Adverse effects not expected from this product. |
| Symptoms/injuries after ingestion | : Ingestion is not considered a potential route of exposure. |
| Symptoms/injuries upon intravenous administration | : Not known. |
| Chronic symptoms | : Adverse effects not expected from this product. |

SECTION 12: Ecological information

12.1. Toxicity

| Hydrogen Sulfide (7783-06-4) | |
|------------------------------|---|
| LC50 fish 1 | 0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through]) |
| EC50 Daphnia 1 | 0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus) |
| LC50 fish 2 | 0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

12.2. Persistence and degradability

| n-Butane (106-97-8) | |
|-------------------------------|--|
| Persistence and degradability | No data available. |
| Hydrogen Sulfide (7783-06-4) | |
| Persistence and degradability | Not applicable for inorganic gases. |
| Propane (74-98-6) | |
| Persistence and degradability | The substance is biodegradable. Unlikely to persist. |
| Ethane (74-84-0) | |
| Persistence and degradability | The substance is biodegradable. Unlikely to persist. |

12.3. Bioaccumulative potential

| n-Butane (106-97-8) | |
|------------------------------|---|
| Log Pow | 2.89 |
| Log Kow | Not applicable for gas-mixtures. |
| Bioaccumulative potential | Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9. |
| Hydrogen Sulfide (7783-06-4) | |
| BCF fish 1 | (no bioaccumulation expected) |
| Log Pow | Not applicable for inorganic gases. |
| Bioaccumulative potential | No data available. |
| Propane (74-98-6) | |
| Log Pow | 2.36 |
| Bioaccumulative potential | Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9. |
| Ethane (74-84-0) | |
| Log Pow | 1.81 |
| Bioaccumulative potential | Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9. |

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

| n-Butane (106-97-8) | |
|------------------------------|---|
| Mobility in soil | No data available. |
| Ecology - soil | Because of its high volatility, the product is unlikely to cause ground or water pollution. |
| Hydrogen Sulfide (7783-06-4) | |
| Ecology - soil | Because of its high volatility, the product is unlikely to cause ground or water pollution. |
| Propane (74-98-6) | |
| Ecology - soil | Because of its high volatility, the product is unlikely to cause ground or water pollution. |
| Ethane (74-84-0) | |
| Ecology - soil | Because of its high volatility, the product is unlikely to cause ground or water pollution. |

12.5. Other adverse effects

| | |
|------------------------------|--|
| Effect on ozone layer | : No known effects from this product. |
| Effect on the global warming | : No known ecological damage caused by this product. |

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------|---|
| Waste treatment methods | : Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into areas where there is a risk of forming an explosive mixture with air. |
| Waste disposal recommendations | : Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods. |

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

| | |
|----------------------------------|---|
| Transport document description | : UN1953 Compressed gas, toxic, flammable, n.o.s. Inhalation Hazard Zone C/D, 2.3 |
| UN-No.(DOT) | : UN1953 |
| Proper Shipping Name (DOT) | : Compressed gas, toxic, flammable, n.o.s. Inhalation Hazard Zone C/D |
| Transport hazard class(es) (DOT) | : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115 |
| Hazard labels (DOT) | : 2.3 - Poison gas 2.1 - Flammable gas |



| | |
|--|---|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : 302;305 |
| DOT Packaging Bulk (49 CFR 173.xxx) | : 314;315 |
| DOT Symbols | : G - Identifies PSN requiring a technical name |
| DOT Special Provisions (49 CFR 172.102) | : 3 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone C (see 173.116(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter. B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : None |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : Forbidden |

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : Forbidden

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

Transport document description : UN1953 COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S., 2.3

UN-No. (TDG) : UN1953

TDG Proper Shipping Name : COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S.

TDG Primary Hazard Classes : 2.3 - Class 2.3 - Toxic Gas.

Transport by sea

UN-No. (IMDG) : 1953

Proper Shipping Name (IMDG) : COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : Forbidden

SECTION 15: Regulatory information

15.1. US Federal regulations

n-Butane (106-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Hydrogen Sulfide (7783-06-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302

Subject to reporting requirements of United States SARA Section 313

| | |
|--|-----|
| SARA Section 302 Threshold Planning Quantity (TPQ) | 500 |
|--|-----|

| | |
|---------------------------------------|-------|
| SARA Section 313 - Emission Reporting | 1.0 % |
|---------------------------------------|-------|

Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethane (74-84-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

n-Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

| | |
|----------------------|--|
| WHMIS Classification | Class A - Compressed Gas Class B Division 1 - Flammable Gas |
|----------------------|--|

Hydrogen Sulfide (7783-06-4)

Listed on the Canadian DSL (Domestic Substances List)

| | |
|----------------------|---|
| WHMIS Classification | Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|---|

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

| | |
|----------------------|--|
| WHMIS Classification | Class A - Compressed Gas Class B Division 1 - Flammable Gas |
|----------------------|--|

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas
Class B Division 1 - Flammable Gas

EU-Regulations

No additional information available

National regulations

n-Butane (106-97-8)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

Hydrogen Sulfide (7783-06-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)

Propane (74-98-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Ethane (74-84-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

n-Butane (106-97-8)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Hydrogen Sulfide (7783-06-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Propane (74-98-6)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Ethane (74-84-0)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

n-Butane (0.00001% - 19.9999%), Propane (0.00001% - 40.00%), Hydrogen Sulfide (14.24% - 40.00%) in Ethane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

- Indication of changes : Revised safety data sheet in accordance with OSHA final rule on GHS implementation promulgated March 26, 2012.
- Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

| | |
|-------------------------------|--|
| Acute Tox. 2 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 2 |
| Acute Tox. 3 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 3 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Compressed gas | Gases under pressure Compressed gas |
| Flam. Gas 1 | Flammable gases Category 1 |
| Liquefied gas | Gases under pressure Liquefied gas |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H220 | Extremely flammable gas |
| H280 | Contains gas under pressure; may explode if heated |
| H330 | Fatal if inhaled |
| H331 | Toxic if inhaled |
| H335 | May cause respiratory irritation |
| H400 | Very toxic to aquatic life |

SDS US (GHS HazCom 2012)

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Air Liquide America Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.