

# SAFETY DATA SHEET

### Nexxus Dry Shampoo (Aerosol) – All Variants Refreshing Mist, Youth Renew

## Section 1. Identification

Product name	:	Nexxus Dry Shampoo (Aerosol) – All Variants Refreshing Mist, Youth Renewal
Product type UPC Code	:	Aerosol Dry Shampoo 005592576834, 605592271281
Internal product code	:	M_83201350

### Relevant identified uses of the substance or mixture and uses advised against

		Identified uses
		h or in preparations at industrial sites
Consumer uses: Private households	(= gei	neral public = consumers)
Professional uses: Public domain (a	dmini	stration, education, entertainment, services, craftsmen)
Supplier's details	:	UNILEVER 700 Sylvan Avenue
		Englewood Cliffs NJ 07632
		USA
Emergency telephone number	:	Phone #: 800-761-3683 Monday thru Friday (8:30 AM – 5:00 PM EST)
(with hours of operation)		Emergency #: 800-745-9269 (24 hours)
		Poison Control #: 800-949-7866 (24 hours)
		CHEMTREC #: 800-424-9300(24 hours, Transportation
		Emergencies)

### **Consumer Information:**

For information regarding the use of this product by a consumer, please refer directly to the product label. This industrial MSDS is provided for workplace employees, per US OSHA regulations. It contains recommendations for handling of this product in an occupational, or workplace, setting.

Any first aid or warnings that are applicable to consumer use are stated directly on the product label, in accordance with all applicable government regulations.

Section 2. Hazards ide	enti	ification
OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas
GHS label elements		
Hazard pictograms	:	
Signal word Hazard statements	:	Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Pressurized container: may burst if heated.
Precautionary statements		
General Prevention	:	Keep out of reach of children. Keep away from heat, sparks, open flames and hot surfaces No smoking. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust or mist. Do not spray on an open flame or other ignition source.
Response	:	Not applicable.
Storage	:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal Supplemental label elements Hazards not otherwise classified	::	Dispose of used up container in accordance with local regulations. None known. None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

### CAS number/other identifiers

Version: 1.1

Date of issue/Date of revision: 06.21.2016

Date of previous issue: 00.00.0000

Ingredient name	%	CAS number
Isobutane	50 - 75	75-28-5
Propane	10 - 25	74-98-6
Alcohol	5 - 10	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### **Section 4. First-aid measures**

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Version:	1.1	Date of issue/Date of revision:	06.21.2016	Date of previous issue:	00.00.0000

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following: irritation redness
Inhalation	<ul> <li>Adverse symptoms may include the following: respiratory tract irritation coughing</li> </ul>
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate medical	tention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing n Unsuitable extinguishing NFPA 30B Classification		Use an ext None know Aerosol Le	vn.	itable for the surround	ing fire.
Specific hazards arising fr chemical	om the :	increase w subsequen or travel a back, caus	ill occur and the con t explosion. Gas ma considerable distance ing fire or explosion from a fire at high sp	In a fire or if heated, a ntainer may burst, with y accumulate in low o ce to a source of igniti h. Bursting aerosol com- peed. Runoff to sewer	n the risk of a r confined areas on and flash ntainers may be
Hazardous thermal decomposition products	:	Decompose carbon dio carbon mo	xide	include the following	materials:
Version: 1.1	Date of issue/Date	of revision:	06.21.2016	Date of previous issue:	00.00.0000

Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personne	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation i inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials See also the information in "For non-emergency personnel".	
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soi or air).	
Methods and materials for contain	nent and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	•
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposa according to local regulations (see Section 13). Dispose of via a	al
Version: 1.1 Date of	sue/Date of revision: 06.21.2016 Date of previous issue: 00.00.0000	

licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C/120°F. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

### **Occupational exposure limits**

Ingredient name	Exposure limits	
Isobutane	NIOSH REL 1994-06-01 TWA	
	1,900 mg/m3	
	800 ppm	
	Form:	
	ACGIH TLV 1996-05-18 TWA	
	1,000 ppm	

Propane	OSHA PEL 1989 1989-03-01 TWA           1,800 mg/m3           1,000 ppm           Form:           OSHA PEL 1993-06-30 TWA           1,800 mg/m3           1,000 ppm           Form:           NIOSH REL 1994-06-01 TWA           1,800 mg/m3           1,000 ppm           Form:           NIOSH REL 1994-06-01 TWA           1,800 mg/m3           1,000 ppm           Form:           ACGIH TLV 2013-06-14           ACGIH TLV 1996-05-18 TWA           1,000 ppm           OSHA PEL 1989 TWA           1,800 mg/m3           1,000 ppm           Form:           OSHA PEL 1989 1989-03-01 TWA           1,900 mg/m3           1,000 ppm           Form:           OSHA PEL 1989 1989-03-01 TWA           1,900 mg/m3           1,000 ppm           Form:           OSHA PEL 1993-06-30 TWA           1,900 mg/m3           1,000 ppm           Form:           NIOSH REL 1994-06-01 TWA           1,900 mg/m3           1,000 ppm           Form:           ACGIH TLV 2008-11-24 STEL           1,000 ppm </th
Appropriate engineering controls : Environmental exposure controls :	fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion- proof ventilation equipment.
Individual protection measures	

Version: 1.1

Date of issue/Date of revision: 06.21.2016

Date of previous issue: 00.00.0000

Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Section 9. Physical and chemical properties

### **Appearance**

Physical state Colour	<ul><li>liquid [aerosol]</li><li>Not available.</li></ul>		
Odour Odour threshold	<ul><li>perfumed</li><li>Not available.</li></ul>		
Version: 1.1	Date of issue/Date of revision: 06.21.2016	Date of previous issue:	00.00.0000

nH		Not available.
pH Melting point	÷	Not applicable
Menting point	•	Not applicable
Boiling point	:	Not available.
Flash point	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		<b>Upper:</b> Not available.
Vapour density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity		Dynamic: Not available.
	:	<b>Dynamic:</b> Not available. <b>Kinematic:</b> Not available.
Viscosity	:	
	:	
Viscosity <u>Aerosol product</u>		Kinematic: Not available.
Viscosity <u>Aerosol product</u> Type of aerosol	:	<b>Kinematic:</b> Not available.
Viscosity <u>Aerosol product</u>		Kinematic: Not available.
Viscosity <u>Aerosol product</u> Type of aerosol		<b>Kinematic:</b> Not available.
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure	:	<b>Kinematic:</b> Not available. Spray 104 PSI at 54°C/130°F
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure	:	<b>Kinematic:</b> Not available. Spray 104 PSI at 54°C/130°F
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure Heat of combustion Ignition distance	: :	Kinematic: Not available. Spray 104 PSI at 54°C/130°F < 20 J/kg 58 cm
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure Heat of combustion Ignition distance Enclosed space ignition - Time	: :	Kinematic: Not available. Spray 104 PSI at 54°C/130°F < 20 J/kg
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure Heat of combustion Ignition distance Enclosed space ignition - Time equivalent	: :	Kinematic: Not available. Spray 104 PSI at 54°C/130°F < 20 J/kg 58 cm Not available.
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure Heat of combustion Ignition distance Enclosed space ignition - Time equivalent Enclosed space ignition - Time	: :	Kinematic: Not available. Spray 104 PSI at 54°C/130°F < 20 J/kg 58 cm
Viscosity <u>Aerosol product</u> Type of aerosol Can pressure Heat of combustion Ignition distance Enclosed space ignition - Time equivalent	: : : : : : : : : : : : : : : : : : : :	Kinematic: Not available. Spray 104 PSI at 54°C/130°F < 20 J/kg 58 cm Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	:	No specific data.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Not available.

:

Version: 1.1

Flame duration

Date of issue/Date of revision: 06.21.2016

# Section 11. Toxicological information

### Information on toxicological effects

Acute toxicity					
Conclusion/Summary	:	Very low	toxicity to humans	or animals.	
Irritation/Corrosion					
Conclusion/Summary Skin Eyes Respiratory <u>Sensitisation</u>	: :	The mixtu	are is not an irritant are is not an irritant available data, the o		re not met.
Conclusion/Summary Skin Respiratory	:			classification criteria a classification criteria a	
<b>Mutagenicity</b>					
Conclusion/Summary	:	Not appli	cable.		
<b>Carcinogenicity</b>					
Conclusion/Summary	:	Not classi	fied or listed by IA	RC, NTP, OSHA, EU	and ACGIH.
<u>Reproductive toxicity</u>					
Conclusion/Summary	:	Not appli	cable.		
<b>Teratogenicity</b>					
Conclusion/Summary	:	Not appli	cable.		
Specific target organ toxic Not available.	<u>ity (single expo</u>	osure)			
Specific target organ toxic Not available.	<u>ity (repeated e</u>	<u>xposure)</u>			
Aspiration hazard Not available.					
Information on the likely of exposure	routes :	Not availa	ıble.		
Version: 1.1	Date of issue/Date	of revision:	06.21.2016	Date of previous issue:	00.00.0000

### Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical,	chem	ical and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: irritation
Inhalation	:	redness Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact		No specific data.
Ingestion	:	No specific data.
Ingestion	•	No specific data.
Delaved and immediate effects and	also c	chronic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Very low toxicity to humans or animals.
General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	: : : : : : : : : : : : : : : : : : : :	No known significant effects or critical hazards. No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Route	ATE value
Oral	>5,000 mg/kg

# Section 12. Ecological information

Conclusion/Summary	:	No known significant effects or critical hazards.
Persistence and degradability		
Conclusion/Summary	:	No known significant effects or critical hazards.
Conclusion/Summary <u>Mobility in soil</u>	:	No known significant effects or critical hazards.
Soil/water partition coefficient (KOC)	:	Not available.
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.
RCRA classification	:	D001 (Ignitable)

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

FOR SHIPMENT IN CONSUMER PACKAGING	<u>GROUND</u>	<u>WATER</u>	AIR
PROPER SHIPPING NAME:	Aerosols, Flammable	Aerosols	Aerosols, Flammable

Version: 1.1

Date of issue/Date of revision: 06.21.2016

HAZARD CLASS:	2.1	2.1	2.1
UN/ID #:	UN1950	UN1950	UN1950
PACKING GROUP:	None	None	None
REQUIRED MARKINGS and/or LABELS:	$\diamondsuit$	$\diamond$	UN1950 Aerosols, Flammable
MARKINGS and/or LABEL TYPES:	Limited Quantity	Limited Quantity	Limited Quantity, Flammable Gas
ADDITIONAL INFORMATION:	ERG #126	ERG #126 Marine Pollutant: Not regulated	ERG #126 Proper Shipping Name & UN # must be shown on the package.

Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product have been trained in the event of an accident or spillage.'

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available.

# Section 15. Regulatory information

U.S. Federal regulations	<ul> <li>United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed</li> <li>United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed</li> <li>United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined</li> <li>United States - TSCA 8(a) - Dioxin/Furan precursor: Not listed</li> <li>United States - TSCA 8(a) - Chemical risk rules: Not listed</li> <li>United States - TSCA 8(a) - Chemical risk rules: Not listed</li> <li>United States - TSCA 6 - Proposed risk management: Not listed</li> <li>United States - TSCA 5(e) - Substances consent order: Not listed</li> <li>United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed</li> </ul>
	Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed
Version: 1.1	Date of issue/Date of revision:       06.21.2016       Date of previous issue:       00.00.0000

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - EPA Clean water act (CWA) section 307 -Priority pollutants: Not listed United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 -Accidental release prevention - Flammable substances: Listed United States - EPA Clean air act (CAA) section 112 -Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class	:	Not listed
II Substances		
<b>DEA List I Chemicals (Precursor</b>	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

### SARA 302/304

:

#### **Composition/information on ingredients**

Name	%	EHS	SARA 302/304
Isobutane	50 - 75	Yes.	SARA 304 RQ: 100 lb/lbs
Propane	10 - 25	Yes.	SARA 304 RQ: 100 lb/lbs
Alcohol	5 - 10	Yes.	SARA 304 RQ: 100 lb/lbs

SARA 304 RQ

: 141.7 lbs

:

### SARA 311/312

Classification

Fire hazard Sudden release of pressure

### **Composition/information on ingredients**

Version: 1.1 Date of issue/Date of revision: 06.21.2016

Date of previous issue: 00.00.0000

Name	%	Classification
Isobutane	50 - 75	F, P, CH
Propane	10 - 25	Р
Alcohol	5 - 10	F, CH

SARA 313 None of the components are listed.

State regulations		
Massachusetts	:	The following components are listed: Propane Isobutane Alcohol
New York	:	None of the components are listed.
New Jersey	:	The following components are listed: Propane Isobutane Alcohol
Pennsylvania	:	The following components are listed: Propane Isobutane Alcohol
<u>US California 22CCR Appendix X</u>	Subs	tances
Alcohol		
<u>California Prop. 65</u>	:	Not available.
United States inventory (TSCA 8b)	:	Exempted
Canada inventory	:	Not determined.
International regulations		
International lists	:	<ul> <li>Philippines inventory (PICCS): Not determined.</li> <li>New Zealand Inventory of Chemicals (NZIoC): Not determined.</li> <li>Korea inventory: Not determined.</li> <li>China inventory (IECSC): Not determined.</li> <li>Japan inventory: Not determined.</li> <li>Malaysia Inventory (EHS Register): Not determined.</li> <li>Taiwan inventory (CSNN): Not determined.</li> <li>Australia inventory (AICS): Not determined.</li> </ul>

<b>Chemical Weapons Convention</b>	:	Not listed
List Schedule I Chemicals		
- · · · · · · · · · · · · · · · · · · ·	:	Not listed
List Schedule II Chemicals		NT - 11 - 1
The second se	:	Not listed
List Schedule III Chemicals		

## Section 16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety. Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### History

110001		
Date of printing	: 06.21.20	16
Date of issue/Date of rev	ision : 06.21.20	16
Date of previous issue	: 04.06.20	16
Version	: 1.1	
Prepared by	: Global P	roduct Compliance
<b>1 0</b>	Unilever	Regulatory Affairs
	40 Merri	
		I, CT 06611
	USA	., 01 00011
	Con	
Key to abbreviations	ATE = Ac	cute Toxicity Estimate
Rey to abbie viations		American Conference of Governmental & Industrial Hygienists
		ite Hazard
	BCF = Bi	oconcentration Factor
	CAA = C	lean Air Act
	CARB = 0	California Air Resources Board
	CCR = Ca	alifornia Code of Regulations
		= Comprehensive Environmental Response, Compensation &
	Liability A	
		bede of Federal Regulations
		onic Hazard
		lean Water Act
		rug Enforcement Administration epartment of Transportation
		opean Commission
		Emergency Planning and Community Right-To-Know Act
		stern Standard Time
	F = Fire	som Sundura Hille
		Hazardous Air Pollutants
		azard Communication Standard
Version: 1.1	Date of issue/Date of revision:	06.21.2016 Date of previous issue: 00.00.0000

	HMIS = Hazardous Materials Information System
	HVOC = High Volatile Organic Compound
	GHS = Globally Harmonized System of Classification and Labelling of
	Chemicals
	IARC = International Agency for the Research of Cancer
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	ICAO = International Civil Aviation Organization
	IMDG = International Maritime Dangerous Goods
	IMO = International Maritime Organization
	ITC = Interagency Testing Committee (TSCA)
	KOC = Organic Carbon/Water Partition Constant
	LogPow = logarithm of the octanol/water partition coefficient
	LVOC = Low Volatile Organic Compound
	MARPOL $73/78$ = International Convention for the Prevention of Pollution
	From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
	pollution)
	MPPCF = Million Particles Per Cubic Foot
	N/A = Not Applicable
	NFPA = National Fire Protection Association
	NOEC = No Observable Effect Concentration
	NTP = National Toxicology Program
	OSHA = Occupation Safety & Health Administration
	PEL = Permissible Exposure Limit
	RCRA = Resource Conservation & Recovery Act
	RQ = Reportable Quantity
	RTK = Right-To-Know
	SARA = Superfund Amendments & Reauthorization Act
	STEL = Short-Term Exposure Limit
	TBD = To Be Determined
	TCC = Tagliabue Closed Cup
	TCLP = Toxicity Characteristic Leaching Procedure
	TDG = Transport of Dangerous Goods
	TLV = Threshold Limit Value
	TSCA = Toxic Substances Control Act
	TWA = Time Weighted Average
	UN = United Nations
:	Evaluation method used for mixture classification: Calculation
	method.
	moutou.

### References

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.