

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mat

**Product Name:** NeutraGreen™ Dry Mat

**Product Code:** 1728-54

### Intended Use of the Product

Formalin Neutralizer. For professional use only.

### Name, Address, and Telephone of the Responsible Party

#### **Company**

StatLab Medical Products

2090 Commerce Drive

McKinney, TX 75069

800-442-3573

[www.statlab.com](http://www.statlab.com)

### Emergency Telephone Number

**Emergency Number** : CHEMTREC 800-424-9300 (USA & Canada)

CHEMTREC 703-527-3887 (International)

Non-transport 800-225-8867 (USA)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

### Label Elements

#### **GHS-US Labeling**

#### **Hazard Pictograms (GHS-US)**



**Signal Word (GHS-US)** : Warning

**Hazard Statements (GHS-US)** : H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

**Precautionary Statements (GHS-US)** : P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - If on skin: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

#### **Other Hazards**

No additional information available

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Hydrogen chloride	(CAS No) 7647-01-0	1	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302

# NeutraGreen™

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

			Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 2, H401
--	--	--	--

Full text of H-phrases: see section 16

### SECTION 4: FIRST AID MEASURES

#### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Using proper respiratory protection, immediately move the exposed person to fresh air. . Keep at rest and in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

**Eye Contact:** Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

**Ingestion:** If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label. Rinse mouth.

#### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes skin irritation. Causes serious eye irritation.

**Inhalation:** May cause respiratory irritation.

**Skin Contact:** Causes skin irritation.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** Not available

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** None known.

#### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable.

**Explosion Hazard:** In contact with metals, emits flammable/explosive gas.

**Reactivity:** None known.

#### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not get water inside containers. Do not apply water stream directly at source of leak.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Chlorine gas. Hydrogen chloride. Sodium oxides.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

#### Reference to Other Sections

Refer to section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor or mist.

#### For Non-Emergency Personnel

**Protective Equipment:** Use recommended respiratory protection. Wear suitable protective clothing, gloves and eye/face protection.

**Emergency Procedures:** Stop leak if safe to do so. Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Use recommended respiratory protection. Wear suitable protective clothing, gloves and eye/face protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

# NeutraGreen™

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Environmental Precautions

Do not allow to enter drains or water courses. Avoid release to the environment.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Ventilate area. Collect absorbed material and place into a sealed, labelled container for proper disposal.

### Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Store away from other materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### Specific End Use(s)

For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

<b>Hydrogen chloride (7647-01-0)</b>		
Mexico	OEL Ceiling (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Mexico	OEL Ceiling (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	2 ppm
USA OSHA	OSHA PEL (Ceiling) (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	50 ppm
Alberta	OEL Ceiling (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup>
Alberta	OEL Ceiling (ppm)	2 ppm
British Columbia	OEL Ceiling (ppm)	2 ppm
Manitoba	OEL Ceiling (ppm)	2 ppm
New Brunswick	OEL Ceiling (mg/m <sup>3</sup> )	7.5 mg/m <sup>3</sup>
New Brunswick	OEL Ceiling (ppm)	5 ppm
Newfoundland & Labrador	OEL Ceiling (ppm)	2 ppm
Nova Scotia	OEL Ceiling (ppm)	2 ppm
Nunavut	OEL Ceiling (mg/m <sup>3</sup> )	7.5 mg/m <sup>3</sup>
Nunavut	OEL Ceiling (ppm)	5 ppm
Northwest Territories	OEL Ceiling (mg/m <sup>3</sup> )	7.5 mg/m <sup>3</sup>
Northwest Territories	OEL Ceiling (ppm)	5 ppm
Ontario	OEL Ceiling (ppm)	2 ppm
Prince Edward Island	OEL Ceiling (ppm)	2 ppm
Québec	PLAFOND (mg/m <sup>3</sup> )	7.5 mg/m <sup>3</sup>
Québec	PLAFOND (ppm)	5 ppm
Saskatchewan	OEL Ceiling (ppm)	2 ppm
Yukon	OEL Ceiling (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
Yukon	OEL Ceiling (ppm)	5 ppm

# NeutraGreen™

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Exposure Controls

**Appropriate Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Chemical resistant suit. Rubber apron, boots.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless
Odor	: Not available
Odor Threshold	: Not available
pH	: 4.8 - 5.2
Evaporation Rate	: Not available
Melting / Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Specific gravity / Relative density	: 1.08 - 1.12 g/ml
Solubility	: Soluble in water.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** None known.

**Chemical Stability:** Stable at standard temperature and pressure.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Extremely high or low temperatures.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Chlorine gas. Hydrogen chloride. Sodium oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

# NeutraGreen™

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Skin Corrosion/Irritation:** Causes skin irritation. (pH: 4.8 - 5.2)

**Serious Eye Damage/Irritation:** Causes serious eye irritation. (pH: 4.8 - 5.2)

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

### Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

Hydrogen chloride (7647-01-0)	
LD50 Oral Rat	238 - 277 mg/kg
LD50 Dermal Rabbit	> 5010 mg/kg
ATE US (dermal)	1,100.00 mg/kg body weight
Hydrogen chloride (7647-01-0)	
IARC Group	3

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

Hydrogen chloride (7647-01-0)	
LC50 Fish 1	3.25 - 3.5 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	4.92 mg/l (Exposure time: 48 h - Species: Daphnia magna)

**Persistence and Degradability** Not available

**Bioaccumulative Potential** Not available

**Mobility in Soil** Not available

**Other Adverse Effects** Not available

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

## SECTION 14: TRANSPORT INFORMATION

### In Accordance With ICAO/IATA/DOT/TDG

**14.1. UN Number** Not regulated for transport

**14.2. UN Proper Shipping Name** Not regulated for transport

**14.3. Additional Information** Not regulated for transport

**Transport by Sea** Not regulated for transport

**Air Transport** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

NeutraGreen™	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Hydrogen chloride (7647-01-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	500 (gas only)

# NeutraGreen™

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SARA Section 313 - Emission Reporting

1.0 % (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)

### US State Regulations

#### Hydrogen chloride (7647-01-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic  
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities  
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities  
U.S. - Delaware - Accidental Release Prevention Regulations - Toxic Endpoints  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Florida - Essential Chemicals List  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - Ceilings  
U.S. - Illinois - Toxic Air Contaminants  
U.S. - Louisiana - Reportable Quantity List for Pollutants  
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants  
U.S. - Massachusetts - Allowable Ambient Limits (AALs)  
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELEs)  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - Ceilings  
U.S. - Michigan - Polluting Materials List  
U.S. - Michigan - Process Safety Management Highly Hazardous Chemicals  
U.S. - Minnesota - Chemicals of High Concern  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - Ceilings  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)  
U.S. - New York - Occupational Exposure Limits - Ceilings  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Carolina - Control of Toxic Air Pollutants  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities  
U.S. - Ohio - Extremely Hazardous Substances - Threshold Quantities  
U.S. - Oregon - Permissible Exposure Limits - Ceilings  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour

# NeutraGreen™

## Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual  
 U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations  
 U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories  
 U.S. - Tennessee - Occupational Exposure Limits - Ceilings  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term  
 U.S. - Vermont - Permissible Exposure Limits - Ceilings  
 U.S. - Washington - Permissible Exposure Limits - Ceilings  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet  
 U.S. - Wyoming - Process Safety Management - Highly Hazardous Chemicals

### Canadian Regulations

#### NeutraGreen™

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects



#### Hydrogen chloride (7647-01-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects  
 Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 02/20/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H290	May be corrosive to metals
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

# NeutraGreen™


## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

H401

Toxic to aquatic life

- NFPA Health Hazard** : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard** : 0 - Materials that will not burn.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

- Health** : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability** : 0 Minimal Hazard
- Physical** : 0 Minimal Hazard

### Party Responsible for the Preparation of This Document

StatLab Medical Products  
Phone Number: 800-442-3573

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS