

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 083269 DRASTA 6801 S

Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

1. IDENTIFICATION

Product identifier

Product name DRASTA 6801 S

Other means of identification

Product Code(s) 083269

Number 705 Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Quenching. Oil.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc

1201 Louisiana Street, Suite 1800

Houston, TX 77002 Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300

Emergency telephone CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

Aspiration toxicity - Category 1

Label elements



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01



DANGER

May be fatal if swallowed and enters airways

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical PropertiesContaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Distillates (petroleum), solvent-dewaxed light	64742-56-9	90-95
paraffinic		
Distillates (petroleum), hydrotreated middle	64742-46-7	1-3

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

* The exact percentage (concentration) of composition has been withheld as a trade secret***

4. FIRST AID MEASURES



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse immediately with plenty of water and seek medical advice.

Skin contact Remove contaminated clothing and shoes. Wash off with soap and water. Wash

contaminated clothing before reuse.

Inhalation Move to fresh air.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If

swallowed, call a poison control center or doctor immediately.

Most important symptoms/effects, acute and delayed

Skin contact Not classified. May cause slight irritation.

Eve contact Not classified.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system. Aspiration into lungs can produce severe lung damage.

Ingestion May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and

pneumonitis. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Difficulty breathing. Coughing and/ or wheezing.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None. None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from

entering drains or water courses. Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for

disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in

well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges: Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measuresEnsure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical

contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid Strong oxidizing agents.



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Metalworking fluids:

USA: NIOSH (REL) TWA 0.5 mg/m³.

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. When working in

confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for

breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information If the product is used in mixtures, it is recommended that you contact the appropriate

protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/Face Protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protectionNone required under normal usage. If exposure limits are exceeded or irritation is

experienced, NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local

regulations.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

Color dark

Physical State @20°C liquid Odor Petrol

Odor Petroleum distillates
Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks</u> <u>Method</u>

pH Not applicable

Melting point/range No information available

Boiling point/boiling range Not applicable

Flash point 191 °C Cleveland Open Cup (COC) 375 °F Cleveland Open Cup (COC).

No information evallable

ISO 3104

Evaporation rateNo information available **Flammability Limits in Air**No information available

Vapor PressureNo information availableVapor densityNo information available

 Relative density
 0.863
 @ 15 °C
 ASTM D 1298

 Density
 863 kg/m³
 @ 15 °C
 ASTM D 1298

Water solubility Not applicable

Solubility in other solvents

No information available
logPow

No information available
No information available

Autoignition temperatureNo information availableDecomposition temperatureNo information availableViscosity, kinematic13 - 16 mm2/s@ 40 °C

Viscosity, kinematic 13 - 16 mm2/s
Explosive properties Not explosive
Oxidizing Properties Not applicable

Possibility of hazardous reactions Not applicable

Other information

Freezing Point No information available

Fire point 201.7 °C Cleveland Open Cup (COC)

10. STABILITY AND REACTIVITY

Reactivity No information available.

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

<u>Incompatible Materials</u> Strong oxidizing agents.

Hazardous Decomposition Products None under normal use.

11. TOXICOLOGICAL INFORMATION



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

Acute toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Numerical measures of toxicity

ATEmix (oral) 5256 mg/kg ATEmix (dermal) 5256 mg/kg

Inhalation

ATEmix (inhalation-dust/mist) 5.4 mg/l

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), solvent-dewaxed light paraffinic	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 > 2000 mg/kg bw (rat - OECD 402)	LC50 (4h) 5.53 mg/l (rat) LC50 (4h) 2.18 mg/l
64742-56-9	,	LD50 > 5000 mg/kg bw (rabbit)	(rat-aerosol-OECD 403)
Distillates (petroleum), hydrotreated middle 64742-46-7	LD50 > 5000 mg/kg bw (rat)	LD50 > 5000 mg/kg bw (rabbit)	LC50(4h) 1.78 mg/l (rat - aerosol)

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Difficulty breathing. Coughing and/ or wheezing.

Skin contact Not classified. May cause slight irritation.

Eye contact Not classified.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system. Aspiration into lungs can produce severe lung damage.

Ingestion May be fatal if swallowed and enters airways. Aspiration may cause pulmonary edema and

pneumonitis. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not classified as a sensitizer.

Carcinogenicity This product is not classified carcinogenic.

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum),	-	-		
solvent-dewaxed light				
paraffinic				
64742-56-9				



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

Mutagenicity This product is not classified as mutagenic.

Reproductive toxicityThis product does not present any known or suspected reproductive hazards.

Aspiration Hazard May be fatal if swallowed and enters airways. Risk of serious damage to the lungs (by

aspiration).

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), solvent-dewaxed light paraffinic 64742-56-9		LC50 (96h) > 5000 mg/l (Oncorhynchus mykiss) LL50 (96h) > 100 mg/l (Pimephales promelas - OECD 203)	EC50 (48h) > 1000 mg/l (Daphnia magna) LL50 (24h) > 10000 mg/l (Gammarus pulex - OECD 202)	e. gae.
Distillates (petroleum), hydrotreated middle 64742-46-7	EL50 (72h) 1.714 mg/l (Pseudokirchnerella subcapitata)	LL50(96h) 1.13 - 65 mg/l (Oncorhynchus mykiss)	EL50 (48h) 7.385 mg/l Daphnia magna	

Chronic aquatic toxicity - Product Information

No information available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), solvent-dewaxed light paraffinic 64742-56-9	NOEL (72h) >= 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	NOEL (21d) 10 mg/l (Daphnia magna - OECD 211) NOEL (96h) >= 10000 mg/l (Gammarus pulex - OECD 202)	NOEL (96h) >= 100 mg/l (Pimephales promelas - OECD 203)	
Distillates (petroleum), hydrotreated middle 64742-46-7	NOEL(14d) 0.069 mg/l (Oncorhynchus mykiss)	NOEL(21d) 0.163 mg/l (Daphnia magna)		

Effects on terrestrial organisms No information available.

Persistence and degradability

General Information No information available.



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), solvent-dewaxed light paraffinic 64742-56-9	3.1
Distillates (petroleum), hydrotreated middle 64742-46-7	4.1

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility

Air Loss by evaporation is limited

Water Insoluble The product spreads on the surface of the water.

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedMEXNot regulatedICAO/IATANot regulatedIMDG/IMONot regulatedADR/RIDNot regulated



Date of the previous version: 2015-05-07 Revision Date: 2015-10-13 Version 1.01

ADN Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Distillates (petroleum), solvent-dewaxed light paraffinic 64742-56-9	X			
Butylated Hydroxytoluene 128-37-0	Х	Х	X	



Date of the previous version: 2015-05-07 **Revision Date: 2015-10-13** Version 1.01

16. OTHER INFORMATION

Instability 0 Physical and chemical NFPA Health Hazard 1 Flammability 1

hazards -

Health Hazard 1 Personal protection X **HMIS** Flammability 1 Physical Hazard 0

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-10-13

Revision Note *** Indicates updated section

Abbreviations, acronyms

Legend Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive.lt is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet