



Material Safety Data Sheet

E-POX-EE KLEEN-ER

MSDS No. 7300

Date of Preparation: August 29, 2007

Revision: 0000

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: E-POX-EE KLEEN-ER

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042, and Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Composition / Information on Ingredients

Component	CAS Number	ACGIH STEL	OSHA STEL	Weight Percent (%)
Mineral Spirits	64742-47-8	100 ppm	100 ppm	50-55
Petroleum Distillate	Mixture	None Established	None Established	5-10
Fatty Acid Oil Mixture	Mixture	None Established	None Established	30-35

Section 3 - Hazards Identification

Inhalation: Over exposure by inhalation of vapors may cause respiratory irritation or nonspecific discomfort

HMIS	
H	2
F	2
R	0

Eye: Eye contact with liquid or vapor may cause irritation.

Ingestion: Ingestion is not considered a potential route of exposure

Carcinogenicity: This product contains no components listed as carcinogenic by IARC, NTP, and OSHA 1910(Z).

Chronic Effects: No chronic health effects known.

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air.

Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flash Point: 125°F (47.2°C)

Flash Point Method: TCC

Flammability Classification: Not Applicable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None



Section 5 - Fire-Fighting Measures (continued)

Fire-Fighting Instructions: Fire fighters should wear self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dike larger spills to minimize the contaminated area and facilitate salvage or disposal. Avoid run-off into storm sewers and ditches, which may lead to natural waterways. Material should be recovered, if possible or collected by absorbent materials such as dry clay, sand or sawdust.

Section 7 - Handling and Storage

Storage Requirements: Store in cool dry, well-ventilated area away from all sources of ignition.

Section 8 - Exposure Controls / Personal Protection

Protective Clothing/Equipment: Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Product Form: Liquid

Water Solubility: None

Appearance and Odor: Clear Liquid, Sweet odor

Boiling Point: None Determined)

Vapor Pressure: None Determined

Evaporation Rate None Determined

Vapor Density (Air=1): None Determined

(BuAc=1):

Specific Gravity: 0.78

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature.

Polymerization: Hazardous polymerization cannot occur.

Section 11- Toxicological Information

None Determined

Section 12 - Ecological Information

None Established

Section 13 - Disposal Considerations

Disposal: Contact your supplier.

Section 14 - Transport Information

DOT	IATA	IMDG
None	Shipping Name: Petroleum Distillate N.O.S. (Naphtha Solvent) UN #: 1268 Hazard Class: 3 Packing Group: III	Shipping Name: Petroleum Distillate N.O.S. (Naphtha Solvent) UN #: 1268 Hazard Class: 3 Packing Group: III

Section 15 - Regulatory Information

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): None

SARA Toxic Chemical (40 CFR 372.65) and SARA 313 Title III Codes: None

California Proposition 65: This product does not intentionally contain any chemicals, which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Section 16 - Other Information

Prepared By: Dominick J. Finocchio

Title: Technical Director

The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.