



# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### CHAMPION® MSDS 2010 SERIES ANTIFREEZE

**Synonyms:**

4118A, AN & F CHAMPION® ANTIFREEZE

**Company Identification**

Champion Brands, L.L.C., 1001 Golden Drive, Clinton, MO 64735

PHONE: 800-821-5693 WEBSITE: [www.championbrands.com](http://www.championbrands.com)

**CAS Registry Number**

Not Applicable

**Synonyms**

None

**Generic/Chemical Name**

Mixture

**Product Type**

Antifreeze

**Preparation Date**

October 23, 2007

**Transportation Emergency Response**

CHEMTREC: (800) 424-9300

**Product Information**

Product Information and MSDS Requests: (800) 821-5693 and [www.championbrands.com](http://www.championbrands.com)

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS	CAS NUMBER	AMOUNT
Ethylene Glycol	107-21-1	80.0 - 95.0 % weight
Diethylene glycol	111-46-6	0.0 – 5.0% weight
Dipotassium Phosphate	7758-11-4	1.0 – 2.0% weight
<ul style="list-style-type: none"><li>- HARMFUL OR FATAL IF SWALLOWED</li><li>- CAUSES EYE IRRITATION</li><li>- CONTAINS MATERIAL THAT MAY CAUSE ADVERSE REPRODUCTIVE EFFECTS BASED ON ANIMAL DATA</li><li>- POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL THAT MAY CAUSE BIRTH DEFECTS BASED ON ANIMAL DATA</li><li>- MAY CAUSE DAMAGE TO: KIDNEY</li></ul>		

## 3. HAZARD IDENTIFICATION

NFPA: HEALTH: 1

FLAMMABILITY: 1

REACTIVITY: 0

HMIS: HEALTH: 2

FLAMMABILITY: 1

REACTIVITY: 0

**IMMEDIATE HEALTH EFFECTS**

**Eye:** May cause slight transient (temporary) eye irritation. Corneal injury is unlikely. Vapors or mists may cause eye irritation.

**Skin:** Prolonged or repeated exposure not likely to cause significant skin irritation. A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. Repeated skin exposure may result in absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn skin may result in absorption of potential lethal amounts.

**Ingestion:** Single dose oral toxicity is considered to be moderate. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; however, swallowing amounts larger than that may cause serious injury, even death.

**Inhalation:** At room temperature, exposures to vapors are minimal due to physical properties; higher temperatures may generate vapor levels sufficient to cause adverse effects.



# MATERIAL SAFETY DATA SHEET

**Systemic (Other Target Organ) Effects:** Repeated excessive exposures may cause severe kidney and liver and gastrointestinal effects. Signs and symptoms of excessive exposure may be central nervous system effects. Signs and symptoms of excessive exposure may be nausea and/or vomiting. Signs and symptoms of excessive exposure may be anesthetic or narcotic effects. Observations in animals include formation of bladder stones after repeated oral doses of ethylene glycol. Reports of kidney failure and death in burn patients suggest the ethylene glycol may have been a factor. The use of topical applications containing this material may not be appropriate in severely burned patients or individuals with impaired renal function.

**Cancer Information:** Based on data from long-term animal studies, ethylene glycol is not believed to pose a carcinogenic risk to man.

**Teratology (Birth Defects):** Exposure to ethylene glycol has caused birth defects in laboratory animals only at doses toxic to the mother.

**Reproductive Effects:** Ethylene glycol has not interfered with reproduction in animal studies except at very high doses.

## DELAYED OR OTHER HEALTH EFFECTS:

**Effects of Repeated Overexposure:** Repeated inhalation of ethylene glycol mist may produce signs of central nervous system involvement, particularly dizziness and nystagmus.

**Other Effects of Overexposure:** repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material.

## 4. FIRST AID MEASURES

**Eyes:** Immediately flush eyes with large amounts of water for 15 minutes, lifting lower and upper lids. Get medical attention as soon as possible. Contact lenses should never be worn when working with this chemical.

**Skin:** Flush area of skin contact immediately with large amounts of water for at least 15 minutes while removing contaminated clothing. If irritation persists after flushing, get medical attention promptly. Wash clothing before re-use.

**Inhalation:** If inhaled, immediately remove victim to fresh air and call emergency medical care. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

**Ingestion:** Obtain medical attention immediately. If patient is fully conscious, give two glasses of water. Do not induce vomiting. If medical advice is delayed, and if the person has swallowed a moderate volume of material (a few ounces), then give three to four ounces of hard liquor, such as whisky. For children, give proportionally less liquor, according to weight.

**Notes to Physician:** It is estimated that the lethal oral dose to adults is of the order of 1.0 ml/kg. Ethylene glycol is metabolized by alcohol dehydrogenase to various metabolites including glyceraldehydes, glycolic acid and oxalic acid which cause an elevated anion-gap metabolic acidosis and renal tubular injury. The signs and symptoms in ethylene glycol poisoning are those of metabolic acidosis, CNS depression, and kidney injury. Urinalysis may show albuminuria, hematuria and oxaluria. Clinical chemistry may reveal anion-gap metabolic acidosis and uremia. The currently recommended medical management of ethylene glycol poisoning includes elimination of ethylene glycol and metabolites, correction of metabolic acidosis and prevention of kidney injury. It is essential to have immediate and follow up urinalysis and clinical chemistry. There should be particular emphasis on acid-base balance and renal function tests. A continuous infusion of 5% sodium bicarbonate with frequent monitoring of electrolytes and fluid balance is used to achieve correction of metabolic acidosis and forced diuresis. As a competitive substrate for alcohol dehydrogenase, ethanol is antidotal. Given in the early stages of intoxication, it blocks the formulation of nephrotoxic metabolites. A therapeutically effective blood concentration of ethanol is in the range 100-150 mg/dl, and should be achieved by a rapid loading dose and maintained by intravenous infusion. For severe and/or deteriorating cases, hemodialysis may be required. Dialysis should be considered for patients who are symptomatic, have severe metabolic acidosis, a blood ethylene glycol concentration greater than 25 md/dl, or compromise of renal functions.



# MATERIAL SAFETY DATA SHEET

A more effective intravenous antidote for physician use is 4-methylpyrazole, a potent inhibitor of alcohol dehydrogenases, which effectively blocks the formation of toxic metabolites of ethylene glycol. It has been used to decrease the metabolic consequences of ethylene glycol poisoning before metabolic acidosis coma, seizures, and renal failure have occurred. A generally recommended protocol is a loading dose of 15 mg/kg followed by 10 mg/kg every 12 hours for 4 doses and then 15 mg/kg every 12 hours until ethylene glycol concentrations are below 20 mg/100 ml. Slow intravenous infusion is required. Since 4-methylpyrazole is dialyzable, increased dosage may be necessary during hemodialysis. Additional therapeutic measures may include the administration of cofactors involved in the metabolism of ethylene glycol. Thiamine (100 mg) and pyridoxine (50 mg) should be given every six hours. eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get medical attention if irritation persists.

Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. The mechanism of production has not been elucidated, but it appears to be non-cardiogenic in origin in several cases. Respiratory support with mechanical ventilation and positive end expiratory pressure may be required. There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphasia.

## 5. FIRE FIGHTING MEASURES

### FIRE CLASSIFICATION:

OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible.

**NFPA RATINGS:** Health: 1 Flammability: 1 Reactivity: 0

### FLAMMABLE PROPERTIES:

**Flashpoint:** 119°C (247°F)

**Autoignition Temperature:** Autoignition temperature for ethylene glycol is 398°C (748°F).

**Flammability Limits - % of vapor concentration at which product can ignite in presence of spark.**

**Lower Flammability Limit:** 3.2%

**Upper Flammability Limit:** 15.3%

**Hazardous Combustion Products:** Hazardous combustion products may include and are not limited to carbon monoxide, carbon dioxide and trace amounts of aldehydes and organic acids. When available oxygen is limited, as in a fire or when heated to very high temperatures by a hot wire or plate, carbon monoxide and other hazardous compounds such as aldehydes might be generated.

**Extinguishing Media:** Water fog or fine spray. Alcohol resistant foams (ATC type) are preferred if available. General purpose synthetic foams (including AFFF) or protein foams may function, but much less effectively. Carbon dioxide. Dry chemical. Do not use direct water stream. May spread fire.

**Fire Fighting Instructions:** No fire and explosion hazards expected under normal storage and handling conditions (i.e. ambient temperatures). However, ethylene glycol or solutions of ethylene glycol and water can form flammable vapors with air if heated sufficiently. Keep people away. Isolate fire area and deny unnecessary entry.

**Protective Equipment for Fire Fighters:** Wear positive-pressure, self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves).

## 6. ACCIDENTAL RELEASE INFORMATION

**Protect People:** Material is moderately toxic when ingested. Take adequate precautions to keep people, especially children away from spill site. PVC-coated rubber gloves and monogoggles or face shield can be used during cleanup of spill site. Product on surfaces can cause slippery conditions. Practice reasonable care and cleanliness. Avoid breathing spray mists if generated. Keep out of reach of children. Product may become a solid at temperatures below -18°C (0°F). Do not store near food, foodstuffs, drugs or potable water supplies.

**Protect the Environment:** Do not dump used product or diluted material into sewers, on the ground, or into any body of water.



# MATERIAL SAFETY DATA SHEET

**Cleanup:** Small spills: Soak up with absorbent material. Large spills: Dike and pump into suitable containers for disposal. Ensure compliance with all applicable statutes that require notification of appropriate government officials. the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

## 7. HANDLING AND STORAGE

**General Handling Information:** Do not taste or swallow antifreeze or solution. Keep out of the reach of children and animals.

**General Storage Information:** Do not store in open or unlabeled containers. Keep out of reach of children. Product may become a solid at temperatures below -18°C (0°F). Do not store near food, foodstuffs, drugs or potable water supplies.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTIVE EQUIPMENT

### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

### ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**Respiratory Protection:** Respiratory protection is required if airborne concentration exceeds TLV. At any detectable concentration any self-contained breathing apparatus with a full face piece and operated in a pressure-demand or other positive pressure mode or any supplied-air respirator with a full face piece and operated in a pressure-demand or other positive pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode.

**Escape:** Any air-purifying full face piece respirator (gas mask) with a chin-style or front- or back-mounted organic vapor canister or any appropriate escape-type self-contained breathing apparatus.

**Skin Protection:** Protective gloves recommended when prolonged skin contact cannot be avoided. Polyethylene; Neoprene; Nitrile; Polyvinyl alcohol; Natural Rubber, Butyl Rubber. Safety shower should be available.

**Eye Protection:** Safety goggles and face shield. Emergency eyewash should be available. Contact lenses should not be worn when working with this chemical.

**Engineering Controls:** Use general or local exhaust ventilation to meet TLV requirements.

### Occupational Exposure Limits:

Component	Exposure Limits	Skin Form
Ethylene glycol	100 mg/m3 CEILING ACGIH	Aerosol
Ethylene glycol	125 mg/m3 CEILING OSHA-vacated	
	50 ppm CEILING OSHA – vacated	
	100 mg/m3 CEILING UCC	Aerosol and Vapor
Diethylene glycol	50 ppm TWA8 AIHA WEEL	Aerosol and Vapor
Diethylene glycol	10 mg/m3 TWA8 AIHA WEEL	Aerosol

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

Boiling Range: 171 - 175°C (339 - 348°F)



# MATERIAL SAFETY DATA SHEET

Freeze Point:	-18°C (0°F)
Specific Gravity (Water =1):	1.12
Pounds/Gallons:	9.3
Vapor Pressure (mm of Hg) @ 20C:	<0.1
Vapor Density (air=1):	2.1
Water Solubility:	Complete
Evaporation Rate (BuAc = 1):	Nil
% Volatile By Volume:	97.0
Appearance:	Green
Odor:	Mild
pH (50% Water Solution):	10.5-11.0

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. Keep away from flame

**Incompatibility With Other Materials:** Strong acid or oxidizing agents

**Hazardous Decomposition Products:** Incomplete combustion may produce CO gas

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

### IMMEDIATE HEALTH EFFECTS

**Skin:** The dermal LD50 has not been determined.

**Ingestion:** The lethal dose in humans is estimated to be 100 ml (3 ozs.). The oral LD50 for rats is in the 6000-13,000-mg/kg range.

**Mutagenicity (The Effects on Genetic Material):** In vitro mutagenicity studies were negative. Animal mutagenicity studies were negative.

**Significant Data with Possible Relevance to Humans:** Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. The no-effect doses for developmental toxicity for ethylene glycol given by gavage over the period of organogenesis has been shown to be 150 mg/kg/day for the mouse and 500 mg/kg/day for the rat. Also, in a preliminary study to assess the effects of exposure of pregnant rats and made to aerosol at concentrations of 150, 1000 and 25000 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentration, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol percutaneous absorption of ethylene glycol from contaminated skin, or swallowing ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1000 and 25000 mg/m<sup>3</sup>) and developmental toxicity with minimal evidence of teratogenicity (2500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen. There is currently no available information to suggest that ethylene glycol has caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity. Exposure to high aerosol concentrations is only minimally effective in producing developmental toxicity. The major route for producing developmental toxicity is perorally. Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous in vitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

A chronic dietary feeding study of diethylene glycol with rats showed mild kidney injury at 1%, while concentrations of 2% and 4% caused more marked kidney injury. In addition, at 2% and 4% of diethylene glycol in the diet, some rats developed benign papillary tumors in the urinary bladder. These have been attributed to the presence of urinary bladder calcium oxalate stones. No evidence for carcinogenicity was found with a chronic skin-painting study with diethylene glycol in mice. The absence of a direct chemical carcinogenic effect addords with the results in vitro





# MATERIAL SAFETY DATA SHEET

MSDS: CHAMPION® MSDS 2010 SERIES ANTIFREEZE

genotoxicity studies that show that it does not produce mutagenic or clastogenic effects. A feeding study employing up to 5.0% diethylene glycol in the diet failed to produce any teratogenic effects. In a mouse continuous breeding study with large doses of diethylene glycol in drinking water, there was evidence for reproductive toxicity at 3.5% (equivalent to 6.1 g/kg/day) as reduced number of litter, live pups per litter and live pup weight. No such effects were seen at 1.75% (approximately 3.05 g/kg/day). The relevance of these very high dosages to human health is uncertain. Pregnant rats receiving undiluted diethylene glycol by gavage over the period of organogenesis had toxic effects at 4.0 and 8.0 ml/kg/day as mortality, decreased body weight, decreased food consumption increased water consumption and increased liver and kidney weights. Fetotoxicity was seen only at these maternally toxic dosages. Decreased fetal body weight occurred at 8.0 ml/kg/day, and increased skeletal variants at 4.0 and 8.0 ml/kg/day. No embryotoxic or teratogenic effects were seen. Neither maternal toxicity nor fetotoxicity occurred at 1.0 ml/kg/day. In a study with mice also receiving undiluted diethylene glycol over the period of organogenesis, maternal toxicity occurred at 2.5 and 10.0 ml/kg/day, but not at 0.5 ml/kg/day. Definitive developmental toxicity was not seen in this species.

## ACUTE TOXICITY

- Peroral:** The lethal dose in humans is estimated to be 3 oz. or 100 ml.  
Rat: LD50 (6000 – 13000) mg/kg
- Percutaneous:** Rabbit: LD50 = >22270 mg/kg; 24 h occluded
- Inhalation:** Rat: 8-hour exposure, substantially saturated vapor studies, dynamic generation method  
Mortality: 0/6
- Inhalation:** Mist/vapor study, rat, at 170°C, 8-hour exposure = 2.2 mg/l  
Mortality: 0/6
- Inhalation:** Rat: 8-hour exposure, fog = 10000 ppm; 65° - 70°C  
Mortality: 0/6

## IRRITATION

- Skin:** Rabbit: 24-hour occluded contact, 0.5 ml  
Results: Minor erythema and edema
- Skin:** Human: Primary irritation patch test, 48-hour occluded, 0.2 ml  
Results: Evidence of irritation
- Eye:** Rabbit: 0.1 ml  
Results: Minor transient iritis, conjunctival irritation with discharge

## REPEATED EXPOSURE

In a 7-day dietary study with rats, a significant increase in kidney weights in females was observed at 5.0 gm/kg. The NOEL was 2.5 gm/kg.

In a 24-month dietary study with rats, increased mortality in males was observed at the highest dose, 1.0 gm/kg/day. There were multiple signs: mineralization of several organs, including the cardiac vessels, cardiac muscle, vas deferens, stomach and pulmonary vessels; cellular hyperplasia of the parathyroids, hemosiderosis of the spleen, myocardial fibrosis, portal fibrosis of the liver, bile duct hyperplasia and hydronephrosis and oxylate nephrosis of the kidneys. Ethylene glycol was not oncogenic.

In a 90-day dietary study with dogs, repeated exposures to 2.5 gm/kg resulted in acute renal failure and deaths. The NOAEL was 1.0 gm/kg.

## SENSITIZATION (ANIMAL AND HUMAN STUDIES)

Repeated skin contact with ethylene glycol may, in a very small proportion of cases, cause sensitization with the development of allergic contact dermatitis. The incidence is significantly less than 1% with the undiluted material.

## REPRODUCTIVE TOXICITY

A three-generation study indicated that ethylene glycol did not affect reproductive parameters at dietary concentrations up to 1.0 gm/kg/day in any generation.

## CHRONIC TOXICITY AND CARCINOGENICITY

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of a carcinogenic potential for ethylene glycol has been supported by numerous in vitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

## GENETIC TOXICOLOGY

**In Vitro:** Ethylene glycol was devoid of genotoxic activity in an Ames test, forward gene mutation and sister chromatid exchange (SCE) studies in Chinese Hamster Ovary (CHO) cells and an in vitro cytogenetics study.



# MATERIAL SAFETY DATA SHEET

**In Vivo:** Ethylene glycol by three different routes (intravenous, peroral and percutaneous) demonstrates apparent first-order pharmacokinetic behavior for the disposition in and the elimination from the plasma. Dose-dependent changes occur for the elimination of metabolites in the urine and as  $^{14}\text{CO}_2$  after single doses for the intravenous and peroral, but not the percutaneous route. The hypothesis from literature sources exists that developmental toxicity is caused by a metabolite of ethylene glycol, called glycolic acid, and not parent ethylene glycol. Under most conditions of ethylene glycol exposure, the glycolic acid metabolite is present in the blood in very low levels. However, it can become the major metabolite following large doses of ethylene glycol due to saturation of glycolic acid oxidation and/or elimination. When levels of this acidic metabolite exceed the capacity of maternal blood buffers to neutralize it, a maternal metabolic acidosis ensues, which has been hypothesized to be the true agent responsible for ethylene glycol induced developmental toxicity. Research suggests that ethylene glycol developmental toxicity is due to a dose-rate dependent toxicokinetic shift leading to glycolate accumulation and metabolic acidosis.

## ADDITIONAL STUDIES

Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. The no-effect doses for developmental toxicity for ethylene glycol given by gavage over the period of organogenesis has been shown to be 150 mg/kg/day for the mouse and 500 mg/kg/day for the rat. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations of 150, 1000 and 2500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentration, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1000 and 2500 mg/m<sup>3</sup>) and developmental toxicity with minimal evidence of teratogenicity (2500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen. There is currently no available information to suggest that ethylene glycol has caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity. Exposure to high aerosol concentrations is only minimally effective in producing developmental toxicity.

## 12. ECOLOGICAL INFORMATION

### ENVIRONMENTAL FATE

**Movement & Partitioning:** Bioconcentration potential is low (BCF less than 100 or Log Kow less than 3). Log octanol/water partition coefficient (log Kow) is -1.36. Henry's Law Constant (H) is 6.0E-08 atm-m<sup>3</sup>/mol. Bioconcentration factor (BCF) is 10 in golden orfe.

**Degradation & Transformation:** Biodegradation under aerobic static laboratory conditions is high (BOD<sub>20</sub> or BOD<sub>28</sub>/ThOD greater than 40%). 5-Day biochemical oxygen demand (BOD<sub>5</sub>) is 0.78 p/p. 10-Day biochemical oxygen demand (BOD<sub>10</sub>) is 1.06 p/p. 20-Day biochemical oxygen demand (BOD<sub>20</sub>) is 1.15 p/p. Theoretical oxygen demand (THOD) is calculated to be 1.29 p/p. Biodegradation may occur under both aerobic and anaerobic conditions (in either the presence or absence of oxygen). Inhibitory concentration (IC<sub>50</sub>) in OECD "Activated Sludge, Respiration Inhibition Test" (Guideline # 209) is < 1000 mg/L. Degradation is expected in the atmospheric environment within days to weeks.

**Ecotoxicology:** Material is practically non-toxic to aquatic organisms on an acute basis (LC<sub>50</sub> greater than 100 mg/L in most sensitive species). Acute LC<sub>50</sub> for fathead minnow (*Pimephales promelas*) is 51000 mg/L. Acute LC<sub>50</sub> for bluegill (*Lepomis macrochirus*) is 27549 mg/L. Acute LC<sub>50</sub> for rainbow trout (*Oncorhynchus mykiss*) is about 18000-46000 mg/L. Acute LC<sub>50</sub> for guppy (*Poecilia reticulata*) is 49300 mg/L. Acute LC<sub>50</sub> for water flea (*Daphnia magna*) is 46300-51100 mg/L. Acute LC<sub>50</sub> for the cladoceran *Ceriodaphnia dubia* is 10000-25800 mg/L. Acute LC<sub>50</sub> for crayfish is 91430 mg/L. Acute LC<sub>50</sub> for brine shrimp (*Artemia salina*) is 20000 mg/L. Acute LC<sub>50</sub> for golden orfe (*Leuciscus idus*) is greater than 10000 mg/L. Acute LC<sub>50</sub> for goldfish (*Carassius auratus*) is greater than 5000 mg/L. Growth inhibition EC<sub>50</sub> for green alga *Selenastrum capricornutum* is 9500-13000 mg/L.



# MATERIAL SAFETY DATA SHEET

## BOD (% Oxygen Consumption):

Day 5	Day 10	Day 15	Day 20	Day 30
51%	80%		97%	

## ECOTOXICITY

### Toxicity to Micro-organisms:

Bacterial / NA: 16 h; IC50  
Result Value: >10000 mg/l

### Toxicity to Aquatic Invertebrates:

Daphnia: 48 h; LC50  
Result Value: >100000 mg/l

### Toxicity to Fish

Fathead Minnow: 94 h; LC50  
Result Value: 70000 mg/l

## FURTHER INFORMATION

Chemical Oxygen Demand (COD) – Measured: 1.29 mg/mg  
Theoretical Oxygen Demand (THOD) – Calculated: 1.30 mg/mg  
Octanol/Water Partition Coefficient – Measured: -1.36

## 13. DISPOSAL INFORMATION

DO NOT discharge to sewer. Wear appropriate personal protection. Take up with sand, vermiculite, or similar inert material. Dispose in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**U.S. DEPARTMENT OF TRANSPORTATION:** Non-Bulk is not regulated by the US D.O.T. (in quantities under 5,000 lbs in any one inner package)

**IATA:** Non-Bulk is not regulated by IATA

**IMDG:** Non-Bulk is not regulated by IMDG (in quantities under 5,000 lbs in any one inner package)

## 15. REGULATORY INFORMATION

### THIS PRODUCT CONTAINS COMPONENT(S) CITED ON THE FOLLOWING REGULATIONS.

<b>Chemical Name</b>	<b>Cas Number</b>
Ethylene Glycol	107-21-1

**United States – TSCA Inventory:** Listed

**Water Standards:** No data available

**Atmospheric Standards: Clean Air Act (1990) - List of Hazardous Air Contaminants:** listed

**CERCLA: Reportable Quantity (RQ):** 5,000 pounds (532 gallons)

**OSHA Hazard Communication Standard:** This product is a "hazardous chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SARA Title III: Section 311/312 - Categories:** Acute hazard; chronic hazard

**Section 312 - Inventory Reporting:** Ethylene glycol is subject to Tier I and/or Tier II annual inventory reporting.

**Section 313 - Emission Reporting:** Ethylene glycol is subject to Form R reporting requirements.

**Section 302 - Extremely Hazardous Substances:** Ethylene glycol is not listed.

### CHEMICAL INVENTORIES:

#### State Right-To-Know:

Director's List of Hazardous Substances: listed





# MATERIAL SAFETY DATA SHEET

**Florida - Hazardous Substances List:** listed  
**Massachusetts - Right-to-Know List:** listed  
**Minnesota - Haz. Subs. List:** listed (particulate and vapor)  
**New Jersey - Right-to-Know List (Total):** Present greater than 1.0%  
**Pennsylvania Right-to-Know List:** environmental hazard  
**California - Exposure Limits - Ceilings:** vapor-50 ppm ceiling; 125 mg/m<sup>3</sup> ceiling  
**California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):** The normal consumer use of this product does not result in exposure to chemicals known to the state of California to cause Cancer and/or reproductive harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Warnings are not required for consumer packaging. However, industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.  
**California SCAQMD Rule 443.1 (South Coast Air Quality Management District Rule 443.1, Labeling of Materials Containing Organic Solvents):** **VOC:** Vapor pressure 0.06 mmHg at 20°C, 1113.38 g/l

**Canadian Regulations:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required.

**WHMIS Information:** D2A - material has potential toxic effects. Refer elsewhere in the MSDS for specific warnings and safe handling information. Refer to the employer's workplace education program.

## 16. DISCLAIMER

**REVISION STATEMENT:** Revision updates many sections and the MSDS should be read in its entirety.

**ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:**

TLV	-	Threshold Limit Value	TWA	-	Time Weighted Average
STEL	-	Short-term Exposure Limit	PEL	-	Permissible Exposure Limit
CHA	-	Champion LLC	CAS	-	Chemical Abstract Service Number
NDA	-	No Data Available	NA	-	Not Applicable
<=	-	Less Than or Equal To	>=	-	Greater Than or Equal To

Prepared according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the ANSI MSDS Standard (Z400.1) by Champion LLC, 1001 Golden Drive, Clinton, Missouri 64735.

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best knowledge of Champion Brands, L.L.C. Champion Brands, L.L.C., makes no warranty whatsoever expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Champion Brands, L.L.C., assumes no legal responsibility for use or reliance upon this data. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.