The following SDS references the product below:

<u>Dynatex® 49661 Disc Brake Quiet</u> Vendor Item Number: 49661PK10

Manufactured By:

Dynatex, Inc.

Distributed by Kimball Midwest with the KM productidentification number:

<u>80-157</u>



# **Safety Data Sheet**

# Dynatex® 49661 Disc Brake Quiet

#### Section 1. Identification

Product Identifier Dynatex® 49661 Disc Brake Quiet

Synonyms 49661PK10 Manufacturer Stock 49661PK10

Numbers

Recommended use Refer to Technical Data
Uses advised against Refer to Technical Data

Manufacturer Contact

Address Dynatex Inc. 350 Ring Road

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax (270) 769-3385 (800) 424-9300 N/A

CHEMTREC

## Section 2. Hazards Identification

Classification HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category

3

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2

Signal Word Warning Pictogram

Hazard Statements Harmful to aquatic life

May cause damage to organs (kidneys, liver, blood) through prolonged or

repeated exposure.

**Precautionary Statements** 

Response Get medical advice/attention if you feel unwell.

Prevention Avoid release to the environment

Do not breathe dust/fume/gas/mist/ vapors/spray.

Storage

Disposal Dispose of contents/container in accordance with local/regional/national

regulations.

Ingredients of unknown

toxicity

78.06%

Hazards not Otherwise

Classified

Additional Information None known

### Section 3. Ingredients

CAS	Ingredient Name	Weight %
111-42-2	Diethanolamine	0.3% - Max
107-21-1	Ethylene Glycol	1% - 3%
102-71-6	Triethanolamine	1% - 3%
7732-18-5	Water	20% - 30%

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First-Aid Measures

**Eye Contact** Immediately flush with water for 15 minutes. Seek medical attention.

Skin Contact Wash affected area throughly with soap and water. Remove contaminated

clothing and launder before re-use. Get medical attention if irritation develops.

Ingestion Seek medical attention. Induce vomiting.

Inhalation Remove patient to fresh air. Administer oxygen if breathing is difficult. Get

medical attention if symptoms persist.

# Section 5. Fire Fighting Measures

Suitable Extinguishing Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Media

Unsuitable Extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

Media

Special Fire Fighting

Remove containers from fire area if possible. Use self-contained breathing

apparatus for fire-fighting.

Unusual Fire or Explosion None known

Hazards

**Products** 

**Procedures** 

Hazardous Decomposition Thermal breakdown of this product during fire or very high heat conditions may

evolve the following hazardous decomposition products:

Carbon Dioxide

#### Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Soak up with inert absorbent. Store in a partly filled, closed container until disposal. Prevent product from entering drains. Local, state and federal regulations may apply to releases and disposal of this material, as well as those materials and items employed in cleanup of releases.

## Section 7. Handling and Storage

Storage Store in a cool, dry place.

### Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Diethanolamine	N/A	N/A	N/A
	Ethylene Glycol	50 mg/m3	40 ppm	40 ppm
	Triethanolamine	N/A	N/A	N/A
	Water	0	N/A	N/A

Personal Protective

Equipment

Goggles, Gloves

Eye Protection

Safety goggles or glasses with side shields are recommended.

Skin Protection

Wear chemically protective gloves. Use splash apron and boots if splashing

occurs.

Ventilation

Should be adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below exposure limits. If working in a

confined space, follow applicable OSHA regulations.

Respiratory Protection

Use NIOSH/MSHA compliant respirators or self-contained breathing

apparatus above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

### Section 9. Physical and Chemical Properties

Semi-solid		
paste		
Red		
Acrylic		
Not available		
Dispersible		
in water		
Not available		
0.7% 7.29g/L		
0.06 lbs/gal		
Not available		

Specific Gravity	1.03
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	None
FP Method	TCC
Ph	Not available
Melting Point	-74.2F -59C
	estimated
Boiling Point	212F 100C
	estimated
Boiling Range	N/A
LEL	0.7
UEL	15.3
Evaporation Rate	Slow
Flammability	Not available
Decomposition Temperature	Not available
Auto-ignition Temperature	700F 371.1C
	estimated
Vapor Pressure	12.1 hPa
	estimated
Vapor Density	Not available

Note

The above information is not intended for use in preparing product specifications. Contact SOUDAL Accumentric before writing specifications.

# Section 10. Stability and Reactivity

Chemical Stability Stable
Hazardous Polymerization
Conditions to Avoid None known

Materials to Avoid / Incompatibility

Avoid contact with strong oxidizing agents.

## Section 11. Toxicological Information

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure.

## Section 12. Ecological Information

Environmental Effects Complete information is not yet available. Fate and Effects in Waste Complete information is not yet available.

Water Treatment Plants
Environmental Fate and

Complete information is not yet available.

Distribution

#### Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this

product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the

requirements of all applicable statutes.

This material if discarded may be hazardous under US EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not

dump into sewers, on the ground or into any body of water.

## Section 14. Transport Information

**UN Number** N/A UN Proper Shipping Name N/A

**DOT Classification** Not regulated as dangerous goods.

**Packing Group** N/A

Road Shipment Not subject to DOT regulations.

Information (DOT)

ICAO/IATA Class: 2.1 Air Shipment (IATA)

UN/ID Number: 1950

Label: 2.1

Packaging Group: -

Proper Shipping Name: AEROSOLS, flammable, n.o.s.

Ocean Shipment (IMDG) Not subject to IMDG code.

## Section 15. Regulatory Information

**TSCA Status** All chemical substances found in this product comply with the Toxic

Substances Control Act inventory reporting requirements.

California Proposition 65 This product contains the following chemical(s) listed by the State of California

under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: A chemical or chemicals known to the State of California to cause cancer, birth

defects or other reproductive harm may be present in this product.

SARA Title III Section 302

Extremely Hazardous

Substances

None

SARA Titre III Section 304

CERCLA Substances

dangereuses

None

SARA Title III Section 312

Hazard Class

Acute: Yes Chronic: Yes

Fire: No Pressure: No Reactive: No

SARA Title III Section 313

**Toxic Chemicals** 

None present or none present in regulated quantities.

New Jersey Ethylene glycol (107-21-1)
Pennsylvania Ethylene glycol (107-21-1)

## Section 16. Other Information

Revision Date

6/11/2015

Disclaimer

The data contained herein is based upon information that SOUDAL Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.