

FLEX TILE LTD
Material Safety Data Sheet
210 CONTRACT GRADE CERAMIC TILE ADHESIVE

MANUFACTURER:

ONTARIO

121-30th Street,

Etobicoke, ON.

M8W 3C1

Tel: (416) 255-1111

FAX: (416) 255-1729

IN CASE OF EMERGENCY.

FLEX TILE LTD.

QUEBEC

555, Rue locke

Ville St. Laurent, QC

H4T 1X7

Tel: (514) 345-6666

FAX: (514) 345-8825

CALL CANUTEC (613) 996-6666

BRITISH COLUMBIA

2829 Lake City Way

Burnaby, BC

V5A 2Z6

Tel: (644) 420-4914

FAX: (604) 420-0936

PRODUCT IDENTIFIER.....

Material Identification

WHMIS CLASSIFICATION.....

210 CONTRACT GRADE CERAMIC TILE ADHESIVE

NOT CONTROLLED

Hazardous Ingredients of Materials

CHEMICAL IDENTITY CONC. CAS#/NA#/UN# LD(50) LC(50)
 THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENT AS DEFINED BY US OSHA HAZARD COMMUNICATION STANDARD - 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT.
 All ingredients are listed within or exempted from US TSCA and Canadian DSL.

Physical Data For Product

PHYSICAL STATE.....	VISCOUS LIQUID
ODOUR AND APPEARANCE.....	OFF-WHITE PASTE, MILD ODOUR.
ODOUR THRESHOLD.....	N/D
SPECIFIC GRAVITY.....	1.3 - 1.4
VAPOUR PRESSURE.....	N/D
VAPOUR DENSITY (air=1).....	N/D
EVAPORATION RATE.....	AS FOR WATER
BOILING POINT.....	100°C
FREEZING POINT.....	N/D
pH.....	8 - 9
DENSITY (g/ml).....	N/D
CALCULATED VOC CONTENT	< 22 gm/litre

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	STABLE
MEANS OF EXTINCTION.....	WATER, CO ₂
FLASHPOINT AND METHOD OF DETERMINATION.....	N/D
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D
AUTO-IGNITION TEMPERATURE.....	N/D
FLAMMABILITY CLASSIFICATION.....	NON-FLAMMABLE PASTE
HAZARDOUS COMBUSTION PRODUCTS.....	N/D
EXPLOSION DATA.....	NON-EXPLOSIVE
SENSITIVITY TO STATIC DISCHARGE...	N/D

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	N/D
CONDITIONS TO AVOID.....	N/D
HAZARDOUS DECOMPOSITION PRODUCTS..	CO, CO ₂ AND FUMES.
HAZARDOUS POLYMERIZATION.....	WILL NOT OCCUR

210 CONTRACT GRADE CERAMIC TILE ADHESIVE

Toxicological Properties of Product

ROUTES OF ENTRY

SKIN CONTACT.....	MAY CAUSED IRRITATION ON PROLONGED CONTACT.
SKIN ABSORPTION.....	N/D.
EYE.....	MAY CAUSE IRRITATION.
INHALATION.....	MAY CAUSE HEADACHE AND NAUSEA.
INGESTION.....	MAY CAUSE DISCOMFORT.
ACUTE OVER EXPOSURE EFFECTS.....	AS ABOVE
CHRONIC OVER EXPOSURE EFFECTS.....	N/D
EXPOSURE LIMITS.....	N/D
IRRITANCY OF PRODUCT.....	N/D
SENSITIZATION TO MATERIAL.....	N/D
CARCINOGENICITY, REPRODUCTIVE EFFECTS.....	N/D
TERATOGENICITY, MUTAGENICITY.....	N/D
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT.....	RUBBER GLOVES.
VENTILATION.....	USE LOCAL (EXHAUST) VENTILATION.
LEAK AND SPILL PROCEDURES.....	ABSORB WITH PAPER, SAND OR SAWDUST. PLACE IN A CONTAINER.
WASTE DISPOSAL.....	DISCARD OR DISPOSE OF WASTE IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL & FEDERAL REGULATIONS.
HANDLING PROCEDURES AND EQUIPMENT.	AVOID EYE AND SKIN CONTACT.
STORAGE REQUIREMENTS.....	PROTECT FROM FREEZING.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

First Aid Measures

SPECIFIC FIRST AID PROCEDURES..... FLUSH EYES WITH ABUNDANT WATER. WASH SKIN WITH SOAP AND WATER.
IN CASE OF INGESTION, SEEK MEDICAL ATTENTION.

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	CHIEF CHEMIST
PHONE NUMBER OF PREPARER.....	(416) 255-1111 FAX: (416) 255-1729
DATE PREPARED.....	26 Oct., 2016

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

...FLEX TILE LTD.

N/D = NOT DETERMINED