



MATERIAL SAFETY DATA SHEET

Page 1 of 6
MSDS-E-S100L-UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/19/2007

1. PRODUCT IDENTIFICATION		CHEMICAL RESPONSE CARD: 03			
1.1	Product Name:	DeoxIT® SHIELD S100L-UV	RESPONSE		
1.2	Chemical Name:	See ingredients listed in section 3	TEAM PPE:		
1.3	Synonyms:	DeoxIT® SHIELD S100L-UV	WHMIS:		
1.4	Trade Names:	DeoxIT® SHIELD S100L-UV (see list below)	HEALTH:		0
1.5	Product Use:	Protect & lubricate electronic contacts & connectors	FLAMMABILITY:		0
1.6	Manufacturer's Name:	CAIG Laboratories, Inc.	REACTIVITY:		0
1.7	Manufacturer's Address:	12200 Thatcher Court, Poway, CA 92064-6876	PERSONAL PROTECTION:		
1.8	Business Phone:	+1 (800)-224-4123			
1.9	Emergency Phone:	CHEMTREC +1 (703) 527-3887 / +1 (800) 424-9300			
1.10	Other Product Names:	DeoxIT® SHIELD S100L-UV, 2 ml (Part No. S100L-UV-2C, S100L-UV-2CP) DeoxIT® SHIELD S100L-UV, 7.4 ml (Part No. S100L-UV-2DB) DeoxIT® SHIELD S100L-UV, 12 ml (Part No. S100L-UV-12C) DeoxIT® SHIELD S100L-UV, 25 ml (Part No. S100L-UV-25C) DeoxIT® SHIELD PEN, 7 ml (Part No. D100P) DeoxIT® SHIELD WIPES, (Part Nos. D50W, K-D1W-25, K-D1W-50, D1W) DeoxIT® SHIELD S100L-UV, 59 ml (Part No. S100L-UV-2) DeoxIT® SHIELD S100L-UV, 236 ml (Part No. S100L-UV-8) DeoxIT® SHIELD S100L-UV, 472 ml (Part No. S100L-UV-16) DeoxIT® SHIELD S100L-UV, 944 ml (Part No. S100L-UV-32) DeoxIT® SHIELD S100L-UV, 30 L (Part No. S100L-UV-8G)			

2. HAZARD IDENTIFICATION

2.1	Hazard Identification: This product is NOT classified as a HAZARDOUS SUBSTANCE or as DANGEROUS GOODS according to the classification criteria of [NOHSC: 1088 (1999)] and ADG Code (Australia). DeoxIT® SHIELD S100L-UV is non-volatile, non-hazardous and non-flammable.						
2.2	Routes of Entry:	Inhalation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure: EYES: Non-irritating when used as directed. Can cause irritation, tearing, and temporary blurred vision. SKIN: Non-irritating when used as directed. Prolonged or repeated contact may cause temporary contact dermatitis (localized redness or rash). INGESTION: Not probable. Small amounts if swallowed may cause temporary gastrointestinal irritation. INHALATION: Unlikely route of exposure. Should vapor concentrations exceed recommended exposure levels, they are temporary irritating to the eyes, nose, throat, and the respiratory tract; may cause temporary headaches and dizziness.						
2.4	Symptoms of Overexposure: EYES: Non-irritating when used as directed. Can cause temporary irritation, tearing, and blurred vision. SKIN: Non-irritating when used as directed. Prolonged or repeated contact may cause temporary contact dermatitis (localized redness or rash). INGESTION: Not probable. Small amounts if swallowed may cause temporary gastrointestinal irritation. INHALATION: Unlikely route of exposure. Should vapor concentrations exceed recommended exposure levels, they are temporary irritating to the eyes, nose, throat, and the respiratory tract; may cause headaches and dizziness.						
2.5	Acute Health Effects: EYES: None reported when used as directed. Mild to moderate temporary irritation. SKIN: Unlikely when used as directed. Repeated exposure at site of contact may cause temporary contact dermatitis (localized redness or rash). INGESTION: Not probable. Small amount may cause temporary gastrointestinal irritation and central nervous system depression. INHALATION: Unlikely route of exposure. Should vapor concentrations exceed recommended exposure levels, they are temporary irritating to the eyes, nose, throat, and the respiratory tract; may cause headaches and dizziness.						
2.6	Chronic Health Effects: None reported by the manufacturer.						
2.7	Target Organs: Eyes and skin.						

NA = Not Available; ND = Not Determined; NE = Not Established; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used
NOTE: all WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format.



MATERIAL SAFETY DATA SHEET

Page 2 of 6
MSDS-E-S100L-UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 11/19/2007

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)					
					ACGIH		OSHA			OTHER
					TLV ppm	STEL ppm	PEL ppm	STEL ppm	IDLH ppm	
DeoxIT® SHIELD S100L-UV	Trade Secret	UNK	UNK	100	NE	NE	NE	NE	NE	
UV Tracer Dye	Trade Secret	UNK	UNK	>0.1	NE	NE	NE	NE	NE	

4. FIRST AID MEASURES

4.1	<p>First Aid:</p> <p>EYES: Flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If irritation persists, seek immediate medical attention.</p> <p>SKIN: Remove contaminated clothing and wash affected areas with soap and water. If irritation persists, seek prompt medical attention. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p>INGESTION: Do not induce vomiting! Drink plenty of water. If irritation persists, contact a physician.</p> <p>INHALATION: Remove victim to fresh air at once. If breathing is difficult, administer supplemental oxygen and seek immediate medical attention. If breathing stops, perform artificial respiration.</p>										
4.2	<p>Medical Conditions Aggravated by Exposure: None reported by the manufacturer.</p> <table border="1" style="float: right;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: yellow;">REACTIVITY</td> <td style="text-align: center;">0</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td style="text-align: center;">A</td> </tr> <tr> <td>EYES</td> <td></td> </tr> </table>	HEALTH	0	FLAMMABILITY	0	REACTIVITY	0	PROTECTIVE EQUIPMENT	A	EYES	
HEALTH	0										
FLAMMABILITY	0										
REACTIVITY	0										
PROTECTIVE EQUIPMENT	A										
EYES											

5. FIREFIGHTING MEASURES

5.1	Flashpoint & Method: > 250 °C (482 °F)
5.2	Autoignition Temperature: NA
5.3	Flammability Limits: Lower Explosive Limit (LEL): ND Upper Explosive Limit (UEL): ND
5.4	Fire & Explosion Hazards: Carbon dioxide, carbon monoxide, hydrocarbons.
5.5	Extinguishing Methods: CO₂, Alcohol foam, Dry Chemical, Water Fog
5.6	Firefighting Procedures: Wear NIOSH/MSHA approved self-contained breathing apparatus and protective clothing. Use a water spray to cool containers involved in fire. Do not use direct water stream. Container storage areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Keep containers cool until well after the fire is out to prevent rupture. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills: Ventilate if in enclosed area. Secure spill area, remove or minimize all sources of ignition, and maximize ventilation. Wipe and rinse with water. Deny entry to all unprotected individuals. Individuals involved in the cleanup must wear appropriate personal protective equipment.
-----	--



MATERIAL SAFETY DATA SHEET

Page 3 of 6
MSDS-E-S100L-
UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards

MSDS Revision: 2.0

MSDS Revision Date: 11/19/2007

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices: Wash hands thoroughly after using this product and before eating, drinking, or smoking. Remove soiled clothing to prevent prolonged skin contact.
7.2	Storage & Handling: Use and store in a cool, dry, well-ventilated area. Do not store near or with any incompatible materials listed in section 10. Open containers may change concentrations, keep tightly closed when not in use. Normal shelf life 2-3 years.
7.3	Special Precautions: Empty containers may contain product residues.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Ventilation & Engineering Controls: Use with adequate ventilation (e.g., open doors and windows, local exhaust ventilation). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).
8.2	Respiratory Protection: None required, when used with adequate ventilation.
8.3	Eye Protection: Wear safety glasses with side shields (ANSI Z87) under normal use conditions.
8.4	Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. In such cases, wear rubber or impervious plastic gloves.
8.5	Body Protection: Use as necessary to prevent skin contact.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Density:	0.72
9.2	Boiling Point:	> 220 °C (428 °F)
9.3	Melting Point:	NA
9.4	Evaporation Rate:	NA
9.5	Vapor Pressure:	< 0.01 mm Hg @ 20 °C (68 °F)
9.6	Molecular Weight:	NA
9.7	Appearance & Color:	Light blue
9.8	Odor Threshold:	Ethereal/hydrocarbon odor
9.9	Solubility:	Not soluble in water
9.10	Ph	NA
9.11	Viscosity:	5.4 – 7.5 cSt @ 104 °F
9.12	VOC (g/L):	None
9.13	Other Information:	NA

10. STABILITY & REACTIVITY

10.1	Stability:	Stable under normal conditions of use (see section 7).
10.2	Hazardous Decomposition Products:	Change in color signifies exposure to ultraviolet light or exceeding shelf life. Will not degrade to unstable products. Discard solution.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Use or storage near open flames, sparks, high heat (>100 °F) or other heat sources, and proximity to incompatible substances and heavily trafficked areas.
10.5	Incompatible Substances:	Strong oxidizers.



MATERIAL SAFETY DATA SHEET

Page 4 of 6
MSDS-E-S100L-UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 11/19/2007

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data:	This product has not been tested on animals to obtain toxicological data. There are toxicology data for the components of this product, which are found in the scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity:	See section 3.5
11.3	Chronic Toxicity:	See section 3.6
11.4	Suspected Carcinogen:	NE
11.5	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not reported to produce teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to produce reproductive effects in humans.
11.6	Irritancy of Product:	See Section 3.3
11.7	Biological Exposure Indices:	NE
11.8	Physician Recommendations:	Treat symptomatically.

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds.
12.2	Effects on Plants & Animals:	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	Releases of large volumes of this product are expected to be harmful or fatal to overexposed aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with federal, state or local regulations.
13.2	Special Considerations:	NA

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	NOT REGULATED
14.2	IATA (AIR):	NOT REGULATED
14.3	IMDG (OCN):	NOT REGULATED
14.4	TDGR (Canadian GND):	NOT REGULATED
14.5	ADR/RID (EU):	NOT REGULATED

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	NA
15.2	SARA Threshold Planning Quantity:	NA
15.3	TSCA Inventory Status:	All chemical substances of this product are listed on the TSCA inventory or are otherwise exempt from inventory status.
15.4	CERCLA Reportable Quantity (RQ):	NA
15.5	Other Federal Requirements:	NA



MATERIAL SAFETY DATA SHEET



Page 5 of 6
MSDS-E-S100L-UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards



MSDS Revision: 2.0

MSDS Revision Date: 11/19/2007

15. REGULATORY INFORMATION- continued

15.6	<p>Other Canadian Regulations</p> <p>This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.</p>	
15.7	<p>State Regulatory Information:</p> <p>The primary component of this product is not listed on the following state lists: California OSHA; California Proposition 65; Massachusetts Right to Know List of Chemicals; New Jersey Right to Know List 8:59 Appendix A; Pennsylvania Hazardous Substances List 34 323 Appendix A; Wisconsin Hazardous Substances List NR 605.09; Minnesota Hazardous Substances List; and Florida Toxic Substances List.</p>	
15.8	<p>67/548/EEC (European Union) Requirements:</p> <p>The primary component of this product is not listed in Annex I of EU Directive 67/548/EEC.</p>	

16. OTHER INFORMATION

16.1	<p>Other Information:</p> <p>NA</p>	
16.2	<p>Terms & Definitions:</p> <p>See page last page of this MSDS.</p>	
16.3	<p>Disclaimer:</p> <p>This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.</p>	
16.4	<p>Prepared for:</p> <p>CAIG Laboratories, Inc. 12200 Thatcher Court Poway, CA 92064-6876 +1 (800) CAIG-123 (244-4123) phone +1 (858) 486-8398 fax http://www.caig.com/</p>	
16.5	<p>Prepared by:</p> <p>ShipMate, Inc. 18436 Hawthorne Blvd., Suite 201 Torrance, CA 90504 +1 (310) 370-3600 phone +1 (310) 370-5700 fax http://www.shipmate.com/</p>	



MATERIAL SAFETY DATA SHEET

Page 6 of 6
MSDS-E-S100L-UV

Prepared to OSHA, ACC, ANSI, WHMIS, NOHSC & 2001/58 EC Standards | MSDS Revision: 2.0 | MSDS Revision Date: 11/19/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
----------------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health


FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
------------	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or S.O.P. for special handling directions.



OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD₁₀, LD₁₀, & LD₀ or TC, TC₀, LC₁₀, & LC₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL_m	Median threshold limit
log K_{ow} or log K_{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)

EC INFORMATION:

C	E	F	N	O	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful