

**SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****Company Address:**8125 Cobb Center Drive  
Kennesaw, GA 30152Product Information: 800-TECH-401  
Customer Service: 800-645-5244Emergency: (Chemtrec) 800-424-9300  
Revision Date: November 27, 2007**Product Identification****Pow-R-Wash® Cable Cleaner****Product Code: ES2425****SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Wt. % Range
Aliphatic hydrocarbons	64742-48-9	35.0-65.0
Aliphatic hydrocarbons	64742-47-8	35.0-65.0
Carbon dioxide	124-38-9	1.0-10.0

**SECTION 3: HAZARD IDENTIFICATION**

**Emergency Overview:** Clear, colorless liquid with mild hydrocarbon odor. This product is flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product may produce drowsiness and a headache.

**Potential Health Effects:**

**Eyes:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

**Skin:** Contact may cause skin irritation.

**Ingestion:** Harmful if swallowed. Irritating to the mouth, throat and stomach. May cause vomiting. Aspiration into the lungs may cause mild to severe pulmonary injury and possibly death.

**Inhalation:** Harmful if inhaled in high concentrations. Vapors can displace oxygen and cause dizziness, unconsciousness and even death, with longer exposure.

**Pre-Existing Medical Conditions Aggravated by Exposure:** Heart, lung, skin, eye.

**SECTION 4: FIRST AID MEASURES**

**Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

**Skin:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**Ingestion:** If swallowed, do not induce vomiting. Keep head below knees to minimize chance of aspirating material into the lungs. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**Flash Point:** 144° F (62C) TCC      **Flame extension** > 18 inches      **LEL/UEL:** 0.6 / 4.5 (% by volume in air)

**Extinguishing Media:** Use alcohol foam, carbon dioxide or water spray when fighting fires involving this material.

**Fire Fighting Instructions:** As in any fire, wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH approved or equivalent) and full protective gear.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Large Spills:** Shut off leak if possible and safe to do so. Wear a self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (i.e. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches that lead to waterways.

**Small Spills:** Absorb spill with inert material (i.e. dry sand or earth), then place in a chemical waste container for proper disposal.

**SECTION 7: HANDLING AND STORAGE**

Avoid prolonged or repeated contact with skin, eyes or clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor. Do not reuse this container. Store in a cool dry place, away from heat, sparks or flames. Do not store in direct sunlight.

**KEEP OUT OF REACH OF CHILDREN.****SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines:**

CHEMICAL NAME	ACGIH TLV	OSHA PEL	ACGIH STEL	OTHER
Aliphatic hydrocarbons	NA	NA	NA	300 ppm (Exxon)

**Work/Hygienic Practices:** Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields, goggles and rubber or other chemically resistant gloves when handling this material.

**NFPA and HMIS Codes:**

	NFPA	HMIS
Health	1	1
Flammability	2	2
Reactivity	1	1
Personal Protection	-	B

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Physical State:** Clear, colorless liquid

**Odor:** Mild hydrocarbon solvent

**pH:** NA

**Vapor Pressure:** 0.8 mmHg @ 68 F (liquid)

**Vapor Density:** 5.9 (Air 1)

**Boiling Point:** 372F to 405F (189C to 207C)

**Solubility in Water:** Negligible

**Specific Gravity:** 0.78 @ 68F

**Evaporation Rate:** 0.4

(Butyl acetate=1)

**Percent Volatile:** 100%

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** This product is stable. **Conditions to Avoid:** Do not spray near open flames, red hot surfaces or other sources of ignition.

**Incompatibility:** Do not mix powdered alkali and alkaline earth metals or strong oxidizing agents.

**Products of Decomposition:** Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.

**Hazardous Polymerization:** Will not occur. **Conditions to avoid:** NA

**SECTION 11: TOXICOLOGICAL INFORMATION**

**Inhalation:**

Not available

**Skin:**

Aliphatic hydrocarbons LD50 rabbit >3.16 g/kg

\*Information from manufacturer

**Cancer Information:** No ingredients listed as human carcinogens by NTP or IARC

**Reproductive effects:** none **Teratogenic effects:** none

**Ingestion:**

Aliphatic hydrocarbons LD50 rat >5000 mg/kg

**Eyes:**

Aliphatic hydrocarbons SL irritant

**Mutagenic effects:** none

**SECTION 12: ECOLOGICAL INFORMATION****Environmental Impact Information**

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

**REPORTING**

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: **1-800-424-8802**

**SECTION 13: DISPOSAL CONSIDERATION**

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

**SECTION 14: TRANSPORTATION INFORMATION**

Proper Shipping Name	UN Number	Class	Sub. Risk	Pkg. Group	Hazard Label	Pkg. Instr.	Max. Quantity
<u>Air:</u> Aerosols flammable	UN 1950	2.1	NA	NA	Flammable Gas	203	75/150kg
<u>Ground:</u> Consumer Commodity ORM-D	ORM-D NA		NA	ORM-D	Pkg. 173.306	Auth.	

**SECTION 15: REGULATORY INFORMATION**

**SECTION 313 SUPPLIER NOTIFICATION** This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

This information should be included on all MSDSs copied and distributed for this material.

**TOXIC SUBSTANCES CONTROL ACT (TSCA).** All ingredients of this product are listed on the TSCA Inventory.

**WHMIS:** Class A; Class B3; Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**SECTION 16: OTHER INFORMATION**

This is a Level 3 aerosol. Do not puncture or incinerate containers. Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.