

J.P. Nissen Co. 2544 Fairhill Avenue P.O. Box 339 Glenside, PA 19038 Phone: 215-886-2025 Fax: 215-886-0707

Emergency: 1-800-424-9300

# Material Safety Data Sheet January 5, 2011 Product Identification NISSEN JUMBO FELTIP PAINT MARKER – WHITE NISSEN NYLON TIP FELTIP PAINT MARKER FINE LINE – WHITE MARKER

HMIS Ratings- Health 1 Flammability 3 Reactivity 1
NFPA Ratings- Health 1 Flammability 3 Reactivity 0

<u>Hazardous ingredients</u> – The paint is contained in a valve action reservoir and will not leak under normal conditions.

<u>Ingredients</u>	CAS#	<u>%</u>	Exposure Limits
1-Methoxy-2-Propanol Acetate	108-65-6	1-10	No Data
Xylol (Xylene)	1330-20-7	40-50	100 ppm/8 hrs pel
Titanium Dioxide	13463-67-7	30-40	5 mg/cu.m Respirable dust
Ethyl Benzene	100-41-4	1-10	100 ppm

## **Physical Data**

**Boiling point**:282 F **Vapor density**: Heavier than air. **Volatile %**: 66.7% by volume **Specific gravity**: Less than 1.

Evaporation rate: Slower than Ethyl Ether Vapor Pressure: 6.2 mm hg @ 20 deg. C

Appearance: Black viscous liquid with an aromatic odor.

Volatile Organic Compounds data not required because product only produced in quantities of less that 1 liter

**Fire and Explosion Data** 

Flammability Class: IC Flashpoint: 76 deg.F LEL:1% UEL 13.1%

**Extinguishing Media:** Foam, Carbon dioxide, or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

# **Health Hazard Data**

Listed as possible carcinogen: NTP - No IARC - OSHA - No

Symptoms of over exposure: Headache, Dizziness, Nausea, Coughing, Eye, Throat and Skin Irritation.

Effects of overexposure: Slight to severe irritation to eyes and mucous membranes. Dermatitis.

Affects central nervous system.

Emergency first aid: Inhalation; seek fresh air. Give artificial respiration if not breathing.

Skin contact; Wash with soap and water. Ingestion; Call Physician. Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs

#### **Reactivity Data**

Stability: Stable, hazardous polymerization: Will not occur.

**Conditions to avoid**: Heat, open flames and sparks. **Incompatibility**: Do not expose to strong oxidizers.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

#### **Environmental Protection Procedures**

Remove all sources of ignition, ventilate area, and use absorbent material to clean spills. Disposal method: Dispose of waste in accordance with all local, state and federal regulations.

## **Control Measures**

**Respiratory protection**: None required under normal use.

Ventilation: Normal-working conditions.

Protective Equipment: Safety glasses and gloves. No special clothing required under normal

conditions of use. Transportation

Shipping Class ORM-D UN Number 1263 Package Group III

# **Toxic Substances Control Act TSCA States:**

All components of this product are listed in the EPA's Inventory of Chemical Substances as required under the Toxic Substances Control Act (TSCA)

For more information visit: http://www.nissenmarkers.com/