

Prepared according to Global Harmonized System (GHS) standards

SECTION 1

CHEMICAL PRODUCT IDENTIFICATION

Polaris Sales Inc. 2100 Highway 55 Medina, MN 55340 Tel: 763-542-0500

Product Trade Name:

Polaris Long Life Antifreeze -Concentrate

CAS Number:
Synonyms/Other:
Recommended Use:
Restrictions on Use:
Created Date:
Preparation/Revision Date:
Emergency Phone Number:
SDS CODE:

Mixture N/A Antifreeze Not Determined 4/3/2019 4/3/2019 1-800-424-9300 (CHEMTREC) 14966

SECTION 2

HAZARD IDENTIFICATION

Appearance:	Flourescent Green/Yellow
Odor:	Sweet
Classification:	Acute Toxicity - oral category 4
	Reproductive toxicant category 2
Target Organs:	Lungs, Reproductive
Pictogram(s):	$\mathbf{A}\mathbf{A}$
Signal Word:	WARNING
Hazard Statement:	H302 - Harmful if swallowed
	H361 - Suspected of damaging fertility or the unborn child
Other Hazards:	Not determined.
Prevention:	P201 - Obtain special instructions before use
	P202 - Do not handle until all safety precautions have been read and understood
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray
	P263 - Avoid contact during pregnancy/while nursing
	P264 - Wash hands thoroughly after handling
	P270 - Do not eat, drink or smoke when using this product
	P281 - Use personal protective equipment as required
Response:	P330 - Rinse mouth
	P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel
	unwell
	P308+P313 - IF exposed or concerned: Get medical advice/attention
Storage Procedures:	P405 - Store locked up
Disposal:	P501 - Dispose of contents and container in accordance with federal, state, and local
	regulations
Other:	See section 11 for complete health hazard information.

Safety Data Sheet Polaris Long Life Antifreeze - Concentrate Revision Date: 4/3/19

ENGINEERED LUBRICANTS

P&LARIS

SECTION 3

COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)
Ethylene Glycol	107-21-1	80 - 95%
Potassium 2-Ethylhexanoate	3164-85-0	1-10%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

SECTION 4	FIRST AID MEASURES
SECTION 4	PIKST AID WEASURES
Eye Contact:	If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.
Skin Contact:	Call a doctor if you feel unwell.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	Rinse mouth. Call a doctor if you feel unwell.
Other:	If exposed or concerned: Get medical advice/attention (carcinogen).
SECTION 5	FIRE FIGHTING MEASURES
Flack Daint	100°C by Clausiand Open Cup Tester
Flash Point:	>100°C by Cleveland Open Cup Tester.
Flammable limits:	Not applicable.
Extinguishing media:	Not applicable. : General directions - product will not burn without driving water from material first.
ороли	Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.
Unusual fire & explosion	High temperatures may create heavy flammable vapors that may settle along ground
hazards:	level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist areas.
Other:	Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
SECTION 6	ACCIDENTAL RELEASE MEASURES
Spill control procedures (land):	Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner

(800-424-9300).

that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec

PALARIS	Safety Data Sheet Polaris Long Life Antifreeze - Concentrate Revision Date: 4/3/19
Spill control procedures (water):	Try to contain large spills with floating booms to prevent spill from spreading. Remove from surface by skimming or with suitable adsorbents. If a large spill occurs notify appropriate authorities (normally the National Response Center or Coast Guard at 800-424-8802).
Waste disposal method:	Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.
Other:	CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.
SECTION 7	HANDLING AND STORAGE
Handling procedures:	Keep containers closed when not in use. Do not transfer to unmarked containers. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse. Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.
Storage procedures:	Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.
Additional information:	No additional information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits/standards for materials that can be formed when handling this product:

Component	CAS Number	OSHA PEL	ACGIH TLV
Ethylene Glycol	107-21-1	N/A	N/A
Potassium 2-Ethylhexanoate	3164-85-0	N/A	N/A

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

 Personal protection:
 Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

 Respiratory protection:
 None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910 134 and ANSL 788.2 requirements must be followed. Where

meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

Eye protection:Eye protection is strongly recommended. Wear safety glasses with side shields or
vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection:Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin
sensitization and absorption.

Other protection:Use of an apron and overboots of chemically impervious materials such as neoprene or
nitrile rubber is recommended based on level of activity and exposure. If handling hot
material use insulated protective equipment. Launder soiled clothes. Properly dispose of
contaminated leather articles and other materials which cannot be decontaminated.



Safety Data Sheet Polaris Long Life Antifreeze - Concentrate Revision Date: 4/3/19

ENGINEERED LUBRICANTS

SECTION 9

Other:

Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.

Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Flourescent Green/Yellow
Odor:	Sweet
Odor threshold:	Not determined.
pH:	8.5
Melting/Freezing point:	Not determined.
Initial boiling point:	>100°C.
Boiling range:	Not determined.
Flash point:	>100°C.
Evaporation rate:	Not determined.
Flammability:	Non-flammable
Upper flammable limit:	Non-flammable
Lower flammable limit:	Non-flammable
Vapor pressure:	Not determined.
Vapor density:	Not determined.
Relative density:	1.1
Solubility:	Miscible in water, negligible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	Not determined.
Other	Not applicable.

SECTION 10

STABILITY AND REACTIVITY

Reactivity	
Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating
Other:	vapors. Not applicable.



ENGINEERED LUBRICANTS

SECTION 11

TOXICOLOGICAL INFORMATION

Acute toxicity (LD50) *See note at the bottom of the section

Acute toxicity (LD50) "See note	at the bottom of the section
Oral:	300 - 2000 mg/kg
Dermal:	>5000 mg/kg
Inhalation:	>20.0 mg/l
Skin irritation:	Non-irritant
Eye irritation:	Non-irritant
Dermal sensitization:	Not expected to have a sensitizing effect.
Respiratory sensitization:	Not expected to have a sensitizing effect.
Aspiration Hazard:	Not applicable
Chronic Toxicity	
Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Suspected of damaging fertility or the unborn child.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	Not expected to have long term adverse effects.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

SECTION 12

ECOLOGICAL INFORMATION

Environmental toxicity		
Fish:	> 100 mg/l.	
Invertebrates:	> 100 mg/l.	
Aquatic plants:	> 100 mg/l.	
Microorganism:	> 100 mg/l.	
Persistence/Degradability:	This product is not expected to be readily biodegradable.	
Bioaccumulation:	Not determined.	
Mobility in soil:	Not determined.	
Other:	All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.	

SECTION 13

DISPOSAL CONSIDERATIONS

Waste disposal: This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.
 Other The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.



ENGINEERED LUBRICANTS

SECTION 14

TRANSPORT INFORMATION

Land Transport (DOT): Proper Shipping Name:	UN 3082 UN3082 Environmentally hazardous substances, liquid, n.o.s. (Contains Ethylene Glycol), 9, III
Land Transport (TDG):	Not regulated for land transport.
Proper Shipping Name:	Not applicable.
Sea Transport (IMDG):	Not regulated for sea transport.
Proper Shipping Name:	Not applicable.
Air Transport (IATA):	Not regulated for air transport.
Proper Shipping Name:	Not applicable.
Other:	Non Bulk: Not regulated by the US D.O.T. (in quantities under 5,000 lbs in any one inner package).

SECTION 15

REGULATORY INFORMATION

Federal Regulation			
Clean water act/oil:	No components of this product are listed.		
TSCA:	All components of this material are listed in the U.S. TSCA Inventory.		
Other TSCA:	Not applicable.		
SARA title III:	Section 302/304 extremely hazardous substances:		
	None.		
	Section 311, 312 hazard categorization:		
	Acute (immediate health effects):	YES	
	Chronic (delayed health effects):	YES	
	Fire (hazard):	NO	
	Reactivity (hazard):	NO	
	Pressure (sudden release hazard):	NO	
	Section 313 toxic chemicals:		
	No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.		
CERCLA:	For stationary/moving sources - reportable quantity (due to): Not hazardous due to the		
State Regulations	petroleum exclusion.		
Right-to-know	Not determined.		
•			
Other:	A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial civil and criminal penalties.		

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

P&LARIS

ENGINEERED LUBRICANTS

OTHER INFORMATION SECTION 16 NFPA 704 NPCA-HMIS KEY HEALTH: 1 0 = Minimal1 FIRE: 1 1 1 = Slight2 = Moderate **REACTIVITY:** 0 0 SPECIFIC HAZARD: None N/A 3 =Serious 4 = Severe **PROTECTION INDEX:** N/A В Version: L

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None. 04/03/19

Internal use only: WB5-KJ