

MSDS Name: DEVCON® 5 Minute® Epoxy amber

[1:1]

Manufacturer Name: ITW Devcon

Stock No.: 14210

Components:

5-MINUTE EPOXY HARDENER
5-MINUTE EPOXY RESIN

ITW Performance Polymers (Finished Goods) Product Code: 14210

View Section: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: 5-MINUTE EPOXY RESIN

Manufacturer Name: ITW Devcon

Address: 30 Endicott Street
Danvers, MA 01923

MSDS Revision Date: 10/10/2006

Emergency telephone number (800) 424-9300

HMIS



^{*} Chronic Health Effects:

In the US, call CHEMTREC: (800) 424-9300

To Top of page

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	
Bisphenol A diglycidyl ether resin	25068-38-6	60 - 100 by Weight

To Top of page

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Potential Sensitizer. Irritant.

Primary Routes of Exposure: Potential Health Effects: Eyes. Skin. Inhalation. Ingestion.

roteiltiai Healtii Ellet

Eye Contact: Can cause moderate irritation, burning sensation, tearing, redness, and swelling.

Overexposure may cause lacrimation, conjunctivitis, corneal damage and

permanent injury..

Skin Contact: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

Allergic reactions are possible.

May cause skin sensitization, an allergic reaction, which becomes evident on

reexposure to this material.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and

anesthetic effects. May cause respiratory sensitization with asthma-like

symptoms in susceptible individuals.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal

tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening,

swelling, and possible tissue destruction

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

Conditions:

Individuals with pre-existing skin disorders, asthma, allergies or known

sensitization may be more susceptible to the effects of this product.

To Top of page

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure

adequate flushing of the eyes by separating the eyelids with fingers. Get

immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while

removing contaminated clothing and shoes. Get medical attention if irritation

develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give

oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

To Top of page

SECTION 5: FIRE FIGHTING MEASURES

Auto Ignition Temp: Not determined. Flash Point: >400°F (204.4°C)

Flash Point Method: Pensky-Martens Closed Cup

Lower Explosive Limit (LEL) Not determined. Upper Explosive Limit (UEL) Not determined.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this

Protective Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand,

MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space

without full protective gear. If possible, contain fire run-off water.

Unsuitable Media: Water or foam may cause frothing.

To Top of page

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering

the spill area.

Spill Cleanup Measures: Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical

waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue.

Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper

personal protective equipment as listed in section 8. Avoid runoff into storm sewers, ditches, and waterways.

Other Precautions:

Pump or shovel to storage/salvage vessels.

To Top of page

SECTION 7: HANDLING AND STORAGE

Environmental Precautions:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Storage:

Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition

products (see Section 10) during welding/flame cutting operations and to protect

against dust during sanding/grinding of cured product.

To Top of page

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below

recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin

contact. Consult manufacturer's data for permeability data.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard

EN 166.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not

provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

and a deluge shower safety station.

Notes: Only established PEL and TLV values for the ingredients are listed below.

To Top of page

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State/Appearance: Viscous Liquid.

Color: Clear.
Odor: slight odor
Boiling Point: >500°F (260°C)
Melting / Freezing Point: Not determined.
Solubility: negligible
Specific Gravity: 1.17

pH: Neutral.

Vapor Density: >1 (air = 1)

Vapor Pressure: 0.03 mmHg @171°F

Molecular Formula: Mixture
Molecular Weight: Mixture
Percent Volatile: 0
VOC Data: 0 g/L
Percent Solids by Weight 100

To Top of page

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and

oxidizing conditions. Heating resin above 300 F in the presence of air may cause

slow oxidative decomposition.

Incompatibilities with Other

Materials:

Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and

organic bases (especially primary and secondary aliphatic amines).

Hazardous Polymerization: Not reported.

To Top of page

SECTION 11: TOXICOLOGICAL INFORMATION

Bisphenol A diglycidyl ether resin:

Skin Effects: Skin - rat LD: >2 gm/kg - [Nutritional and Gross Metabolic - other changes]

(RTECS)

Ingestion Effects: Oral - Rat LD: >5 gm/kg - [Nutritional and Gross Metabolic - other changes]

(RTECS)

To Top of page

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

To Top of page

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: None

To Top of page

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.

DOT UN Number: N/A

DOT Hazard Class: Not applicable.

DOT Packing Group: Not applicable.

IATA Shipping Name: Non regulated.

To Top of page

SECTION 15: REGULATORY INFORMATION

Bisphenol A diglycidyl ether resin:

TSCA Inventory Status Listed

EC Num: 603-074-00-8

Canadian Regulations. WHMIS Hazard Class(es): D2B

All components of this product are on the Canadian Domestic Substances List.

To Top of page

SECTION 16: ADDITIONAL INFORMATION

HMIS Health Hazard: 2*
HMIS Fire Hazard: 1
HMIS Reactivity: 1
HMIS Personal Protection: x

MSDS Revision Date: 10/10/2006

Disclaimer: "This Health and Safety Information is correct to the best of our knowledge and

belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within

a controlled environment."

Copyright© 1996-2007 Actio Software Corporation. All Rights Reserved.

View Section: 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: 5-MINUTE EPOXY HARDENER

Manufacturer Name: ITW Devcon
Address: 30 Endicott Street
Danvers, MA 01923

10/10/2006

MSDS Revision Date: 10/10/2006

Emergency telephone number (800) 424-9300

HMIS



Chronic Health Effects:

In the US, call CHEMTREC: (800) 424-9300

To Top of page

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Trade secret. N/A 60 - 100 by Weight

To Top of page

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: WARNING! Potential Sensitizer. Irritant.

Primary Routes of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye Contact: Can cause severe eye irritation and burns. Eye contact may cause permanent

damage or blindness.

Skin Contact: Causes severe skin irritation. May cause permanent skin damage. Allergic

reactions are possible.

May cause skin sensitization, an allergic reaction, which becomes evident on

reexposure to this material.

Inhalation: Vapor or mist may cause severe respiratory system irritation. May cause

respiratory sensitization with asthma-like symptoms in susceptible individuals.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal

tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening,

swelling, and possible tissue destruction

Signs/Symptoms: Overexposure may cause eye watering or discomfort, redness and swelling.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Individuals with pre-existing skin disorders, asthma, allergies or known

Conditions: sensitization may be more susceptible to the effects of this product.

To Top of page

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure

adequate flushing of the eyes by separating the eyelids with fingers. Get

immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while

removing contaminated clothing and shoes. Get medical attention if irritation

develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give

oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center

immediately. Never give anything by mouth to an unconscious person.

To Top of page

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Class III B.

Auto Ignition Temp: Not determined.

Flash Point: >200°F (93.3°C)

Flash Point Method: Pensky-Martens Closed Cup

Lower Explosive Limit (LEL) Not determined.
Upper Explosive Limit (UEL) Not determined.

Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this

material.

Protective Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand,

MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire

exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

Unsuitable Media: Water or foam may cause frothing.

To Top of page

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering

the spill area.

Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical

waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area

with soap and water to remove trace residue.

Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper

personal protective equipment as listed in section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Other Precautions: Pump or shovel to storage/salvage vessels.

To Top of page

SECTION 7: HANDLING AND STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Storage: Store in a cool, dry, well ventilated area away from sources of heat and

incompatible materials. Keep container tightly closed when not in use. Do not

store in reactive metal containers. Keep away from acids, oxidizers.

Hygiene Practices: Wash thoroughly after handling.

Special Handling Procedures: Provide appropriate ventilation/respiratory protection against decomposition

products (see Section 10) during welding/flame cutting operations and to protect

against dust during sanding/grinding of cured product.

To Top of page

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust

ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training,

inspection and maintenance of the personal protective equipment.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin

contact. Consult manufacturer's data for permeability data.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR

1910.133, OSHA eye and face protection regulation, or the European standard

EN 166.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or

canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not

provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash

and a deluge shower safety station.

Notes: Only established PEL and TLV values for the ingredients are listed below.

To Top of page

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State/Appearance: Liquid.

Color: Clear to slight Yellow.

Odor: Mercaptan.

Boiling Point: Not determined.

Melting / Freezing Point: Not determined.

Solubility: negligible

Specific Gravity: 1.13

pH: 9.5 @ 5 Percent Solution

Vapor Density: Not determined.
Vapor Pressure: <<1 mmHg @70°F

Molecular Formula: Mixture
Molecular Weight: Mixture
Percent Volatile: 0
VOC Data: 0 g/L
Percent Solids by Weight 100

To Top of page

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and

oxidizing conditions.

Incompatibilities with Other

Materials:

Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide,

nitrites. Peroxides. Materials reactive with hydroxyl compounds.

Hazardous Polymerization: Not reported.

To Top of page

SECTION 11: TOXICOLOGICAL INFORMATION

To Top of page

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

To Top of page

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: None

To Top of page

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.

DOT UN Number: N/A

DOT Hazard Class: Not applicable.

DOT Packing Group: Not applicable.

IATA Shipping Name: Non regulated.

To Top of page

SECTION 15: REGULATORY INFORMATION

Canadian Regulations. WHMIS Hazard Class(es): D2B

All components of this product are on the Canadian Domestic Substances List.

To Top of page

SECTION 16: ADDITIONAL INFORMATION

HMIS Health Hazard: 3*
HMIS Fire Hazard: 1
HMIS Reactivity: 1
HMIS Personal Protection: x

MSDS Revision Date: 10/10/2006

Disclaimer: "This Health and Safety Information is correct to the best of our knowledge and

belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within

a controlled environment."

Copyright© 1996-2007 Actio Software Corporation. All Rights Reserved.