



MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	Seche Blanc	DATE:	6/18/2009
Formula:	30-0479	REV.	00
Item#:	83042, 83009		

Manufacturer: American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Hazardous Ingredients:

Component	CAS #	%	Exposure Limits ppm ACGIH-TWA / OSHA-PEL
Butyl Acetate	123-86-4	20.0 - 44.0%	ACGIH-TWA: 100ppm OSHA-PEL: 150ppm
Ethyl Acetate	141-78-6	20 - 44.0%	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
Nitrocellulose	9004-70-0	10.0 - 20.0%	ACGIH-TWA: 400ppm
Isopropyl Alcohol	67-63-0	5.0 - 10.0%	ACGIH-TWA: 400ppm
Propyl Acetate	108-21-4	5.0 - 15.0%	ACGIH-TWA: 100ppm OSHA-PEL: 250ppm
Camphor	76-22-2	0.2 - 5.0%	ACGIH-TWA: 2ppm OSHA-PEL: 2ppm
Tosylamide Formaldehyde Resin	1338-51-5	4.0 - 12.0%	N/A
Triphenyl Phosphate	115-86-6	1.5 - 5.0%	N/A
Trimethyl Pentanyl Diisobutyrate	6846-50-0	1.5 - 5.0%	N/A
Diacetone Alcohol	123-42-2	0.2 - 0.8%	ACGIH-TLV: 50ppm OSHA-PEL: 50ppm

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Eye:	May cause irritation or burning eyes.
Skin:	Repeated or prolonged liquid contact may cause skin irritation with discomfort or dermatitis.
Ingestion:	Gastro intestinal distress, call a physician.
Inhalation:	May cause nose and throat irritation.



MATERIAL SAFETY DATA SHEET

Section 4. First Aid Measures

- First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.
- First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.
- First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.
- First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.
-

Section 5. Fire Fighting Measures

- Flash Point (°F/°C): 24°F (-4.4°C)TCC
- Flammable Limit (vol%): LEL: 1.7%
UEL: 12.0%
- Auto-ignition Temp. (vol%): None Established
- Extinguisher Media: Foam, dry chemical or carbon dioxide.
- Fire Fighting Procedures: Full protective equipment, including self contained breathing apparatus is recommended. Water from fog nozzle may be used to cool containers to prevent pressure build up.
- Unusual Fire and Explosion Hazards: When heated above the flash point flammable vapors may be emitted. Fine mists or sprays may be flammable at temperatures below the flash point.
-

Section 6. Accidental Release Measures

- Spill or Release Procedures: Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.
- Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-880; in case if the spill is in excess of EPA reportable quantity.
-

Section 7. Handling and Storage



MATERIAL SAFETY DATA SHEET

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash face and hands before eating, drinking, or smoking. Store in original container, away from excessive heat and keep in a dry are.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: Use local Exhaust.

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Colored viscous liquid

Viscosity (RAT): Not applicable

Odor @ 25°C: Sweet Ester Odor

Vapor Pressure: Not Available

pH Not applicable

Vapor Density: Not Available

Specific Gravity: 7.746lb/gl

Evaporation Rate: Slower than ether

Ignition: Not applicable

Coating V.O.C.: 1.44 lb/gl

Melting Point: Not applicable

Material V.O.C.: 1.44 lb/gl

Boiling Range: 171°F - 640°F

Solubility in Water Moderate

Section 10. Stability and Reactivity

Stability: Stable


Hazardous Decomposition Products:

CO, CO₂, Nitrous Oxides, Smoke

Incompatibility (Materials to Avoid):

Acids, Alkalies and Peroxides.

Hazardous Polymerization:



MATERIAL SAFETY DATA SHEET

Will not occur

Conditions to Avoid: Do not store over 120°F

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name:	Paint
DOT Hazard Class:	3, Flammable Liquid
Packaging Group:	II
UN ID Number	UN 1263

Section 15. Regulatory Information

Regulatory Information Available Upon Request

Section 16. Other Information

No additional information available.