

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name: Ardell LashFree Remover - Individual Eyelash Adhesive DATE: 5/17/2010

Remover

30-2651 REV. Formula: 00

Item#: 65060, 680340, 680230

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Composition:

Component CAS# **Exposure Limits** Ethoxydiglycol 111-90-0 100.00% None Established

(Glycol Ether De)

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Eyes, skin or inhalation

Eye: Excess redness and swelling of the conjunctiva may occur. Causes irritation, experienced as

stinging and discomfort or pain.

Skin: Brief contact is not irritating. Prolonged contact causes mild to moderate local redness and

swelling.

Slightly toxic. May produce signs of intoxication characterized by incoordination, dizziness, Ingestion:

drowiness, headache, nausea, mental confusion, possibly slurred speech, and stupor, depending

on the quantity of material ingested.

Inhalation: Short-term harmful health affects are not expected from vapor generated at ambient temperature.

Chronic Exposure: Prolonged or repeated overexposure to mist or vapor generated at high temperature may result in

the inhalation of harmful amounts of material

Medical Conditions

A knowledge of the available toxicology information and of the physical and chemical properties of

Aggravated by

the material suggests that overexposure is unlikely to aggravate existing medical conditions.

Exposure:

Section 4. First Aid Measures

First Aid for Eye: Immediately flush eyes with water and continue washing for several minutes. Remove contact

lenses if worn. Obtain medical attention.





MATERIAL SAFETY DATA SHEET

First Aid for Skin: Remove contaminated clothing. Wash skin with soap and water. Obtain medical attention if

irritation persists. Wash clothing before reuse.

First Aid for Inhalation: Remove to fresh air. Obtain medical attention if symptoms persist.

First Aid for Ingestion: If patient is fully conscious, give two glasses of water. Induce momiting (This should be done only

by medical or experienced first-air personnel). Obtain medical attention.

Notes To Physician: There is no specific antidote. Treatment of overexposure should be directed at the control of

symptoms and the clinical condition of the patient.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 215°F /102°C (Closed Cup); 230°F / 110°C (Open Cup)

Flammable Limit LEL: 1.2 (vol%): UEL: 23.5

Extinguisher Media to

Avoid:

No information currently available.

Special Fire Fighting

Procedures:

Do not direct a solid stream of water or foam into hot, burning pools; this may cause frothing and

increased fire intensity.

Special Protective Equipment for Firefighters Use self-contained breathing apparatus and protective clothing.

Hazardous

Combustion Products:

Burning can produce the following products. Carbon Monoxide and / or carbon dioxide. Carbon

monoxide is highly toxic if inhaled. Carbon dioxide in sufficient concentrations can act as an

asphyxiant.

Unusual Fire And Explosion Hazards:

This material may produce a floating fire hazard in extreme fire conditions.

Section 6. Accidental Release Measures

Spill or Release Procedures: Small spills can be flushed with large amounts of water; larger spills should be collected for disposal.

Page 2 of 5



MATERIAL SAFETY DATA SHEET

Section 7. Handling and Storage

Handling & Storing:

Avoid contact with eyes. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

Glycol ethers as a family of solvents can be stored in carbon steel. Stainless steel or high baked, phenolic-lined tanks may be considered for critical applications sensitive to slight discoloration or trace iron contamination. Piping can be made of the same material as the storage tank. A centrifugai pmp is suitable for transfer services. Butyl rubber or EPDM can be used for gaskets and packing. NOTE: UCC does not recommend using aluminum, copper, galvanized iron, galvanized steel, Viton, neoprene, nitrile or nutrual rubber with glycol esters. Glycol ethers do not present a significant flammability hazard at normal storage temperatures. They have relatively low vapor pressures, viscosities and freezing points.

Section 8. Exposure Controls / Personal Protective Equipment

Respiratory Protections (Specific Type):

If necessary, use rspirator or a NIOSH-approved air-purifying respirator with organic vapor cartridge and particulate pre-filter is recommended.

Ventilation to be Used:

General (mechanical) room ventila

Other Protective Clothing and Equipment:

Eye: Safety glasses or monogoggles **Gloves:** Polyvinyl chloride coated.

Other Protective Equipment:

Eye bath, safety shower.

Process Hazard:

Sudden release of hot orgaqnic chemical vapor or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into hot equipment under a vacuum, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated-temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions. Further information is availabe in a technical bulletin entitled "ignition Hazards of Organic Chemical Vapor."



MATERIAL SAFETY DATA SHEET

Standard (ASTM) test values do not predict many real life situations. Autoignition is the result of a gas-phase runaway reaction which occurs when the heat generation rate inside a given volume of reactant exceeds that of heat loss rate. The heat balance determining autoignition is therefore dependent on factors such as the reactant pressure plus the volume and geometry of any container. The ASTM standard AIT test uses a small (500ml) atmospheric pressure. The AITs determined using this test can be appreciably greater than those that might be experienced in large commercial equipment, especially if elevated pressures are involved. Any operation at temperatures above the flash point should be reviewed by the appropriate expert (e.g., safety engineer, chemist). When the ASTM autoignition temperature is required it can be obtained by calling the Vendor.

Section 9. Physical and Chemical Properties

Viscosity (RVT): Appearance @ 25°C: Transparent colorless Not applicable

liquid

Odor @ 25°C: Mild ethereal 0.009 kpa / 0.07mmHg @ 20°C Vapor Pressure:

Not applicable Vapor Density: 4.6 (air = 1)pН

0.990 20°C/ 20°C **Specific Gravity: Evaporation Rate:** 0.01 (Butyl Acetate =1)

Ignition: Not applicable Freezing Point: -44°C / -46°F

Melting Point: Not applicable Percent Volatiles: 100% **Boiling Point:** 393.4°F /200.8°C Molecular Weight: 134.2 g/mol

Solubility in Water Miscible

Section 10. Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Incompatibility (Materials to Avoid):

Strong alkalies. High temperatures in the presence of strong bases. Acids. Strong oxidizing agents.

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Do not distill to dryness. Avoid excessive temperature or prolonged reflux, suach as in batch

distillations.

Section 11. Toxicological Information

Acute Oral Toxicity: No data available.



MATERIAL SAFETY DATA SHEET

Acute Dermal Toxicity: No data available.

Acute Inhalation

No data available.

Skin Irritation:

Toxicity:

No data available.

Eye Irritation:

No data available.

Sensitisation:

No data available.

Section 12. Ecological Information

Acute Toxicity

Fish: No data available.

Aquatic Invertebrates: No data available.

Algae: No data available.

Micro organisms: No data available.

Section 13. Disposable Considerations

Incinerate in a furnace where premitted under Federal, State, and local regulations. At low concentrations in water this product is biodegradable in wastewater treatment plant. Dispose in accordance with all applicable Federal, State, and local environmental regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name (49CFR 172.101):

Non Regulated Material

Hazard Class:

UN/NA:

Packing Group:

Section 15. Regulatory Information

Regulatory information available upon request.

Section 16. Other Information

Additional information available upon request.