

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	Seche Plus	DATE:	3/18/2010
Formula:	30-3012	REV.	02
Item#:	83001, 83108, 83118		

Manufacturer: American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Hazardous Ingredients:


Component	CAS #	%	Exposure Limits ppm ACGIH / OSHA
Ethyl Acetate	141-78-6	40-50	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
Nitrocellulose	9004-70-0	10-20	None Established
Heptane	142-82-5	10-20	ACGIH-TLV: 400ppm OSHA-PEL: 500ppm
*Propyl Acetate	109-60-4	5-10	ACGIH-TLV: 200ppm OSHA-PEL: 200ppm
Isopropyl Alcohol	67-63-0	5-15	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
MEK	78-93-3	1-5	ACGIH-TLV: 200ppm OSHA-PEL: 200ppm
*n-Butyl Alcohol	71-36-3	1-5	ACGIH-TLV: 20ppm OSHA-PEL: 100ppm
Butyl Acetate	123-86-4	1-5	ACGIH-TWA: 150ppm OSHA-PEL: 150ppm
Camphor	76-22-2	1-5	ACGIH-TLV: 12 mg/m3 OSHA-PEL: 2 mg/m3
*Formaldehyde	50-00-0	<1.0	OSHA-PEL: 0.75ppm

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of the Title III and of 40 CFR 372.

Components in this product have been verified as being on the TSCA Inventory and has been classified in accordance with the hazard criteria of the CPR and all information required.

PROPOSITION 65 WARNING: This product contains a chemical "known to the state" of California to cause cancer or reproductive toxicity.

Section 3. Hazardous Identification



MATERIAL SAFETY DATA SHEET

Potential Health Effects, Signs and Symptoms of Exposure:

Eye:	May cause irritation or burning eyes.
Skin:	Repeated or prolonged liquid contact may cause skin irritation with discomfort or dermatitis.
Ingestion:	Gastro intestinal distress, call a physician.
Inhalation:	May cause nose and throat irritation.


Section 4. First Aid Measures

First Aid for Eye:	Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.
First Aid for Skin:	Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.
First Aid for Inhalation:	Remove to fresh air. Seek medical attention if discomfort persists.
First Aid for Ingestion:	Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5. Fire Fighting Measures

Flash Point (°F/°C):	24°F/ -4.44°C (TCC)
Flammable Limit (vol%):	LEL: 1.4% UEL: 12.7%
Auto-ignition Temp. (vol%)	None Established
Extinguisher Media:	Water is the most effective fire extinguishing medium for nitrocellulose. It is recommended to be used in large volume. Dry chemical, CO2 or a universal type foam could be used to extinguish small fires.
Fire Fighting Procedures:	Full protective equipment, including self contained breathing apparatus is recommended. Water from fog nozzle may be used to cool containers to prevent pressure build up.
Unusual Fire and Explosion Hazards:	When heated above the flash point flammable vapors may be emitted. Fine mists or sprays may be flammable at temperatures below the flash point.

Section 6. Accidental Release Measures



MATERIAL SAFETY DATA SHEET

Spill or Release Procedures: Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-880; in case if the spill is in excess of EPA reportable quantity.

Section 7. Handling and Storage

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash face and hands before eating, drinking, or smoking. Store in original container, away from excessive heat and keep in a dry are.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: Use local Exhaust. If vapor concentration exceeds the establishe exposure limits respiratory protection is necessary. Depending on the airbourne concentration, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved) or supplied air equipment.

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Transparent viscous liquid

Odor @ 25°C: Sweet Ester Odor
pH Not applicable

Specific Gravity: 7.332 lbs/gl

Ignition: Not applicable

Melting Point: Not applicable

Boiling Range: 171°F - 228°F

Solubility in Water Partial

Viscosity (RVT): Not applicable


Vapor Pressure: Not Available

Vapor Density: Not Available

Evaporation Rate: Not Available

Coating V.O.C.: 3.45 lb/gl

Material V.O.C.: 3.44 lb/gl



MATERIAL SAFETY DATA SHEET

Section 10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition Products:

Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, and nitrogen oxide. Under some conditions, methane, irritating aldehydes and carboxylic acids and hydrogen cyanide may be formed.

Incompatibility (Materials to Avoid):

This product is incompatible with strong acids or bases and oxidizers.

Hazardous Polymerization:

Will not occur

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

Section 14. Transportation Information


<DOT Information>

Proper Shipping Name:

Paint

DOT Hazard Class:

3



MATERIAL SAFETY DATA SHEET

Packaging Group:

III

UN ID Number

UN 1263

Section 15. Regulatory Information

Regulatory Information available upon request.

Section 16. Other Information

No additional information available.