



MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	EzFlow Milky Basecoat	DATE:	9/12/2007
Formula:	30-6131	REV.	00
Item#:	66110, 66101		

Manufacturer: American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Reportable Components:

Component	CAS #	%	Exposure Limits ppm
Butyl Acetate	123-86-4	30 - 40	TLV/PEL: 150ppm
Ethyl Acetate	141-78-6	30 - 40	TLV/PEL: 400ppm
Nitrocellulose	9004-70-0	10 - 20	None Established
Isopropyl Alcohol	67-63-0	5 - 10	TLV/PEL: 400ppm
Camphor	76-22-2	0 - 1	TLV/PEL: 2mg/m3

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Inhalation, Skin Absorption.

Eye: This Product may cause eye irritation. Direct contact with this material or exposure to its vapors or mist (greater than approximately 1000ppm) may cause burning, tearing, redness or swelling.

Skin: This Product may cause skin irritation. Prolonged or repeated exposure to this material may cause redness and burning, drying and cracking and dermatitis.

Ingestion: Ingestion of excessive quantities may cause irritation of the digestive tract. Signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination, and fatigue.)

Inhalation: Breathing high concentrations of vapors may cause irritation of the nose and throat. Signs of nervous system depression (e.g. drowsiness, dizziness, loss of coordination, and fatigue.)

Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water. Seek medical attention if discomfort persists.



MATERIAL SAFETY DATA SHEET

First Aid for Skin:	Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.
First Aid for Inhalation:	In case of irritation by vapor, remove from exposure, treat symptomatically. Seek medical attention if symptoms persist.
First Aid for Ingestion:	Call a physician or poison control center immediately. Induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person.

Section 5. Fire Fighting Measures

Flash Point (°F/°C):	24°F TCC
Flammable Limit (vol%):	LEL: 1.7% UEL: 12.7%
Auto-ignition Temp. (vol%)	None Established
Extinguisher Media:	Water is the most effective fire extinguishing medium for Nitrocellulose. It is recommended to be used in large volume. Dry chemical, CO2 or a universal type foam could be used to extinguish small fires.
Fire Fighting Procedures:	Full protective equipment, including self contained breathing apparatus is recommended. Water may be used to cool containers to prevent pressure build up.
Unusual Fire and Explosion Hazards:	Handle as flammable liquid. Vapors from an explosive mixture in air between the upper and lower explosive limits which can be ignited by many sources such as pilot lights, open flames, electrical motors and switches.

Section 6. Accidental Release Measures

Spill or Release Procedures:	Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbant pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (800-424-8802) in case of the spill is in excess of EPA reportable quantity.
------------------------------	---

Section 7. Handling and Storage

Handling & Storing:	Use non-sparking utensils when handling this material. Keep containers tightly closed, cool, dry and away from sources of ignition.
---------------------	---

Section 8. Exposure Controls / Personal Protective Equipment



MATERIAL SAFETY DATA SHEET

Ventilation:	The ventilation system should be designed to be able to maintain airborne concentrations below the established exposure limits. If the current ventilation is not adequate to maintain this level, additional ventilation of exhaust systems may be required. Use explosion proof equipment.
Protective Gloves:	The use of gloves impermeable to the specific material handled is advised to prevent skin
Eye Protection:	Include splash guards and side shields.
Clothing:	Coveralls
Respiratory Protection:	When vapor concentration exceed the established exposure limits respiratory protection is necessary. Depending on the airborne concentration, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved organic vapor) or supplied air equipment.
Other Protective Equipment:	Eye bath and shower.

Section 9. Physical and Chemical Properties

Appearance @ 25°C:	Transparent viscous liquid	Viscosity (RVT):	Not applicable
Odor @ 25°C:	Sweet Ester Odor	Vapor Pressure:	Not applicable
pH	Not applicable	Vapor Density:	Not available
Specific Gravity:	7667 lb/gal	Evaporation Rate:	Not available
Ignition:	Not applicable	Material V.O.C.:	3.13 lb/gal
Total Solids, %	Not applicable		
Boiling Point / Freezing Point	171°F - 228°F		
Solubility in Water	Partial		

Section 10. Stability and Reactivity

Stability:	Stable
Hazardous Decomposition Products:	CO, CO ₂ , Nitrous Oxides.
Incompatibility (Materials to Avoid):	Strong acids or bases and oxidizers.
Hazardous Polymerization:	



MATERIAL SAFETY DATA SHEET

Will not occur

Conditions to Avoid: Keep away from heat, sparks and flames. Avoid any source of ignition.

Section 11. Toxicological Information

No Information Available.

Section 12. Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish:

No data available

Acute Toxicity to Invertebrates:

No data available

Acute Toxicity to Algae

No data available

Bioconcentration:

No data available

Toxicity to Sewage Bacteria:

No data available

Chemical Fate Information

Biodegradability:

No data available

Chemical Oxygen Demand:

No data available

Section 13. Disposable Considerations

Dispose in compliance with State, Local and Federal regulations.

Section 14. Transportation Information

Proper Shipping Name: Paint

DOT Hazard Class: 3 (Flammable Limit)

Packaging Group: PG II

UN ID Number: 1263



MATERIAL SAFETY DATA SHEET

Section 15. Regulatory Information

Regulatory Information Available Upon Request.

Section 16. Other Information

No additional information available.