

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	Seche Ultra V Topcoat	DATE:	6/18/2009
Formula:	30-9003	REV.	00
Item#:	83142		

Manufacturer: American International Industries
 2220 Gaspar Ave
 Los Angeles, CA 90040
 Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Hazardous Ingredients:

Component	CAS #	%	Exposure Limits ppm ACGIH-TWA / OSHA-PEL
Ethyl Acetate (Ethyl Ethanoate)	141-78-6	>20%	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm
Butyl Acetate (Butyl Ethanoate)	123-86-4	>20%	ACGIH-TWA: 100ppm OSHA-PEL: 150ppm
Cellulose Acetate (Cellulose Ester)	9004-35-7	>5%	None Established
Isopropyl Alcohol	67-63-0	>5%	ACGIH-TWA: 400ppm OSHA-PEL: 400ppm

Section 3. Hazardous Identification


Potential Health Effects, Signs and Symptoms of Exposure:

Eye: May cause irritation or burning eyes.
 Skin: Repeated or prolonged liquid contact may cause skin irritation with discomfort or dermatitis.
 Ingestion: Gastro intestinal distress, call a physician.
 Inhalation: May cause nose and throat irritation.

 Acute: Irritation, burning of eyes and skin, nervous depression.
 Chronic: Reports have associated repeated and prolonged overexposure to solvent with permanent brain damage.

Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention.



MATERIAL SAFETY DATA SHEET

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 24°F /-4°C (TCC)

Flammable Limit (vol%): Not available.

Auto-ignition Temp. (vol%): None Established

Extinguisher Media: Carbon Dioxide, Dry Chemical, Foam

Fire Fighting Procedures: Full protective equipment, including self-contained breathing apparatus is recommended. Water from fog nozzle may be used to cool containers to prevent pressure build up.

Unusual Fire and Explosion Hazards: When heated above the flash point, flammable vapors may be emitted. Fine mists or sprays may be flammable at temperatures below the flash point.

Section 6. Accidental Release Measures

Spill or Release Procedures: Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.


Section 7. Handling and Storage

Handling & Storing: Observe label precautions and keep away from heat, sparks and flames. Close container after each use. Ground container when pouring. Do not store over 120°F. Wash hands thoroughly after handling - before eating.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Handling & Storing Precautions



MATERIAL SAFETY DATA SHEET

In accordance with good industrial practice avoid unnecessary personal contact. Wash face and hands before eating, drinking, or smoking. Store in original container away from excessive heat and keep in a dry area.

Ventilation: Use local Exhaust.

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Transparent Viscous Liquid

Viscosity (RVT): Not applicable

Odor @ 25°C: Ether Odor

Vapor Pressure: Not Available

pH: Not applicable

Vapor Density: Not Available

Weight/gallon: 7.46

Evaporation Rate: Slower than ether

Ignition: Not applicable

Melting Point: Not applicable

Boiling Range: 171 - 640°F

Solubility in Water: Partial

Section 10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition Products:

CO, CO2, Nitrous Oxides, Smoke


Incompatibility (Materials to Avoid):

Acids, Alkalies and Peroxides.

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Do not store over 120°F



MATERIAL SAFETY DATA SHEET

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name:	Paint
DOT Hazard Class:	3, Flammable Liquid
Packaging Group:	II
UN ID Number	UN 1263

Section 15. Regulatory Information

Regulatory information available upon request.

Section 16. Other Information

No additional information available.