

Section 1. Chemical Product and Company Identification		
Common Name		
	Nail Tek Hydration Therapy	
	Moisture Balancing Topcoat	
Supplier	American International Industries	
	2220 Gaspar Avenue	
	Los Angeles, CA 90040	
Synonym		
	Topcoat Polish Dryer	
Trade Name	Nail Tek HYDRATION THERAPY MOISTURE	

Item#:	55565, HT67000)
Bulk#:	30-9691
Validation Date:	05-17-12
Rev.:	00
Chem-Tel:	(800) 255-3924

Section 2. Composition, Information on Ingredients

BALANCING TOPCOAT

Cosmetic or Sundry Only

Name	CAS#	% by Weight	Exposu	re Limits
1) Butyl Acetate	123-86-4	15 - 25	ACGIH-TWA 150.0	OSHA-PEL 150.00
2) Ethyl Acetate	141-78-6	35 - 45	400.0	400.00
3) Isopropyl Alcohol	67-63-0	0.1 - 1	NA	NA
4) Nitrocellulose	9004-70-0	1 - 10	400.0	NA
5) SD Alcohol 40-B	64-17-5	15 - 25	1000.0	1000.00
6) Trimethyl Pentanyl Diisobutyrate	6846-50-0	1 - 5	NA	NA
Cellulose Acetate Butyrate	9004-36-8	5 - 15	NA	NA
8) Acrylates Copolymer	NA	1 - 10	NA	NA
9) Sucrose Benzoate	12738-64-6	1 - 10	NA	NA
10) Triphenyl Phosphate	7664-38-2	1 - 10	NA	NA

Continued on Next Page

Material Uses

Section 3. Hazards Identification

Emergency Overview	Vapors are irritating to mucous membrane and upper respiratory tract. Continuous high volume usage may irritate eyes, nose and throat. Vapors may cause headache, drowsiness, dizziness, nausea, staggering gate, confusion, unconsciousness. May cause skin irritation leading to dermatitis. Keep away from heat, sparks, and flame. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Potential Acute Health Effects Eyes	Liquid and vapors are irritating to eyes.
Skin	Causes skin irritation. Overexposure causes sensitization.
Inhalation	Vapors are irritating to mucous membrane and upper respiratory tract. Continuous high volume usage irritates eyes and nose. Vapors may cause drowsiness, dizziness, nervous system depression.
Ingestion	Harmful if swallowed.
Potential Chronic Health Effects	Reports have associated repeated and prolonged overexposure to solvent with permanent brain damage.
Medical Conditions Aggravated by Overexposure:	
Overexposure/Signs/Symptoms	Medical conditions generally aggravated by overexposure.
See Toxicological Information/ (section 11)	Not available

Section 4. First Aid Measures		
Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.	
Skin Contact	In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.	
Inhalation	If symptoms of prolonged exposure to concentrated material vapors appear, remove to fresh air. If breathing is difficult, loosen any restrictive clothing and provide oxygen and get medical care if necessary.	
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to any unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.	
Notes to Physician	Not available	

Section 5. Fire Fighting Measures	
Flammability of the Product	Flammable
Auto-Ignition Temperature	Not established
Flash Points	TCC 24 DEG F (-4.4 DEG C)
Flammable Limits	Not available
Products of Combustion	Not available
Fire Hazards in Presence of Various Substances	Considered to be flammable.
Explosion Hazards in Presence of Various Substances	Fine mists or sprays may be flammable at temperatures below the Flash Point.
Fire Fighting Media and Instructions	Carbon Dioxide (CO2), Foam, and Dry Chemical.
Protective Clothing (Fire)	Full protective equipment, including approved/certified respirator or self contained breathing apparatus is recommended.
Special Remarks on Fire Hazards	Use NIOSH approved self-contained breathing apparatus in the pressure demand mode. Isolate fire area. Remove all personnel.
Special Remarks on Explosion Hazards	When heated above the flash point flammable vapors may be emitted. Cool containers with stream of water. Vapors are heavier than air and may travel along the ground to a source of

ignition.

Section 6. Accidental Release Measures

Small Spill and Leak Prevent skin contact and breathing vapors. Confine and absorb on non-flammable absorbent. Dispose of as

flammable solid in accordance with applicable Federal, State, and Local Regulations.

Large Spill and Leak Ventilate area and remove all sources of ignition. Pump into suitable tank for disposal or reclamation. Do not

incinerate in closed containers.

Section 7. Handling and Storage

Handling

Observe label precautions and keep away from heat, sparks and flame. Keep container closed after each use.

Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical

(ventilating, lighting, and material handling) equipment.

Storage Storage Store in a segregated and approved area. Do not store over 120 degrees F (48 deg C). Keep container in a

cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

Section 8. Exposure Controls, Personal Protection

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below

their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the

work station location.

Personal Protection

Eyes Face shield

Body Synthetic apron

Respiratory

Use NIOSH approved Respirator

Hands

Chemical resistant gloves (impervious)

Not applicable

Protective Clothing (Pictograms)



Personal Protection in Case of a Large Spill

Face Shield. Full suit. Boots. Gloves.

Continued on Next Page

Nail Tek HYDRATION THERAPY MOISTURE BALANCING TOPCOAT

Page 4 of 7

Product Name Exposure Limits

		ACGIH-TWA	OSHA-PEL	
1)	Butyl Acetate	150.0	150.00	
2)	Ethyl Acetate	400.0	400.00	
3)	Isopropyl Alcohol	NA	NA	
4)	Nitrocellulose	400.00	NA	
5)	SD Alcohol 40-B	1000.00	1000.00	
6)	Trimethyl Pentanyl Diisobutyrate	NA	NA	
7)	Cellulose Acetate Isobutyrate	NA	NA	
8)	Acrylates Copolymer	NA	NA	
9)	Sucrose Benzoate	NA	NA	
10)	Triphenyl Phosphate	NA	NA	
Consult local authorities for acceptable exposure limits.				

Section 9. Physical and Chemical Properties		
Physical State and Appearance	Liquid (Clear)	
Molecular Formula	Not applicable	
PH (1% Soln/Water)	Not available	
Boiling/Condensation Point	171 - 342 F (77 – 172 C)	
Melting/Freezing Point	Not available	
Critical Temperature	Not available	
Specific Gravity	Not available	
Vapor Pressure	32 MMHG at 68 deg F (Isopropyl Alcohol)	
Vapor Density	Not available	

Not available

Volatility

Odor	Strong Solvent
Taste	Not Available
Color	Clear

Odor Threshold	Not available
Evaporation Rate	Slower than Ether
VOC	7.85 LBS/GAL
Viscosity	Not available
Log K _{ow}	Not available
Iconicity (in Water)	Not available
Dispersion Properties	Not available
Solubility	Not available
Physical Chemical Comments	Not available

Continued on Next Page	
Noil Tak HYDDATION THERADY MOISTINE BALANCING TODOGAT	Dave Fof7
Nail Tek HYDKATION THEKAPY WOISTOKE BALANCING TOPCOAT	Page 5 of 7
	· ·

Section 10. Stability and Reactivity	
Stability and Reactivity	The product is stable.
Conditions of Instability	Do not store over 120 DEG F (48 DEG C).
Incompatibility with Various Substances	Avoid acids, alkalies, and peroxides.
Hazardous Decomposition Products	CO, CO2, Nitrous Oxides, Smoke
Hazardous Polymerization	Will not occur

Section 11. Toxicological Information		
Toxicity to Animals	Not available	
Chronic Effects on Humans	No known carcinogen	
Other Toxic Effects Humans	Vapors are irritating to mucous membrane and upper respiratory tract. Continuous high volume usage irritates eyes and nose. Vapors may cause drowsiness and dizziness. Irritating to eyes. Causes skin irritation and exposure to the skin can cause dermatitis.	
Special Remarks on Toxicity to Animals	Not available	
Special Remarks on Chronic Effects on Humans	Not available	
Special Remarks on Other Toxic Effects on Humans	No additional remarks	

Section 12. Ecological Information		
Ecotoxicity	Not available	
BOD5 and COD	Not available	
Biodegradable /OECD	Not available	
Mobility	Not available	
Products of Degradation	Not available	

Toxicity of the Products of Biodegradation	Not available
Special Remarks on the Products of Biodegradation	Not available

Section 13. Disposal Considerations

Waste Information _____ Dispose of in accordance with applicable regulatory ordinance.

Waste Stream Not available

Consult your local or regional authorities.

Continued on Next Page

Section 14. Transport Information



	FLAMMABLE LIQUIDS, N.O.S., 3, UN1263, II, Emergency Response Guide 128
Marine Pollutant	Not available
Special Provision for Transport	Not available
ADR/RID Classification	Not controlled under ADR (Europe).
IMO/IMDG Classification	Not controlled under IMDG.
ICAO/IATA Classification	Not controlled under IATA.


Section 15. Regulatory Information		
HCS Classification	CLASS: Flammable liquid having a flash point lower than 37.8°C (100°F).	
U.S. Federal Regulations	TSCA 8(b) inventory: All ingredients are in compliance with TSCA. SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: No products were found. SARA 311/312 MSDS distribution – chemical inventory – hazard identification: No products were found. SARA 313 toxic chemical notification and release reporting: No products were found. Clean water act (CWA) 307: No products were found. Clean water act (CWA) 311: No products were found. Clean air act (CAA) 112 accidental release prevention: No products were found. Clean air act (CAA) 112 regulated toxic substances: No products were found.	

International Regulations	
EINECS	Not available
DSCL (EEC)	R11-Highly flammable R36/38 – Irritating to eyes and skin
International Lists	Australia: Isopropyl Alcohol Japan (MITI): Isopropyl Alcohol
State Regulations	No products were found.

Section 16. Other Information

Hazardous Material Information System (USA)

Fire Hazard



References Manufacturers Material Safety Data Sheet

Other Special Considerations Not available

Validated by Company on 08/01/2005 Verified by Company

Printed 08/01/2005

Nail Tek-Prima Technologies, Inc. 01 631-366-0500 Monday - Friday, 9:00 am - 5:00 pm EST

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.