

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

*** Section 1 - Product and Company Identification ***

MSDS #2123E

Product Numbers: 3046S, 3036S, 3024

Manufacturer Information

United Elchem Industries
c/o Oatey Co.
4700 West 160th Street
P.O. Box 35906
Cleveland, OH 44135

Phone: 216-267-7100

For Emergency First Aid call 1-877-740-5015. For chemical transportation emergencies ONLY, call Chemtrec at 1-800-424-9300. Outside the U.S. 1- 703-527-3887.

*** Section 2 - Hazards Identification ***

GHS Classification:

Flammable Liquids - Category 2
Acute Toxicity Oral - Category 4
Acute Toxicity Dermal - Category 4
Acute Toxicity Inhalation - Category 4
Eye Damage/Irritation - Category 2A
Carcinogenicity - Category 2
Specific Target Organ Toxicity Single Exposure - Category 3

GHS LABEL ELEMENTS

Symbol(s)



Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor.
Harmful if swallowed.
Harmful in contact with skin.
Harmful if inhaled.
Causes serious eye irritation.
Contains a chemical classified by the US EPA as a suspected possible carcinogen.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames and hot surfaces. - No smoking.
Keep container tightly closed.
Use explosion-proof electrical/ventilating/lighting/equipment.

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/eye protection/face protection.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing fume/gas/mist/vapors.
Use only outdoors or in a well-ventilated area.

Response

If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth. Do not induce vomiting.
If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
If exposed or concerned: Get medical advice/attention.
In case of fire: Use dry chemical, CO₂, or foam to extinguish fire.

Storage

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
109-99-9	Tetrahydrofuran	40-80
67-64-1	Acetone	10-20
9002-86-2	PVC (Chloroethylene, polymer)	10-20
78-93-3	Methyl ethyl ketone	5-15
112945-52-5	Silica, amorphous, fumed, crystalline-free	1-4

*** Section 4 - First Aid Measures ***

First Aid: Eyes

If material gets into eyes or if fumes cause irritation, immediately flush eyes with plenty of water until chemical is removed. If irritation persists, get medical attention immediately.

First Aid: Skin

Remove contaminated clothing immediately. Wash all exposed areas with soap and water. Get medical attention if irritation develops. Remove dried cement with hand cleaner or baby oil.

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

First Aid: Ingestion

DO NOT INDUCE VOMITING. Rinse mouth with water. Never give anything by mouth to a person who is unconscious or drowsy. Get immediate medical attention by calling a Poison Control Center, or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital.

First Aid: Inhalation

If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.

***** Section 5 - Fire Fighting Measures *****

General Fire Hazards

See Section 9 for Flammability Properties.

Highly flammable liquid and vapor. Keep away from heat and all sources of ignition including sparks, flames, lighted cigarettes and pilot lights. Containers may rupture or explode in the heat of a fire. Vapors are heavier than air and may travel to a remote ignition source and flash back. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

Hazardous Combustion Products

Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

Extinguishing Media

Use dry chemical, CO₂, or foam to extinguish fire. Cool fire exposed container with water. Water may be ineffective as an extinguishing agent.

Unsuitable Extinguishing Media

None.

Fire Fighting Equipment/Instructions

Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

***** Section 6 - Accidental Release Measures *****

Recovery and Neutralization

Stop leak if it can be done without risk.

Materials and Methods for Clean-Up

Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent such as sand, earth or other non-combusting material. Put absorbent material in covered, labeled metal containers.

Emergency Measures

Isolate area. Keep unnecessary personnel away.

Personal Precautions and Protective Equipment

Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high.

Environmental Precautions

Prevent liquid from entering watercourses, sewers and natural waterways.

Prevention of Secondary Hazards

None

***** Section 7 - Handling and Storage *****

Handling Procedures

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use with adequate ventilation (equivalent to outdoors). Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use. Other: "Empty" containers retain product residue and can be hazardous. Follow all SDS precautions in handling empty containers. Do not cut or weld on or near empty or full containers.

Storage Procedures

Store in a cool, dry, well-ventilated area away from incompatible materials. Keep containers closed when not in use.

Incompatibilities

Oxidizing agents, alkalis, amines, ammonia, acids, chlorine compounds, chlorinated inorganics (potassium, calcium and sodium hypochlorite) and hydrogen peroxides. May attack plastic, resins and rubber.

***** Section 8 - Exposure Controls / Personal Protection *****

Component Exposure Limits

Tetrahydrofuran (109-99-9)

ACGIH: 50 ppm TWA
100 ppm STEL
Skin - potential significant contribution to overall exposure by the cutaneous route
OSHA: 200 ppm TWA; 590 mg/m3 TWA
NIOSH: 200 ppm TWA; 590 mg/m3 TWA
250 ppm STEL; 735 mg/m3 STEL

Acetone (67-64-1)

ACGIH: 500 ppm TWA
750 ppm STEL
OSHA: 1000 ppm TWA; 2400 mg/m3 TWA
NIOSH: 250 ppm TWA; 590 mg/m3 TWA

PVC (Chloroethylene, polymer) (9002-86-2)

ACGIH: 1 mg/m3 TWA (respirable fraction)

Methyl ethyl ketone (78-93-3)

ACGIH: 200 ppm TWA
300 ppm STEL
OSHA: 200 ppm TWA; 590 mg/m3 TWA
NIOSH: 200 ppm TWA; 590 mg/m3 TWA
300 ppm STEL; 885 mg/m3 STEL

Engineering Measures

Open doors & windows. Provide ventilation capable of maintaining emissions at the point of use below recommended exposure limits. If used in enclosed area, use exhaust fans. Exhaust fans should be explosion-proof or set up in a way that flammable concentrations of solvent vapors are not exposed to electrical fixtures or hot surfaces.

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

Personal Protective Equipment: Respiratory

For operations where the exposure limit may be exceeded, a NIOSH approved organic vapor respirator or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

Personal Protective Equipment: Hands

Rubber gloves are suitable for normal use of the product. For long exposures chemical resistant gloves may be required such as 4H(tm) or Silver Shield(tm) to avoid prolonged skin contact.

Personal Protective Equipment: Eyes

Safety glasses with side shields or safety goggles.

Personal Protective Equipment: Skin and Body

No additional protective equipment needed.

***** Section 9 - Physical & Chemical Properties *****

Appearance:	Blue	Odor:	Ether-like
Physical State:	Liquid	pH:	NA
Vapor Pressure:	145 mmHg @ 20°C	Vapor Density:	2.5
Boiling Point:	151°F (66°C)	Melting Point:	NA
Solubility (H2O):	Negligible	Specific Gravity:	0.92 +/- 0.02 @ 20°C
Evaporation Rate:	(BUAC = 1) = 5.5 - 8.0	VOC:	80-85% Maximum 510 g/L per SCAQMD Test Method 316A.
Octanol/H2O Coeff.:	ND	Flash Point:	14-23°F (-10 to -5°C)
Flash Point Method:	CCCFP	Upper Flammability Limit (UFL):	11.8
Lower Flammability Limit (LFL):	1.8	Burning Rate:	ND
Auto Ignition:	ND		

***** Section 10 - Chemical Stability & Reactivity Information *****

Chemical Stability

This is a stable material.

Hazardous Reaction Potential

Will not occur.

Conditions to Avoid

Avoid heat, sparks, flames and other sources of ignition.

Incompatible Products

Oxidizing agents, alkalis, amines, ammonia, acids, chlorine compounds, chlorinated inorganics.

Hazardous Decomposition Products

Combustion will produce toxic and irritating vapors including carbon monoxide, carbon dioxide and hydrogen chloride.

***** Section 11 - Toxicological Information *****

Acute Toxicity

Component Analysis - LD50/LC50

Tetrahydrofuran (109-99-9)

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

Inhalation LC50 Rat 53.9 mg/L 4 h; Inhalation LC50 Rat 180 mg/L 1 h; Oral LD50 Rat 1650 mg/kg

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg

Methyl ethyl ketone (78-93-3)

Inhalation LC50 Mouse 32 g/m³ 4 h; Oral LD50 Rat 2737 mg/kg; Dermal LD50 Rabbit 6480 mg/kg

Silica, amorphous, fumed, crystalline-free (112945-52-5)

Oral LD50 Rat 3160 mg/kg

Potential Health Effects: Skin Corrosion Property/Stimulativeness

May cause irritation with redness, itching and pain. Methyl ethyl ketone and cyclohexanone may be absorbed through the skin causing effects similar to those listed under inhalation.

Potential Health Effects: Eye Critical Damage/ Stimulativeness

Vapors may cause irritation. Direct contact may cause irritation with redness, stinging and tearing of the eyes. May cause eye damage.

Potential Health Effects: Ingestion

Swallowing may cause abdominal pain, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.

Potential Health Effects: Inhalation

Vapors or mists may cause mucous membrane and respiratory irritation, coughing, headache, dizziness, dullness, nausea, shortness of breath and vomiting. High concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.

Respiratory Organs Sensitization/Skin Sensitization

This product is not reported to have any skin sensitization effects.

Generative Cell Mutagenicity

Cyclohexanone has been positive in bacterial and mammalian assays. Acetone, methyl ethyl ketone and tetrahydrofuran are generally thought not to be mutagenic.

Carcinogenicity**A: General Product Information**

In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.

B: Component Carcinogenicity**Tetrahydrofuran (109-99-9)**

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

Acetone (67-64-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

PVC (Chloroethylene, polymer) (9002-86-2)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

Silica, amorphous, fumed, crystalline-free (112945-52-5)

IARC: Monograph 68 [1997] (listed under Amorphous silica) (Group 3 (not classifiable))

Reproductive Toxicity

Methyl ethyl ketone and cyclohexanone have been shown to cause embryofetal toxicity and birth defects in laboratory animals. Acetone and tetrahydrofuran has been found to cause adverse developmental effects only when exposure levels cause other toxic effects to the mother.

Specified Target Organ General Toxicity: Single Exposure

May cause respiratory irritation. Inhalation of high concentrations may cause central nervous system depression, narcosis and unconsciousness. May cause kidney, liver and lung damage.

Specified Target Organ General Toxicity: Repeated Exposure

This product is not reported to have any specific target organ toxicity repeat exposure effects.

Aspiration Respiratory Organs Hazard

Aspiration during swallowing or vomiting can cause chemical pneumonia and lung damage. May cause kidney and liver damage.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

This product is not expected to be toxic to aquatic organisms.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Tetrahydrofuran (109-99-9)

Test & Species

96 Hr LC50 Pimephales promelas	1970-2360 mg/L [flow-through]
96 Hr LC50 Pimephales promelas	2700-3600 mg/L [static]
24 Hr EC50 Daphnia magna	5930 mg/L

Conditions

Acetone (67-64-1)

Test & Species

96 Hr LC50 Oncorhynchus mykiss	4.74 - 6.33 mL/L
96 Hr LC50 Pimephales promelas	6210 - 8120 mg/L [static]
96 Hr LC50 Lepomis macrochirus	8300 mg/L
48 Hr EC50 Daphnia magna	10294 - 17704 mg/L [Static]
48 Hr EC50 Daphnia magna	12600 - 12700 mg/L

Conditions

Methyl ethyl ketone (78-93-3)

Test & Species

96 Hr LC50 Pimephales promelas	3130-3320 mg/L [flow-through]
48 Hr EC50 Daphnia magna	>520 mg/L
48 Hr EC50 Daphnia magna	5091 mg/L

Conditions

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

48 Hr EC50 Daphnia magna

4025 - 6440 mg/L
[Static]

Persistence/Degradability

No information available for the product.

Bioaccumulation

No information available for the product.

Mobility in Soil

No information available for the product.

***** Section 13 - Disposal Considerations *****

Waste Disposal Instructions

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

US EPA Waste Number & Descriptions

Component Waste Numbers

Tetrahydrofuran (109-99-9)

RCRA: waste number U213 (Ignitable waste)

Acetone (67-64-1)

RCRA: waste number U002 (Ignitable waste)

Methyl ethyl ketone (78-93-3)

RCRA: waste number U159 (Ignitable waste, Toxic waste)
200.0 mg/L regulatory level

Disposal of Contaminated Containers or Packaging

Dispose of contents/container in accordance with local/regional/national/international regulations.

***** Section 14 - Transportation Information *****

DOT Information

For Greater than 1 liter (0.3 gal):

Shipping Name: Adhesives

UN #: 1133 Hazard Class: 3 Packing Group: II

Required Label(s): Flammable Liquid

For Less than 1 liter (0.3 gal):

Shipping Name: Consumer Commodity, ORM-D

IMDG Information

For Greater than 1 liter (0.3 gal):

Shipping Name: Adhesives

UN #: 1133 Hazard Class: 3 Packing Group: II

Required Label(s): Flammable Liquid

For Less than 1 liter (0.3 gal):

Shipping Name: Adhesives

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT**UN #: 1133 Hazard Class: 3 Packing Group: II****Required Label(s):** None (Limited Quantities are expected from labeling)*** * * Section 15 - Regulatory Information * * *****Regulatory Information****US Federal Regulations****Component Analysis**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Tetrahydrofuran (109-99-9)

CERCLA: 1000 lb final RQ; 454 kg final RQ

Acetone (67-64-1)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

Methyl ethyl ketone (78-93-3)

CERCLA: 5000 lb final RQ; 2270 kg final RQ

State Regulations**Component Analysis - State**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Tetrahydrofuran	109-99-9	Yes	Yes	Yes	Yes	Yes	No
Acetone	67-64-1	Yes	Yes	Yes	Yes	Yes	No
PVC (Chloroethylene, polymer)	9002-86-2	No	No	No	Yes	No	No
Methyl ethyl ketone	78-93-3	Yes	Yes	Yes	Yes	Yes	No

This product contains trace amounts of chemicals known to the State of California to cause cancer. Under normal use conditions, exposure to these chemicals at levels above the State of California "No Significant Risk Level" (NSRL) are unlikely. The use of proper personal protective equipment (PPE) and ventilation guidelines noted in Section 8 will minimize exposure to these chemicals.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Tetrahydrofuran	109-99-9	1 %
Acetone	67-64-1	1 %
Methyl ethyl ketone	78-93-3	1 %

Material Name: UNI-WELD WELL-TITE MEDIUM HOT BLUE CEMENT

Additional Regulatory Information

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Tetrahydrofuran	109-99-9	Yes	DSL	EINECS
Acetone	67-64-1	Yes	DSL	EINECS
PVC (Chloroethylene, polymer)	9002-86-2	Yes	DSL	ELINCS
Methyl ethyl ketone	78-93-3	Yes	DSL	EINECS
Silica, amorphous, fumed, crystalline-free	112945-52-5	No	DSL	No

*** * * Section 16 - Other Information * * ***

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Literature References

None

Other Information

NFPA and HMIS:

NFPA Hazard Signal: Health: 2 Flammability: 3 Reactivity: 1 Special: None

HMIS Hazard Signal: Health: 2* Flammability: 3 Reactivity: 1 PPE: G

Disclaimer:

The information herein has been compiled from sources believed to be reliable, up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources, and expressly do not make warranties, nor assume any liability for its use.

End of Sheet