

SAFETY DATA SHEET

052

Product Name **R410A****1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Supplier name	BOC LIMITED (AUSTRALIA)
Address	10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA
Telephone	131 262, (02) 8874 4400
Fax	132 427 (24 hours)
Emergency	1800 653 572 (24/7) (Australia only)
Web site	http://www.boc.com.au/
Synonym(s)	PRODUCT CODE: 168
Use(s)	REFRIGERANT
SDS date	08 January 2014

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN number	1078	DG division	2.2
Packing group	None Allocated	Subsidiary risk(s)	None Allocated
Hazchem code	2TE		

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
DIFLUOROMETHANE (HFC-32)	CAS: 75-10-5 EC: 200-839-4	Not Available	50%
PENTAFLUOROETHANE (HFC-125)	CAS: 354-33-6 EC: 206-557-8	Not Available	50%

4. FIRST AID MEASURES

Eye	Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate for 15 minutes. Seek medical attention.
Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
Skin	Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15 minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for 15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.

Ingestion Ingestion is not considered a potential route of exposure.

Advice to doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability	Non flammable. May evolve toxic gases (fluorides, carbon oxides, hydrocarbons) when heated to decomposition.
Fire and explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.
Extinguishing	Use water fog to cool containers from protected area.
Hazchem code	2TE
	2 Water Fog (or fine water spray if fog unavailable)
	T Self Contained Breathing apparatus and protective gloves.
	E Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment as detailed in Section 8 of this SDS.
Environmental precautions	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Methods of cleaning up	Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.
References	See Sections 8 and 13 for exposure controls and disposal.

7. STORAGE AND HANDLING

Storage	Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
PENTAFLUOROETHANE (HFC-125)	SWA (AUS)			Asphyxiant	

Biological limits No biological limit allocated.

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face	Wear safety glasses.
Hands	Wear nitrile gloves.
Body	Wear safety boots.
Respiratory	Where an inhalation risk exists, wear an Air-line respirator.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	COLOURLESS LIQUID
Odour	FAINT SWEET AND ETHEREAL ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	-52.8°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	3.0 (Air = 1)
Specific gravity	NOT APPLICABLE
Solubility (water)	0.28 % @ 25°C
Vapour pressure	1484 kPa @ 21°C
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
% Volatiles	99.99 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites), alkalis (eg. sodium hydroxide), alkaline earth metals (eg. manganese). Also incompatible with freshly abraded aluminium surfaces and may cause a strong exothermic reaction.
Hazardous Decomposition Products	This material will not decompose to form hazardous products.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Asphyxiant gas - non irritant. Adverse health effects may result from exposure at high levels or with direct contact. Prevent vapour build up and direct eye or skin contact. Over exposure may result in cardiac arrhythmias (irregular beating or arrest of the heart) in sensitive individuals. Individuals with pre-existing medical conditions may be at increased risk if over exposed.
Eye	Direct contact with evaporating liquid may result in cold burns, similar to frostbite injury, with possible permanent damage.
Inhalation	Asphyxiant. Effects are proportional to oxygen displacement. Acts as a simple asphyxiant by displacing oxygen in the lungs thereby diminishing the supply of oxygen to the blood and tissues.
Skin	Direct contact with the liquefied material or escaping compressed gas may cause cold burns similar to frostbite injury.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity data	DIFLUOROMETHANE (HFC-32) (75-10-5) LC50 (inhalation) 1810 g/m ³ (mouse) TCLo (inhalation) 50000 ppm/6 hrs/6-15 days of pregnancy (rat)

PENTAFLUOROETHANE (HFC-125) (354-33-6)
 LC50 (inhalation) 2735 g/m³/2 hours (mouse)

12. ECOLOGICAL INFORMATION

Toxicity	No information provided.
Persistence and degradability	No information provided.
Bioaccumulative potential	No information provided.
Mobility in soil	No information provided.
Other adverse effects	Global warming has been predicted as a potential consequence of the emission of this product.

13. DISPOSAL CONSIDERATIONS

Waste disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



LAND TRANSPORT (ADG)

UN number	1078
Proper shipping name	REFRIGERANT GAS, N.O.S.
DG class/ Division	2.2
Subsidiary risk(s)	None Allocated
Packing group	None Allocated
GTEPG	2C2
Hazchem code	2TE
Other information	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.

SEA TRANSPORT (IMDG / IMO)

AIR TRANSPORT (IATA / ICAO)

15. REGULATORY INFORMATION

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Inventory Listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information	<p>The storage of significant quantities of gas cylinders must comply with AS4332. The storage and handling of gases in cylinders.</p> <p>ASPHYXIANT GASES: Asphyxiант gases may displace oxygen, leading to oxygen deficiency. Where oxygen content is low, effects may include: 12-16% oxygen: increased breathing/ pulse rate, lack of coordination; 10-14%: mental disturbance, fatigue, breathing stress; 6-10%: vomiting, collapse and possible unconsciousness; 0-6%: convulsions, respiratory collapse and death.</p>
------------------------	--

ASPHYXIANTS (1): When present in the atmospheres in high concentrations, asphyxiants reduce the oxygen concentration by displacement. Atmospheres deficient in oxygen do not provide adequate sensory warning of danger and most simple asphyxiants are odourless. Therefore it is not appropriate to recommend an exposure standard for each asphyxiant, but to maintain oxygen concentrations. However, some asphyxiants may be given an exposure standard due to the potential for narcotic effects at high concentrations or an explosion hazard.

ASPHYXIANTS (2): There is a significant hazard associated with workers entering poorly ventilated areas (eg. tanks) where oxygen may be deficient. An air supplied breathing apparatus may be required if adequate ventilation is not ensured.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Revision history

Revision	Description
2.0	Standard SDS Review.
1.0	Initial SDS creation

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au.

Revision: 2
SDS Date: 08 January 2014

End of SDS