

MATERIAL SAFETY DATA SHEET

1017

Product Name **LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE
NITROGEN**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name **BOC LIMITED (AUSTRALIA)**
Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web Site <http://www.boc.com.au/>

Synonym(s) 1017 - MSDS NUMBER • 2940022NR - PART NUMBER • BOC LESS THAN 8300 PPM HYDROGEN SULFIDE
BALANCE NITROGEN • LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE NITROGEN • PRODUCT
CODE: 292 • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS
SDS Date 19 Feb 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
HYDROGEN SULPHIDE	H ₂ S	7783-06-4	<0.83%
NITROGEN	N ₂	7727-37-9	>99.17%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Observe for premonitory signs of pulmonary oedema. Treatment is symptomatic and supportive.

Product Name **LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE NITROGEN**

5. FIRE FIGHTING MEASURES

Flammability	Non flammable gas.
Fire and Explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Ensure work area is thoroughly ventilated before re-entry.
Extinguishing	Use water fog to cool containers from protected area.
Hazchem Code	2TE

6. ACCIDENTAL RELEASE MEASURES

Spillage	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.
-----------------	--

7. STORAGE AND HANDLING

Storage	Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement. Do not drop, roll or drag cylinders. The uncontrolled release of any gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.


8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Hydrogen sulfide	ASCC (AUS)	10	14	15	21
	Nitrogen	ASCC (AUS)	Asphyxiant			

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE Wear safety boots, cotton or leather gloves, coveralls and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS	Solubility (Water)	2.3 L/L (Hydrogen sulphide)
Odour	ROTTEN EGG ODOUR	Specific Gravity	NOT APPLICABLE
pH	NOT APPLICABLE	% Volatiles	100 %
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	0.97 (Air = 1) (Approximately)	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT APPLICABLE		
Cylinder Pressure	13000 kPa @ 15°C		

Product Name **LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE
NITROGEN**

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid contact with incompatible substances.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), metals, metal oxides, alkalis (eg. hydroxides), lithium, ozone, titanium and lithium tetrahydroaluminate under specific conditions. Corrosive when moist. Copper and copper alloys unsuitable for use with hydrogen sulphide.
Decomposition	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes. This product also contains small amounts of Hydrogen sulphide which may result in depression and damage to the central nervous system.
Eye	Hydrogen sulphide can cause inflammation and irritation at concentrations below 10 ppm. Symptoms disappear when exposure ceases, but in severe cases damage may be permanent. Persons with potential exposure should not wear contact lenses.
Inhalation	Irritant. When released into air the concentrations are diluted. Hydrogen sulphide has an unpleasant odour above 0.12 ppm but odour is not an adequate warning due to paralysis of sense of smell. At 200 to 250 ppm, hydrogen sulphide causes severe irritation as well as symptoms such as headache, nausea, vomiting and dizziness. High level exposure may result in systemic poisoning, particularly on the nervous system. Unconsciousness may follow, and this is very rapid at concentrations above 1000 ppm. High level exposure may result in paralysis of the respiratory centre.
Skin	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	HYDROGEN SULPHIDE (7783-06-4) LC50 (Inhalation): 444 ppm (rat)

12. ECOLOGICAL INFORMATION

Environment	Microorganisms in soil and water are involved in oxidation-reduction reactions which oxidise hydrogen sulphide to elemental sulphur. Not anticipated to bioaccumulate or concentrate in the food chain.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport	Ensure cylinder is separated from driver and foodstuffs. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.
------------------	--



Product Name **LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE
NITROGEN**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	COMPRESSED GAS, N.O.S.				
UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 7 (S7) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

Application Method: Gas regulator of suitable pressure and flow rating fitted to cylinder valve or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.
BEI - Biological Exposure Indice(s)
CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.
CNS - Central Nervous System.
EINECS - European INventory of Existing Commercial chemical Substances.
IARC - International Agency for Research on Cancer.
M - moles per litre, a unit of concentration.
mg/m3 - Milligrams per cubic metre.
NOS - Not Otherwise Specified.
NTP - National Toxicology Program.
OSHA - Occupational Safety and Health Administration.
pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm - Parts Per Million.
RTECS - Registry of Toxic Effects of Chemical Substances.
TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711

Product Name **LESS THAN 8300 PPM HYDROGEN SULPHIDE BALANCE
NITROGEN**

Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

SDS Date: 19 Feb 2010

End of Report