

SAFETY DATA SHEET

1002

Product Name **LESS THAN 1.5% ETHYLENE BALANCE AIR**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web Site <http://www.boc.com.au/>
Synonym(s) 1002 - SDS NUMBER · PRODUCT CODES: 285, 288 · SPECIAL GAS MIXTURE
Use(s) CALIBRATION · INDUSTRIAL APPLICATIONS
SDS Date 30 January 2012

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number	1956	DG Division	2.2
Packing Group	None Allocated	Subsidiary Risk(s)	None Allocated
Hazchem Code	2TE		

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	Cas No.	Content (v/v)
ETHYLENE	C ₂ -H ₄	74-85-1	<1.5%
AIR	Not Available	Not Available	>98%

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. If other than minor symptoms are displayed, seek immediate medical attention. An inhalation hazard is not anticipated under normal conditions of use. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Product Name **LESS THAN 1.5% ETHYLENE BALANCE AIR**

Fire and Explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot.		
Extinguishing	Use water fog to cool containers from protected area.		
Hazchem Code	2TE	2	Water Fog (or fine water spray if fog unavailable)
		T	Self Contained Breathing apparatus and protective gloves.
		E	Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Spillage	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.
-----------------	--

7. STORAGE AND HANDLING

Storage	Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Ethylene	SWA (AUS)	Asphyxiant			

Biological Limits No biological limit allocated.

Engineering Controls No special precautions are normally required when handling this product. Maintain vapour levels below the recommended exposure standard.

PPE

Eye / Face	Wear safety glasses.
Hands	Wear leather gloves.
Body	Wear safety boots.
Respiratory	Not required under normal conditions of use.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS
Odour	SWEET ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT APPLICABLE

Product Name LESS THAN 1.5% ETHYLENE BALANCE AIR

Solubility (water)	NOT AVAILABLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
% Volatiles	100 %
Cylinder pressure (when full)	13000 kPa @ 13°C

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Ethylene explodes spontaneously when mixed with chlorine in sunlight or UV irradiation. Phytotoxic. Reacts vigorously with some oxidising agents. Violent polymerisation catalysed by copper above 400°C and 54 bar.
Hazardous Decomposition Products	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Non toxic gas. As the amount of oxygen inhaled is increased, chest tightness, burning pains and coughing spasms may occur. Other symptoms of hyperoxia include cramps, nausea, dizziness, hypothermia, amblyopia (loss of vision), bradycardia, fainting spells and convulsions capable of causing death. Over exposure at normal or elevated pressure may result in severe thickening and scarring of lung tissues. Not carcinogenic or mutagenic.
Eye	Non irritant.
Inhalation	Non irritant. Adverse health effects are not anticipated under normal conditions of use.
Skin	Non irritant.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment	No known ecological damage is caused by this product.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1956	1956	1956
Proper Shipping Name	COMPRESSED GAS, N.O.S. (contains air)	COMPRESSED GAS, N.O.S.	COMPRESSED GAS, N.O.S. (contains air)

Product Name **LESS THAN 1.5% ETHYLENE BALANCE AIR**

DG Class/ Division	2.2	2.2	2.2
Subsidiary Risk(s)	None Allocated	None Allocated	None Allocated
Packing Group	None Allocated	None Allocated	None Allocated
GTEPG	2C1		
Hazchem Code	2TE		
Other Information	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.		

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)
Inventory Listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional Information	The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.
------------------------	--

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this ChemAlert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	mg/m ³	Milligrams per Cubic Metre
	PEL	Permissible Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	TLV	Threshold Limit Value
	TWA/OEL	Time Weighted Average or Occupational Exposure Limit

Revision History

Product Name **LESS THAN 1.5% ETHYLENE BALANCE AIR**

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Revision: 2
SDS Date: 30 January 2012

End of SDS