

SAFETY DATA SHEET

1205

Product Name **FROM 3 TO 80 PPM NITROGEN DIOXIDE BALANCE HELIUM****1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

Supplier Name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web Site <http://www.boc.com.au/>

Synonym(s) 1205 - SDS NUMBER • BOC FROM 3 TO 80 PPM NITROGEN DIOXIDE BALANCE HELIUM • PRODUCT CODES: 285, 288 • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS Date 29 Mar 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
NITROGEN DIOXIDE	N-O ₂	10102-44-0	3.0E-4-8.0E-4%
HELIUM	He	7440-59-7	>99.99%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability	Non flammable.
Fire and Explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot.
Extinguishing	Use water fog to cool containers from protected area.
Hazchem Code	2TE

6. ACCIDENTAL RELEASE MEASURES

Spillage	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.
-----------------	--

7. STORAGE AND HANDLING

Storage	Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.


8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Helium	ASCC (AUS)	Asphyxiant			
	Nitrogen dioxide	ASCC (AUS)	3	5.6	5	9.4

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: a Type NO (Nitrogen Oxides) or an Air-line respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS	Solubility (Water)	REACTS
Odour	ODOURLESS	Specific Gravity	NOT APPLICABLE
pH	NOT APPLICABLE	% Volatiles	100 %
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT APPLICABLE		
Cylinder Pressure	13,000 kPa @ 15°C		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.
Material to Avoid	Nitric oxide reacts in air to form nitrogen dioxide which is highly oxidising and reacts violently with fluorine and chlorine in the presence of moisture.
Decomposition	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Asphyxiant. A toxic and asphyxiant mixture if directly inhaled. When released into air the concentration of nitrogen dioxide is diluted. Nitrogen dioxide concentrations above 25 ppm may have an immediate effect of irritating the nose and throat followed by delayed onset of respiratory difficulties. Over exposure to concentrations of nitrogen dioxide above 5 ppm may result in sudden onset pulmonary oedema which can be rapidly fatal. The effects of nitric oxide may be observed before the asphyxiation hazard due to other gases present. Mutation data reported for nitrogen dioxide. Results in chronic irritation of the respiratory tract in low doses.
Eye	Irritant. Contact may result in irritation. Contact lenses should not be worn when using this product.
Inhalation	Irritant. An asphyxiant mixture if directly inhaled.
Skin	Irritant. Contact may result in irritation.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	NITROGEN DIOXIDE (10102-44-0) LC50 (Inhalation): 88 ppm/4 hours (rat) LCLo (Inhalation): 200 ppm/1 minute (human) TCLo (Inhalation): 6200 ppb/10 minutes (man)

12. ECOLOGICAL INFORMATION

Environment	Nitrogen oxides react with volatile organic compounds to produce ozone, a principal factor in photochemical smog. Will form nitric acid in contact with water. Nitrates can persist for prolonged periods in water. Not expected to concentrate in the food chain.
--------------------	--

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.
------------------	--



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	COMPRESSED GAS, N.O.S.				
UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information	The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.
-------------------------------	--

Product Name **FROM 3 TO 80 PPM NITROGEN DIOXIDE BALANCE HELIUM**

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

SDS Date: 29 Mar 2010

End of Report