

SAFETY DATA SHEET

1016

Product Name **BETWEEN 2 PPM TO 2,900 PPM SULPHUR DIOXIDE BALANCE AIR**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web Site <http://www.boc.com.au/>
Synonym(s) 1016 - SDS NUMBER • PRODUCT CODE: 292 • SPECIAL GAS MIXTURE
Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS
SDS Date 29 Mar 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
SULPHUR DIOXIDE	S-O ₂	7446-09-5	2.0E-4-0.29%
AIR	Not Available	Not Available	remainder

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type B (Inorganic and acid gas) respirator where an inhalation risk exists. Apply artificial respiration if not breathing. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Adrenaline may be useful in presence of bronchospasm.

5. FIRE FIGHTING MEASURES

Flammability	Non flammable. May evolve toxic gases if strongly heated.
Fire and Explosion	No fire or explosion hazard exists.
Extinguishing	Prevent contamination of drains or waterways.
Hazchem Code	2TE

6. ACCIDENTAL RELEASE MEASURES

Spillage	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices. Always ensure regulator is set to deliver a pressure below equipment pressure rating and any relief valve setting. In an emergency evacuate the area and notify emergency services. Monitor concentration in confined spaces. Contact the manufacturer for guidance. Leak checking may be done by pressure drop test, gas detection tubes or by using soapy water on joints and outlets. Shut cylinder valve to stop gas leaks if possible and safe to do so.
----------	--

7. STORAGE AND HANDLING

Storage	Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.


8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Sulphur dioxide	ASCC (AUS)	2	5.2	5	13

Biological Limits	No biological limit allocated.
-------------------	--------------------------------

Engineering Controls	Avoid inhalation. Use in well ventilated areas. Protective equipment should be worn if levels exceed recommended exposure standards. Maintain vapour levels below the recommended exposure standard.
----------------------	--

PPE	Wear splash-proof goggles, safety boots and cotton or leather gloves. Only experienced and properly trained people should use this product. At high vapour levels, wear: a Full-face Type B (Inorganic and Acid gas) or an Air-line respirator.
-----	---



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS	Solubility (Water)	0.1128 kg/kg (Sulphur dioxide)
Odour	PUNGENT IRRITATING ODOUR	Specific Gravity	NOT APPLICABLE
pH	NOT APPLICABLE	% Volatiles	100 %
Vapour Pressure	NOT AVAILABLE	Flammability	NON FLAMMABLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT RELEVANT
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT RELEVANT
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT RELEVANT
Evaporation Rate	NOT APPLICABLE		
Cylinder Pressure	13000 kPa @ 15°C		

10. STABILITY AND REACTIVITY

Material to Avoid	Incompatible with chlorates, peroxides, chromates, dichromates, permanganates, oxygen difluoride. Sulphur dioxide is highly corrosive to ordinary steel in the presence of moisture.
Decomposition	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Asphyxiant. Uncontrolled release of compressed gas may result in physical injuries. Regular exposure to sulphur dioxide may deaden the sense of smell and cause irritation of the mucous membranes of the upper respiratory gastrointestinal tract. Chronic bronchitic emphysema has been documented. Chronic conjunctivitis may result. Dental degradation has been reported.
Eye	Irritant. Sulphur dioxide concentrations of 8 to 12 ppm can irritate the eye. Do not wear contact lenses.
Inhalation	Severe irritant. Sulphur dioxide concentrations above 8 ppm will irritate the nose. At 150 ppm extreme irritation is only tolerable for a few minutes. At 500 ppm a sense of suffocation is felt. Inhalation may have fatal consequences as a result of spasm, inflammation and oedema of the larynx and bronchi, chemical pneumonitis and pulmonary oedema.
Skin	Irritant. Contact may result in irritation. Sulphur dioxide irritates the skin. Skin irritation is aggravated by sweating.
Ingestion	Exposure is considered unlikely.
Toxicity Data	SULPHUR DIOXIDE (7446-09-5) LC50 (Inhalation): 2520 ppm/1 hour (rat) LCLo (Inhalation): 1000 ppm/10 minutes (human) TCLo (Inhalation): 3 ppm/5 days (human)

12. ECOLOGICAL INFORMATION

Environment	Sulphur dioxide in air is oxidised to sulphuric acid, which is a major component of acid rain. Acid rain has been associated with accelerated leaching of heavy metals from plumbing systems and generally fixed sites such as insoluble deposits and ores, and with bioaccumulation of heavy metals, especially mercury, in fish. Sulphur dioxide is harmful to aquatic life in very low concentrations.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport	Ensure cylinder is separated from driver and foodstuffs.
------------------	--



CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	COMPRESSED GAS, N.O.S.				
UN No.	1956	DG Class	2.2	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	2TE	EPG	2C1

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information	The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.
-------------------------------	--

Product Name**BETWEEN 2 PPM TO 2,900 PPM SULPHUR DIOXIDE BALANCE AIR**

Application Method: Gas regulator of suitable pressure and flow rating fitted to cylinder valve or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

SDS Date: 29 Mar 2010

End of Report