

## SAFETY DATA SHEET

# 1404

LESS THAN 23% OXYGEN BALANCE HELIUM **Product Name** 

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name BOC LIMITED (AUSTRALIA)** 

**Address** 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

131 262, (02) 8874 4400 **Telephone** Fax 132 427 (24 hours)

1800 653 572 (24/7) (Australia only) **Emergency** 

**Web Site** http://www.boc.com.au/

1404 - SDS NUMBER • PRODUCT CODE: 285, 288 • SPECIAL GAS MIXTURE Synonym(s)

**CALIBRATION • INDUSTRIAL APPLICATIONS** Use(s)

**SDS Date** 29 Mar 2010

### 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1956 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

**EPG Packing Group** Hazchem Code 2TE 2C1 None Allocated

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content	
OXYGEN	O2	7782-44-7	<23%	
HELIUM	Не	7440-59-7	>77%	

# 4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice,

contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically

### 5. FIRE FIGHTING MEASURES

**Flammability** Non flammable.

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying Fire and

**Explosion** water from a protected location. Do not approach cylinders or containers suspected of being hot.

**Extinguishing** Use water fog to cool containers from protected area.

**Hazchem Code** 2TE

ChemAlert.

**RMT** 

Reviewed: 29 Mar 2010 Printed: 29 Mar 2010

# **LESS THAN 23% OXYGEN BALANCE HELIUM**

### 6. ACCIDENTAL RELEASE MEASURES

**Spillage** 

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

### 7. STORAGE AND HANDLING

Storage Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling.

Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm

level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The

uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder

movement.

### 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

**Exposure Stds** 

Ingredient	Deference	7	TWA		STEL		
	Reference	ppm	mg/m3	ppm	mg/m3		
Helium	ASCC (AUS)		Asphyxiant				

**Biological Limits** 

No biological limit allocated.

Engineering Controls

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately

ventilated or gas tested.

PPF

Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).







## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance COLOURLESS GAS** Solubility (Water) **INSOLUBLE** Odour **ODOURLESS** Specific Gravity NOT APPLICABLE **NOT APPLICABLE** % Volatiles 100 % На Vapour Pressure **NOT AVAILABLE Flammability** NON FLAMMABLE Vapour Density **NOT AVAILABLE Flash Point** NOT RELEVANT **Boiling Point NOT AVAILABLE Upper Explosion Limit** NOT RELEVANT **Melting Point NOT AVAILABLE Lower Explosion Limit** NOT RELEVANT **Evaporation Rate NOT APPLICABLE Cylinder Pressure** 13000 kPa @ 15°C

## 10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to AvoidCompatible with most commonly used materials.DecompositionMay evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.



Page 2 of 4 RMT

Reviewed: 29 Mar 2010 Printed: 29 Mar 2010

#### **Product Name**

## LESS THAN 23% OXYGEN BALANCE HELIUM

# 11. TOXICOLOGICAL INFORMATION

**Health Hazard** Summary

Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes.

Eve Non irritant.

Inhalation Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.

Skin Non irritant

Ingestion Ingestion is considered unlikely due to product form.

**Toxicity Data** No LD50 data available for this product.

### 12. ECOLOGICAL INFORMATION

**Environment** Product is not harmful to the environment.

### 13. DISPOSAL CONSIDERATIONS

Cylinders should be returned to the manufacturer or supplier for disposal of contents. **Waste Disposal** 

Legislation Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

**Transport** Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.



#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

**Shipping Name** COMPRESSED GAS, N.O.S.

UN No. 1956 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

**Packing Group Hazchem Code** 2TE **EPG** None Allocated 2C1

### 15. REGULATORY INFORMATION

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

**AICS** All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

### 16. OTHER INFORMATION

Additional Information The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration. mg/m3 - Milligrams per cubic metre.



Page 3 of 4 **RMT** 

Reviewed: 29 Mar 2010

Printed: 29 Mar 2010

# Product Name LESS THAN 23% OXYGEN BALANCE HELIUM

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

#### **HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### **Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

#### Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au

SDS Date: 29 Mar 2010 End of Report



Reviewed: 29 Mar 2010 Printed: 29 Mar 2010