

SAFETY DATA SHEET

1698

Product Name BETWEEN 5.2 AND 8.4% HYDROGEN SULPHIDE BALANCE

NITROGEN

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

Telephone 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 1698 - MSDS NUMBER • PRODUCT CODE: 292 • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS Date 26 Mar 2010

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

RISK PHRASES

R26 Very toxic by inhalation.

SAFETY PHRASES

S16 Keep away from sources of ignition - No smoking.

S36 Wear suitable protective clothing.

S38 In case of insufficient ventilation, wear suitable respiratory equipment.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

S61 Avoid release to the environment. Refer to special instructions / safety data sheets.

S9 Keep container in a well ventilated place.

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1953 DG Class 2.3 Subsidiary Risk(s) 2.1

Packing Group None Allocated Hazchem Code 2PE EPG 2A4

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
HYDROGEN SULPHIDE	H2S	7783-06-4	5.2-8.4%
NITROGEN	N2	7727-37-9	remainder



BETWEEN 5.2 AND 8.4% HYDROGEN SULPHIDE BALANCE NITROGEN

4. FIRST AID MEASURES

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to Eve

stop by a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor, or for at least 15 minutes.

If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Inhalation

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if breathing is difficult. Seek immediate medical attention. For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a

doctor.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor If inhalation has occurred observe for premonitary signs of pulmonary oedema. Otherwise, treatment is

symptomatic and supportive. Treat for cold burns if severe liquid contact.

5. FIRE FIGHTING MEASURES

Flammability Non flammable gas. May evolve toxic gases (sulphur oxides) when heated to decomposition. Do not expose to

heat and ignition sources.

Fire and Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying

Explosion water from a protected location. Do not approach cylinders or containers suspected of being hot.

Extinguishing Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve.

Hazchem Code 2PE

6. ACCIDENTAL RELEASE MEASURES

Spillage If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not

attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area

constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic

and emergency exits.

Handling Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide

or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand

truck for cylinder movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Deference	1	TWA		STEL	
	Reference	ppm	mg/m3	ppm	mg/m3	
Hydrogen sulfide	ASCC (AUS)	10	14	15	21	
Nitrogen	ASCC (AUS)		Asphyxiant			

Biological Limits No biological limit allocated.

Engineering Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof **Controls** extraction ventilation is recommended. Flammable or explosive vapours may accumulate in confined or poorly ventilated areas. Vapours may travel some distance to an ignition source and flash back. Maintain atmospheric

levels below the recommended exposure standard.

PPF Wear splash-proof goggles, safety boots, rubber gloves and an Air-line respirator or self Contained Breathing

Apparatus (SCBA). Only experienced and trained person should use this product.











Page 2 of 5 **RMT**

Reviewed: 26 Mar 2010

Printed: 26 Mar 2010

BETWEEN 5.2 AND 8.4% HYDROGEN SULPHIDE BALANCE **NITROGEN**

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance COLOURLESS GAS Solubility (Water) 2.3 L/L (Hydrogen sulphide)

Odour **ROTTEN EGG ODOUR Specific Gravity NOT APPLICABLE**

NOT APPLICABLE % Volatiles 100 %

Vapour Pressure NOT AVAILABLE **Flammability** NON FLAMMABLE NOT RELEVANT **Vapour Density** 1.2 (Air =1) (Hydrogen sulphide) **Flash Point** NOT RELEVANT **Boiling Point** -60.3°C (Hydrogen sulphide) **Upper Explosion Limit**

Melting Point NOT AVAILABLE Lower Explosion Limit 5.2 % (Hydrogen sulphide)

Evaporation Rate NOT APPLICABLE

Critical Pressure 9,010 kPa (Hydrogen sulphide) **Critical Temperature** 100.4°C (Hydrogen sulphide)

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to Avoid Incompatible with oxidising agents (eq. hypochlorites), metals, metal oxides, nitrogen trichloride, alkalis

(eg. soda lime), heat and ignition sources. Corrodes most materials when moist.

Decomposition May evolve toxic gases (sulphur oxides) when heated to decomposition.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary

Very toxic by inhalation - severe irritant. Over exposure to hydrogen sulphide may result in headache, nausea, vomiting, diarrhea, vertigo, amnesia, dizziness, apnea, palpitations, tachycardia, hypotension, muscle cramps, weakness, disorientation, and coma. Higher concentrations may also result in result in respiratory paralysis, asphyxial seizures, and death. Cold burns may be caused by evaporating liquid. Persons with potential exposure

should not wear contact lenses

Eye Severe irritant. Inflammation and irritation can occur at concentrations below 10 vppm. Above 50 vppm, there is

intense tearing, blurring of vision and photophobia. Most symptoms disappear when exposure ceases, however in serious cases permanent eye damage can occur. Cold burns may be caused by evaporating liquid. Persons with

potential exposure should not wear contact lenses.

Very toxic by inhalation - severe irritant. Exposure to concentrations approaching 250 ppm causes irritation of Inhalation

mucus membranes, conjunctivitis, photophobia, lacrimation, corneal opacity, rhinitis, bronchitis, cyanosis, and acute lung injury. At concentrations of 250 ppm to 500 ppm, signs and symptoms include headache, nausea, vomiting, diarrhea, vertigo, amnesia, dizziness, apnea, palpitations, tachycardia, hypotension, muscle cramps, weakness, disorientation, and coma. At concentrations of 750 ppm to 1000 ppm, victims may experience abrupt physical collapse or "knock down". Higher concentrations may also result in result in respiratory paralysis,

asphyxial seizures, and death.

Skin Severe irritant. Over exposure to hydrogen sulphide may result in severe pain, and erythema, especially in moist

areas. Cyanosis may be noted following severe exposure.

Ingestion is considered unlikely due to product form. However, ingestion of liquid may result in burns to the mouth Ingestion

and throat.

Toxicity Data HYDROGEN SULPHIDE (7783-06-4)

LC50 (Inhalation): 444 ppm (rat)

12. ECOLOGICAL INFORMATION

Environment Microorganisms in soil and water are involved in oxidation-reduction reactions which oxidise hydrogen sulphide to

elemental sulphur. Not anticipated to bioaccumulate or concentrate in the food chain.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Return to manufacturer for recycling/ reuse. Contact Waste Disposal Authorities in your state for further details

and required approvals.

Legislation Dispose of in accordance with relevant local legislation.

ChemAlert.

Page 3 of 5 **RMT**

Reviewed: 26 Mar 2010

Printed: 26 Mar 2010

BETWEEN 5.2 AND 8.4% HYDROGEN SULPHIDE BALANCE NITROGEN

14. TRANSPORT INFORMATION

Transport

Ensure cylinder is separated from driver and foodstuffs. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.





CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S.

UN No. 1953 DG Class 2.3 Subsidiary Risk(s) 2.1

Packing Group None Allocated Hazchem Code 2PE EPG 2A4

15. REGULATORY INFORMATION

Poison Schedule Classified as a Schedule 7 (S7) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and

Poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas withdrawal: regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of

Page 4 of 5

RMT

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010



BETWEEN 5.2 AND 8.4% HYDROGEN SULPHIDE BALANCE NITROGEN

the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au

SDS Date: 26 Mar 2010 End of Report



Page 5 of 5 RMT

Reviewed: 26 Mar 2010 Printed: 26 Mar 2010