

SAFETY DATA SHEET

1837

Product Name 4 COMPONENT MIXTURE (CO, C3H8, O2, BALANCE N2)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

Telephone 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 1837 - MSDS NUMBER • PRODUCT CODE: 285, 288 • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS Date 26 Mar 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. 1956 DG Class 2.2 Subsidiary Risk(s) None Allocated

Packing Group None Allocated Hazchem Code 2TE EPG 2C1

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
OXYGEN	O2	7782-44-7	19%
PROPANE	C3-H8	74-98-6	0.2%
CARBON MONOXIDE	C-O	630-08-0	<0.04%
NITROGEN	N2	7727-37-9	remainder

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained

Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice,

contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically



Product Name

4 COMPONENT MIXTURE (CO, C3H8, O2, BALANCE N2)

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying **Explosion** water from a protected location. Do not approach cylinders or containers suspected of being hot.

Extinguishing Use water fog to cool containers from protected area.

Hazchem Code 2TE

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area

constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The

uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder

movement.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference		TWA		STEL	
	Reference	ppm	mg/m3	ppm	mg/m3	
Carbon monoxide	ASCC (AUS)	30	34			
Nitrogen	ASCC (AUS)		Asphyxiant			
Propane	ASCC (AUS)		Asphyxiant			

Biological Limits

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end- exhaled air	End of shift	20 ppm

Engineering **Controls**

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure standard.

PPE

Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: an Air-line respirator or self Contained Breathing Apparatus (SCBA).







9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance COLOURLESS GAS Solubility (Water) **INSOLUBLE** Odour **ODOURLESS Specific Gravity NOT APPLICABLE** рΗ **NOT APPLICABLE** % Volatiles 100 % Vapour Pressure **NOT AVAILABLE Flammability** NON FLAMMABLE Vapour Density **NOT AVAILABLE Flash Point NOT AVAILABLE Boiling Point NOT AVAILABLE Upper Explosion Limit** NOT RELEVANT **Melting Point NOT AVAILABLE Lower Explosion Limit** NOT RELEVANT

ChemAlert.

Page 2 of 5 **RMT**

Reviewed: 26 Mar 2010

Printed: 26 Mar 2010

Product Name 4 COMPONENT MIXTURE (CO, C3H8, O2, BALANCE N2)

Evaporation Rate NOT APPLICABLE

Cylinder Pressure 13000 kPa @ 15°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to Avoid Carbon monoxide can react with iron, nickel and other metals. Below 3,500 kPa corrosion is negligible

and common materials can be used. Incompatible with acrylaldehyde, aziridine, sodium peroxide.

Corrosive when moist.

Decomposition May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas - toxic. Carbon monoxide effects depend on the percentage of carboxyhaemoglobin: 10-20% mild headache and breathlessness on mild exertion; 20-30% headache, irritability, rapid fatigue and impaired memory; 30-40% severe headache, weakness, nausea, vomiting, dizziness, visual impairment and confusion; 40-50% increasing confusion, ataxia and collapse; 50-60% coma; >80% rapid death. Chronic exposure to carbon monoxide may result in an increase in cardiovascular problems. Can aggravate some diseases of the cardiovascular system such as coronary artery disease. The effect is enhanced by cigarette smoking. Adverse behavioural effects have been noted including impairment of vigilance, co-ordination, timing, behaviour, visual perception and certain cognitive functions. Some adaptation occurs in individuals repeatedly exposed to moderate concentrations. Developmental defects on foetuses can occur without maternal symptoms.

Eye Non irritant

Inhalation Irritant. Over exposure to carbon monoxide may result in rapid breathing, nausea, lack of coordination,

unconsciousness and coma. Reacts with blood haemoglobin to prevent oxygen uptake.

Skin Non irritant

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data CARBON MONOXIDE (630-08-0)

LC50 (Inhalation): 1807 ppm/4H (rat) LCLo (Inhalation): 5000 ppm/5M (human)

12. ECOLOGICAL INFORMATION

Environment

When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect. Carbon monoxide is slowly oxidised in the atmosphere to carbon dioxide.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.





4 COMPONENT MIXTURE (CO, C3H8, O2, BALANCE N2) **Product Name**

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name COMPRESSED GAS, N.O.S.

UN No. 1956 **DG Class** 2.2 Subsidiary Risk(s) None Allocated

Hazchem Code 2TF **FPG Packing Group** None Allocated 2C1

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m3 - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.



Page 4 of 5 **RMT**

Reviewed: 26 Mar 2010

Printed: 26 Mar 2010

Product Name 4 COMPONENT MIXTURE (CO, C3H8, O2, BALANCE N2)

Prepared By Risk Management Technologies

5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

> SDS Date: 26 Mar 2010 End of Report

