

SAFETY DATA SHEET

2014

Product Name 10 COMPONENT MIXTURE (BALANCE NITROGEN) (# 2014)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113

Telephone 131 262, (02) 8874 4400

Fax 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web Site http://www.boc.com.au/

Synonym(s) 2014 - MSDS NUMBER · PRODUCT CODES: 285 288 · SPECIAL GAS MIXTURE

Use(s) CALIBRATION · INDUSTRIAL APPLICATIONS

SDS Date 23 February 2012

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number 1956 DG Division 2.2

Packing Group None Allocated Subsidiary Risk(s) None Allocated

Hazchem Code 2TE

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Formula	Cas No.	Content (v/v)
ACETYLENE	C2-H2	74-86-2	0.0005%
BUTANE	C4-H10	106-97-8	0.0005%
ETHANE	C2-H6	74-84-0	0.0005%
ETHYLENE	C2-H4	74-85-1	0.0005%
ISOBUTANE	C4-H10	75-28-5	0.0005%
METHANE	C-H4	74-82-8	0.0005%
PENTANE	C5-H12	109-66-0	0.0005%
PROPANE	C3-H8	74-98-6	0.0005%
PROPYLENE	C3-H6	115-07-1	0.0005%
NITROGEN	N2	7727-37-9	Remainder

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

ChemAlert.

Page 1 of 6 SDS Date: 23 Feb 2012

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and Explosion Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by

applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being

hot.

Extinguishing Use water fog to cool containers from protected area.

Hazchem Code 2TE

2 Water Fog (or fine water spray if fog unavailable)

T Self Contained Breathing apparatus and protective gloves.

E Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Spillage If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow

to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling Cylinders should also be stored in a dry well ventilated area constructed of

from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic

and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

Ingredient	Reference	TWA		STEL	
Ingredient		ppm	mg/m³	ppm	mg/m³
Acetylene	SWA (AUS)	Asphyxiant			
Butane	SWA (AUS)	800	1900		
Ethane	SWA (AUS)	Asphyxiant			
Ethylene	SWA (AUS)	Asphyxiant			
Isobutane	SWA (AUS)	1000			
Methane	SWA (AUS)	Asphyxiant			
Nitrogen	SWA (AUS)	Asphyxiant			
Pentane	SWA (AUS)	600	1770	750	2210
Propane	SWA (AUS)	Asphyxiant			
Propylene	SWA (AUS)	Asphyxiant			

Biological Limits No biological limit allocated.



SDS Date: 23 Feb 2012

Engineering Controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

PPE

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

COLOURLESS GAS Appearance SLIGHT ODOUR Odour NON FLAMMABLE **Flammability** Flash point NOT RELEVANT **Boiling point** NOT AVAILABLE NOT AVAILABLE **Melting point** NOT APPLICABLE **Evaporation rate NOT APPLICABLE NOT AVAILABLE** Vapour density Specific gravity NOT APPLICABLE Solubility (water) 0.0149 L/L (Nitrogen) Vapour pressure NOT AVAILABLE **Upper explosion limit** NOT RELEVANT Lower explosion limit NOT RELEVANT **Autoignition temperature** NOT AVAILABLE **Decomposition temperature** NOT AVAILABLE Viscosity NOT AVAILABLE Partition coefficient NOT AVAILABLE

% Volatiles 100 %

Cylinder pressure (when full) 13,000 kPa @ 15°C

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to Avoid Avoid Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

Material to Avoid

Compatible with most commonly used materials. Ethylene explodes spontaneously when mixed with chlorine in sunlight or UV irradiation. Phytotoxic. Reacts vigorously with oxidising agents. Acetylene can form explosive acetylides with unalloyed copper, silver, mercury and brasses containing more

than 66% copper and brazing materials containing copper and silver.

Hazardous Decomposition

Products

This material will not decompose to form hazardous products.

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture

ChemAlert.

SDS Date: 23 Feb 2012

containing no oxygen may result in unconsciousness from the first breath and death may follow in

minutes.

Eye Non irritant.

Inhalation Asphyxiant. Effects are proportional to oxygen displacement. Acts as a simple asphyxiant by

displacing oxygen in the lungs thereby diminishing the supply of oxygen to the blood and tissues.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity Data ACETYLENE (74-86-2)

LCLo (inhalation) 50pph/5M (human) TCLo (inhalation) 20 pph (human)

BUTANE (106-97-8)

LC50 (inhalation) 658000 mg/m3/4H (rat)

METHANE (74-82-8)

LC50 (inhalation) 326 gm/m3/2h (mouse)

PENTANE (109-66-0)

LC50 (inhalation) 364 g/m³/4 hours (rat)
LCLo (inhalation) 325 g/m³/2 hours (mouse)
LD50 (intravenous) 446 mg/kg (mouse)

PROPANE (74-98-6)

LC50 (inhalation) > 800000 ppm/15M (rat)

12. ECOLOGICAL INFORMATION

Environment Product is not harmful to the environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



(ADG) (IMDG / IMO) (IATA / ICAO)

UN Number 1956 1956 1956

Proper Shipping NameCOMPRESSED GAS, N.O.S. (BALANCE NITROGEN)

DG Class/ Division2.22.22.2Subsidiary Risk(s)None AllocatedNone AllocatedNone AllocatedPacking GroupNone AllocatedNone AllocatedNone Allocated

GTEPG 2C1 Hazchem Code 2TE

Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which

SEA TRANSPORT

affect gas storage and transport.

LAND TRANSPORT

15. REGULATORY INFORMATION

ChemAlert.

Page 4 of 6 SDS Date: 23 Feb 2012

AIR TRANSPORT

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard

for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Inventory Listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional Information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this ChemAlert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

GHS Globally Harmonized System

IARC International Agency for Research on Cancer

mg/m³ Milligrams per Cubic Metre
PEL Permissible Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

TLV Threshold Limit Value

TWA/OEL Time Weighted Average or Occupational Exposure Limit

Revision History

Revision	Description
1.0	Standard SDS Review

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.



SDS Date: 23 Feb 2012

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005

Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au

Revision: 1

SDS Date: 23 February 2012

End of SDS



Page 6 of 6 SDS Date: 23 Feb 2012