

SAFETY DATA SHEET

1567

Product Name 6 COMPONENT MIXTURE (C5H12, C5H12, C3H8, C4H10, C4H10, BALANCE N2)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

Telephone 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

Emergency 1800 653 572 (24/7) (Australia only)

Web site http://www.boc.com.au/

Synonym(s) 1567 - MSDS NUMBER • PRODUCT CODES: 288 • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS date 15 March 2013

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

R12 Extremely Flammable.

SAFETY PHRASES

S9 Keep container in a well ventilated place.

Keep away from sources of ignition - No smoking.
 Take precautionary measures against static discharges.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

S53 Avoid exposure - obtain special instructions before use.

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN number 1954 **DG division** 2.1

Packing group None Allocated Subsidiary risk(s) None Allocated

Hazchem code 2SE

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
BUTANE	CAS: 106-97-8 EC: 203-448-7	F+;R12	15 to 30%
ISOBUTANE	CAS: 75-28-5 EC: 200-857-2	F+;R12	5 to 10%
PROPANE	CAS: 74-98-6 EC: 200-827-9	F+;R12	3 to 10%
ISOPENTANE	CAS: 78-78-4 EC: 201-142-8	Xn;R65 F+;R12 Xi;R66 Xn;R67 N;R51/53	1.5 to 4%
PENTANE	CAS: 109-66-0 EC: 203-692-4	Xn;R65 F+;R12 Xi;R66 Xn;R67 N;R51/53	0.5 to 4%



Page 1 of 6 SDS Date: 15 Mar 2013

NITROGEN	CAS: 7727-37-9	Not Available	Remainder	
	EC: 231-783-9			

4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Due to product form and application, ingestion is considered unlikely.

Advice to doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing

switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

Fire and explosionTemperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location.

Do not approach cylinders or containers exposed to fire by applying water from a protected location.

explosive mixtures with air.

Extinguishing Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve. If the gas source

cannot be isolated, do not extinguish the flame, since re-ignition and explosion could occur. Await arrival of emergency services or manufacturer's advisor. Drench and cool cylinders with water spray from protected area at a safe distance. If it is absolutely necessary to extinguish the flame, use only a dry chemical powder extinguisher. Do not move cylinders for at least 24 hours. Avoid shock and

bumps to cylinders.

Hazchem code 2SE

2 Water Fog (or fine water spray if fog unavailable)

S Self Contained Breathing apparatus and protective gloves.

E Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Spillage

If the cylinder is leaking, eliminate all potential ignition sources and evacuate area of personnel. Prevent spreading of vapours through drains and ventilation systems. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

7. STORAGE AND HANDLING

Storage Do not store near sources of ignition or incompatible materials. Cylinders should be stored below

45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor

(preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.



SDS Date: 15 Mar 2013

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m³	ppm	mg/m³
Butane	SWA (AUS)	800	1900		
Isobutane	SWA (AUS)	1000			
Nitrogen	SWA (AUS)	Asphyxiant			
Pentane	SWA (AUS)	600	1770	750	2210
Propane	SWA (AUS)	Asphyxiant			

Biological limits No biological limit allocated.

Engineering controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.

PPE

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

COLOURLESS GAS Appearance PLEASANT ODOUR Odour HIGHLY FLAMMABLE **Flammability NOT AVAILABLE** Flash point NOT AVAILABLE **Boiling point NOT AVAILABLE Melting point** NOT APPLICABLE **Evaporation rate** NOT APPLICABLE Vapour density NOT AVAILABLE NOT APPLICABLE Specific gravity Solubility (water) INSOLUBLE Vapour pressure NOT AVAILABLE **Upper explosion limit** NOT AVAILABLE

Lower explosion limit
Autoignition temperature
Decomposition temperature
Viscosity
Partition coefficient

6 % (Butane in nitrogen)
NOT AVAILABLE
NOT AVAILABLE
NOT AVAILABLE

% Volatiles 100 %

Cylinder pressure (when full) 350 kPa @ 15°C

10. STABILITY AND REACTIVITY

Chemical stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Material to avoid Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), heat and ignition

sources. Do not use natural rubber flexible hoses. Also incompatible (potentially violently) with

oxygen, halogens and metal halides.

Hazardous Decomposition This material will not decompose to form hazardous products other than that already present.

ChemAlert.

Page 3 of 6 SDS Date: 15 Mar 2013

Products

Hazardous Reactions Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes.

Eye Non irritant.

Inhalation Asphyxiant. Effects are proportional to oxygen displacement.

Skin Non irritant.

Ingestion Ingestion is considered unlikely due to product form.

Toxicity data BUTANE (106-97-8)

LC50 (inhalation) 658000 mg/m3/4H (rat)

PROPANE (74-98-6)

LC50 (inhalation) > 800000 ppm/15M (rat)

PENTANE (109-66-0)

LC50 (inhalation) 364 g/m³/4 hours (rat)
LCLo (inhalation) 325 g/m³/2 hours (mouse)
LD50 (intravenous) 446 mg/kg (mouse)

12. ECOLOGICAL INFORMATION

Toxicity No information provided.

Persistence and degradability No information provided.

Bioaccumulative potential No information provided.

Mobility in soil No information provided.

13. DISPOSAL CONSIDERATIONS

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



LAND TRANSPORT SEA TRANSPORT AIR TRANSPORT (ADG) (IMDG / IMO) (IATA / ICAO)

UN number 1954 - - - Proper shipping name COMPRESSED GAS, - -

FLAMMABLE, N.O.S.

Page 4 of 6 SDS Date: 15 Mar 2013



DG class/ Division 2.1 - -

Subsidiary risk(s)None Allocated--Packing groupNone Allocated--

GTEPG 2A1

Hazchem code 2SE

Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which

affect gas storage and transport.

15. REGULATORY INFORMATION

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard

for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Inventory Listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

GHS Globally Harmonized System

IARC International Agency for Research on Cancer LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
PEL Permissible Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

REACH Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

TLV Threshold Limit Value

TWA/OEL Time Weighted Average or Occupational Exposure Limit

Revision history

Revision	Description	
2.0	Standard SDS Review.	
1.0	Standard SDS Review.	



SDS Date: 15 Mar 2013

Page 5 of 6

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au

Revision: 2

SDS Date: 15 March 2013

End of SDS



Page 6 of 6

SDS Date: 15 Mar 2013