

SAFETY DATA SHEET

2249

Product Name 5 COMPONENT MIXTURE, (HYDROGEN SULPHIDE, CARBON MONOXIDE, METHANE AND OXYGEN IN NITROGEN) (2249)

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web site <http://www.boc.com.au/>
Synonym(s) 2249 - MSDS NUMBER • PRODUCT CODES: 292-578, -593, -669, -765, -791, -840, -898, -964, -989 • PRODUCT CODES: 294479, 276PS111 • SPECIAL GAS MIXTURE
Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS
SDS date 01 February 2013

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS (GHS) ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN number 1956 **DG division** 2.2
Packing group None Allocated **Subsidiary risk(s)** None Allocated
Hazchem code 2TE

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
OXYGEN	CAS: 7782-44-7 EC: 231-956-9	O;R8	17 to 20%
METHANE	CAS: 74-82-8 EC: 200-812-7	F+;R12	2.5%
CARBON MONOXIDE	CAS: 630-08-0 EC: 211-128-3	T;R23 Repr.;R61 T;R48/23 F+;R12	<0.05%
HYDROGEN SULPHIDE	CAS: 7783-06-4 EC: 231-977-3	T+;R26 N;R50 F+;R12	<0.005%
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	Remainder

4. FIRST AID MEASURES

Eye None required.

Product Name **5 COMPONENT MIXTURE, (HYDROGEN SULPHIDE, CARBON MONOXIDE, METHANE AND OXYGEN IN NITROGEN) (2249)**

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Ingestion is not considered a potential route of exposure.

Advice to doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability Non flammable.

Fire and explosion This product will support combustion. Temperatures in a fire may cause cylinders to rupture. Cool cylinders exposed to fire by applying water from a protected location. Do not approach cylinders suspected of being hot. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool.

Extinguishing Use water fog to cool containers from protected area.

Hazchem code 2TE

 2 Water Fog (or fine water spray if fog unavailable)

 T Self Contained Breathing apparatus and protective gloves.

 E Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment as detailed in Section 8 of this SDS.

Environmental precautions Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Methods of cleaning up Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

References See Sections 8 and 13 for exposure controls and disposal.

7. STORAGE AND HANDLING

Storage Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement. Do not drop, roll or drag cylinders. The uncontrolled release of any gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Carbon monoxide	SWA (AUS)	30	34	--	--
Hydrogen sulfide	SWA (AUS)	10	14	15	21
Methane	SWA (AUS)	Asphyxiant			
Nitrogen	SWA (AUS)	Asphyxiant			

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end-exhaled air	End of shift	20 ppm

Engineering controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure standard.

PPE

- Eye / Face** Wear safety glasses.
- Hands** Wear leather gloves.
- Body** Wear safety boots.
- Respiratory** Not required under normal conditions of use.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS
Odour	SLIGHT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT APPLICABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	1.1 (Air = 1)
Specific gravity	NOT APPLICABLE
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT APPLICABLE
Upper explosion limit	NOT APPLICABLE
Lower explosion limit	NOT APPLICABLE
% Volatiles	100 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Carbon monoxide can react with iron, nickel and other metals to form highly toxic carbonyls. Corrosive when moist. Copper and copper alloys unsuitable for use with hydrogen sulphide.
Hazardous Decomposition Products	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization cannot occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Non irritant. Carbon monoxide effects depend on the percentage of carboxyhaemoglobin: 10-20% mild headache and breathlessness on mild exertion; 20-30% headache, irritability, rapid fatigue and impaired memory; 30-40% severe headache, weakness, nausea, vomiting, dizziness, visual impairment and confusion; 40-50% increasing confusion, ataxia and collapse; 50-60% coma; >80% rapid death. Chronic exposure to carbon monoxide may result in an increase in cardiovascular
------------------------------	--

Product Name**5 COMPONENT MIXTURE, (HYDROGEN SULPHIDE, CARBON MONOXIDE, METHANE AND OXYGEN IN NITROGEN) (2249)**

problems. Can aggravate some diseases of the cardiovascular system such as coronary artery disease. The effect is enhanced by cigarette smoking. Developmental defects on foetuses can occur without maternal symptoms. Hydrogen sulphide has an unpleasant odour above 0.12 ppm but odour is not an adequate warning due to paralysis of sense of smell.

Eye

Non irritant. Hydrogen sulphide can cause inflammation and irritation at concentrations below 10 ppm. Symptoms disappear when exposure ceases, but in severe cases damage may be permanent. Persons with potential exposure should not wear contact lenses.

Inhalation

Harmful. Over exposure to carbon monoxide may result in rapid breathing, nausea, lack of coordination, unconsciousness and coma. Reacts with blood haemoglobin to prevent oxygen uptake. Irritant. Over exposure to dust or fumes (if heated) may result in respiratory irritation, loss of appetite and nausea and at high levels dizziness, breathing difficulties and pulmonary oedema. Coal tar, Coal tar pitches and benzo[a]pyrene are classified as carcinogenic to humans (IARC Group 1).

Skin

Hydrogen sulphide may irritate the skin

Ingestion

Due to product form, ingestion is not considered a potential exposure route.

Toxicity data

METHANE (74-82-8)	
LC50 (inhalation)	326 gm/m3/2h (mouse)
CARBON MONOXIDE (630-08-0)	
LC50 (inhalation)	1807 ppm/4H (rat)
LCLo (inhalation)	5000 ppm/5M (human)
HYDROGEN SULPHIDE (7783-06-4)	
LC50 (inhalation)	444 ppm (rat)

12. ECOLOGICAL INFORMATION

Toxicity	No information provided.
Persistence and degradability	No information provided.
Bioaccumulative potential	No information provided.
Mobility in soil	No information provided.
Other adverse effects	When discharged into the atmosphere, Methane may contribute to the greenhouse effect. Methane has a global warming potential of 21 (CO ₂ = 1).

13. DISPOSAL CONSIDERATIONS

Waste disposal	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN number	1956	-	-
Proper shipping name	COMPRESSED GAS, N.O.S.	-	-
DG class/ Division	2.2	-	-
Subsidiary risk(s)	None Allocated	-	-
Packing group	None Allocated	-	-

Product Name **5 COMPONENT MIXTURE, (HYDROGEN SULPHIDE, CARBON MONOXIDE, METHANE AND OXYGEN IN NITROGEN) (2249)**

Report status This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Revision: 2
SDS Date: 01 February 2013

End of SDS