

## SAFETY DATA SHEET

# 2117

Product Name **16 COMPONENT MIXTURE (BALANCE N2)**

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier name** BOC LIMITED (AUSTRALIA)  
**Address** 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA  
**Telephone** 131 262, (02) 8874 4400  
**Fax** 132 427 (24 hours)  
**Emergency** 1800 653 572 (24/7) (Australia only)  
**Web site** <http://www.boc.com.au/>  
**Synonym(s)** 2117 - MSDS NUMBER • PRODUCT CODES: 285, 288 • SPECIAL GAS MIXTURE  
**Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS  
**SDS date** 01 February 2013

### 2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS (GHS) ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**RISK PHRASES**

None allocated

**SAFETY PHRASES**

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

**UN number** 1956 **DG division** 2.2  
**Packing group** None Allocated **Subsidiary risk(s)** None Allocated  
**Hazchem code** 2TE

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
PROPANE	CAS: 74-98-6 EC: 200-827-9	F+;R12	0.6%
ETHANE	CAS: 74-84-0 EC: 200-814-8	F+;R12	0.02%
METHANE	CAS: 74-82-8 EC: 200-812-7	F+;R12	0.015%
ETHYLENE	CAS: 74-85-1 EC: 200-815-3	F+;R12 Xn;R67	0.005%
1-BUTENE	CAS: 106-98-9 EC: 203-449-2	F+;R12	0.001%
ACETYLENE	CAS: 74-86-2 EC: 200-816-9	E;R5 E;R6 F+;R12	0.001%
BUTANE	CAS: 106-97-8 EC: 203-448-7	F+;R12	0.001%

**Product Name 16 COMPONENT MIXTURE (BALANCE N2)**

ISOBUTANE	CAS: 75-28-5 EC: 200-857-2	F+;R12	0.001%
ISOBUTENE	CAS: 115-11-7 EC: 204-066-3	F+;R12	0.001%
PROPYLENE	CAS: 115-07-1 EC: 204-062-1	F+;R12	0.001%
TRANS-2-BUTENE	CAS: 624-64-6 EC: 210-855-3	F+;R12	0.001%
CIS-2-BUTENE	CAS: 590-18-1 EC: 209-673-7	Not Available	0.001%
CYCLOPROPANE	CAS: 75-19-4 EC: 200-847-8	F+;R12	0.001%
METHYL ACETYLENE	CAS: 74-99-7 EC: 200-828-4	Not Available	0.001%
PROPADIENE	CAS: 463-49-0 EC: 207-335-3	Not Available	0.001%
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	Remainder

---

**4. FIRST AID MEASURES**

---

<b>Eye</b>	None required.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
<b>Skin</b>	None required.
<b>Ingestion</b>	Due to product form and application, ingestion is considered unlikely.
<b>Advice to doctor</b>	Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

<b>Flammability</b>	Non flammable.
<b>Fire and explosion</b>	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.
<b>Extinguishing</b>	Use water fog to cool containers from protected area.
<b>Hazchem code</b>	2TE 2 Water Fog (or fine water spray if fog unavailable) T Self Contained Breathing apparatus and protective gloves. E Evacuation of people in the vicinity of the incident should be considered.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

<b>Personal precautions</b>	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment as detailed in Section 8 of this SDS.
<b>Environmental precautions</b>	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
<b>Methods of cleaning up</b>	Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.
<b>References</b>	See Sections 8 and 13 for exposure controls and disposal.

---

**7. STORAGE AND HANDLING**

---

**Product Name 16 COMPONENT MIXTURE (BALANCE N2)**

**Storage** Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

**Handling** Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Acetylene	SWA (AUS)	Asphyxiant			
Butane	SWA (AUS)	800	1900	--	--
Ethane	SWA (AUS)	Asphyxiant			
Ethylene	SWA (AUS)	Asphyxiant			
Isobutane	SWA (AUS)	1000	--	--	--
Methane	SWA (AUS)	Asphyxiant			
Methyl acetylene	SWA (AUS)	1000	1640	--	--
Nitrogen	SWA (AUS)	Asphyxiant			
Propane	SWA (AUS)	Asphyxiant			
Propylene	SWA (AUS)	Asphyxiant			

**Biological limits** No biological limit allocated.

**Engineering controls** Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure standard.

**PPE**

**Eye / Face** Wear safety glasses.  
**Hands** Wear leather gloves.  
**Body** Wear safety boots.  
**Respiratory** Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**Appearance** COLOURLESS GAS  
**Odour** SLIGHT ODOUR  
**Flammability** NON FLAMMABLE  
**Flash point** NOT RELEVANT  
**Boiling point** NOT AVAILABLE  
**Melting point** NOT AVAILABLE  
**Evaporation rate** NOT APPLICABLE  
**pH** NOT APPLICABLE  
**Vapour density** NOT AVAILABLE  
**Specific gravity** NOT APPLICABLE  
**Solubility (water)** 0.0149 L/L (Nitrogen)  
**Vapour pressure** NOT AVAILABLE  
**Upper explosion limit** NOT RELEVANT  
**Lower explosion limit** NOT RELEVANT  
**Autoignition temperature** NOT AVAILABLE

**Product Name 16 COMPONENT MIXTURE (BALANCE N2)**

<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>% Volatiles</b>	100 %
<b>Cylinder pressure (when full)</b>	3000 kPa @ 15°C

---

**10. STABILITY AND REACTIVITY**

---

<b>Chemical stability</b>	Stable under recommended conditions of storage.
<b>Conditions to avoid</b>	Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources. Avoid heat, sparks, open flames and other ignition sources.
<b>Material to avoid</b>	Compatible with most commonly used materials.
<b>Hazardous Decomposition Products</b>	This material will not decompose to form hazardous products.
<b>Hazardous Reactions</b>	Polymerization will not occur.

---

**11. TOXICOLOGICAL INFORMATION**

---

<b>Health Hazard Summary</b>	Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes.																								
<b>Eye</b>	Non irritant.																								
<b>Inhalation</b>	Asphyxiant. Effects are proportional to oxygen displacement. Acts as a simple asphyxiant by displacing oxygen in the lungs thereby diminishing the supply of oxygen to the blood and tissues.																								
<b>Skin</b>	Non irritant.																								
<b>Ingestion</b>	Ingestion is considered unlikely due to product form.																								
<b>Toxicity data</b>	<table><tr><td>PROPANE (74-98-6)</td><td></td></tr><tr><td>    LC50 (inhalation)</td><td>&gt; 800000 ppm/15M (rat)</td></tr><tr><td>METHANE (74-82-8)</td><td></td></tr><tr><td>    LC50 (inhalation)</td><td>326 gm/m3/2h (mouse)</td></tr><tr><td>ACETYLENE (74-86-2)</td><td></td></tr><tr><td>    LCLo (inhalation)</td><td>50pph/5M (human)</td></tr><tr><td>    TCLo (inhalation)</td><td>20 pph (human)</td></tr><tr><td>BUTANE (106-97-8)</td><td></td></tr><tr><td>    LC50 (inhalation)</td><td>658000 mg/m3/4H (rat)</td></tr><tr><td>CYCLOPROPANE (75-19-4)</td><td></td></tr><tr><td>    LCLo (inhalation)</td><td>282 g/m3/2 hours (mouse)</td></tr><tr><td>    TCLo (inhalation)</td><td>4 pph (human)</td></tr></table>	PROPANE (74-98-6)		LC50 (inhalation)	> 800000 ppm/15M (rat)	METHANE (74-82-8)		LC50 (inhalation)	326 gm/m3/2h (mouse)	ACETYLENE (74-86-2)		LCLo (inhalation)	50pph/5M (human)	TCLo (inhalation)	20 pph (human)	BUTANE (106-97-8)		LC50 (inhalation)	658000 mg/m3/4H (rat)	CYCLOPROPANE (75-19-4)		LCLo (inhalation)	282 g/m3/2 hours (mouse)	TCLo (inhalation)	4 pph (human)
PROPANE (74-98-6)																									
LC50 (inhalation)	> 800000 ppm/15M (rat)																								
METHANE (74-82-8)																									
LC50 (inhalation)	326 gm/m3/2h (mouse)																								
ACETYLENE (74-86-2)																									
LCLo (inhalation)	50pph/5M (human)																								
TCLo (inhalation)	20 pph (human)																								
BUTANE (106-97-8)																									
LC50 (inhalation)	658000 mg/m3/4H (rat)																								
CYCLOPROPANE (75-19-4)																									
LCLo (inhalation)	282 g/m3/2 hours (mouse)																								
TCLo (inhalation)	4 pph (human)																								

---

**12. ECOLOGICAL INFORMATION**

---

<b>Toxicity</b>	No information provided.
<b>Persistence and degradability</b>	No information provided.
<b>Bioaccumulative potential</b>	No information provided.
<b>Mobility in soil</b>	No information provided.
<b>Other adverse effects</b>	Product is not harmful to the environment.

### 13. DISPOSAL CONSIDERATIONS

<b>Waste disposal</b>	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>UN number</b>	1956	-	-
<b>Proper shipping name</b>	COMPRESSED GAS, N.O.S.	-	-
<b>DG class/ Division</b>	2.2	-	-
<b>Subsidiary risk(s)</b>	None Allocated	-	-
<b>Packing group</b>	None Allocated	-	-
<b>GTEPG</b>	2C1		
<b>Hazchem code</b>	2TE		
<b>Other information</b>	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.		

### 15. REGULATORY INFORMATION

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)
<b>Inventory Listing(s)</b>	<b>AUSTRALIA: AICS (Australian Inventory of Chemical Substances)</b> All components are listed on AICS, or are exempt.

### 16. OTHER INFORMATION

**Additional information** The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

**APPLICATION METHOD:** Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Product Name**      **16 COMPONENT MIXTURE (BALANCE N2)**

<b>Abbreviations</b>	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	PEL	Permissible Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	TLV	Threshold Limit Value
	TWA/OEL	Time Weighted Average or Occupational Exposure Limit

**Revision history**

Revision	Description
2.0	Standard SDS Review.
1.0	Initial SDS creation

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: info@rmt.com.au  
Web: www.rmt.com.au

**Revision:** 2  
**SDS Date:** 01 February 2013

**End of SDS**