

FLEX TILE LTD
Material Safety Data Sheet
FLEXTECH 310 CLEAR SET FLOORING ADHESIVE

MANUFACTURER:
ONTARIO
121-30th Street,
Etobicoke, ON.
M8W 3C1
Tel: (416) 255-1111
FAX: (416) 255-1729
IN CASE OF EMERGENCY.

FLEX TILE LTD.
QUEBEC
555, Rue locke
Ville St. Laurent, QC
H4T 1X7
Tel: (514) 345-6666
FAX: (514) 345-8825
CALL CANUTEC (613) 996-6666

BRITISH COLUMBIA
2829 Lake City Way
Burnaby, BC
V5A 2Z6
Tel: (644) 420-4914
FAX: (604) 420-0936

Material Identification

PRODUCT IDENTIFIER..... FLEXTECH 310 CLEAR SET FLOORING ADHESIVE
WHMIS CLASSIFICATION..... NOT REGULATED UNDER WHMIS

Hazardous Ingredients of Materials

CHEMICAL IDENTITY CONCENTRATION CAS#/NA#/UN# OSHA (PEL) ACGIH (TLV-TWA)
THIS PRODUCT CONTAINS NO HAZARDOUS INGREDIENT AS DEFINED BY US OSHA HAZARD COMMUNICATION STANDARD - 29 CFR 1910.1200 OR SECTION 13 OF THE CANADIAN HAZARDOUS PRODUCT ACT.
All ingredients are listed within or exempted from US TSCA and Canadian DSL.

Physical Data For Product

PHYSICAL STATE.....	VISCOUS LIQUID		
ODOUR AND APPEARANCE.....	MILD ODOUR, BEIGE-COLOURED PASTE		
ODOUR THRESHOLD.....	NOT DETERMINED		
SPECIFIC GRAVITY.....	1.1		
VAPOUR PRESSURE.....	N/D	VAPOUR DENSITY (air=1).....	N/D
EVAPORATION RATE(Butyl Acetate=1)...Same as water		BOILING POINT.....	212°F (100°C)
FREEZING POINT.....	N/D	pH.....	9-10
CALCULATED VOC CONTENT	0 gm/litre		

Fire and Explosion Hazard of Product

CONDITIONS OF FLAMMABILITY.....	NON-COMBUSTIBLE		
MEANS OF EXTINCTION.....	Will not burn except under extreme temperature. Water spray, CO ₂ , dry chemical or foam		
FLASHPOINT.....	>212°F (100°C)		
UPPER EXPLOSION LIMIT (% BY VOL)..	N/D		
LOWER EXPLOSION LIMIT (% BY VOL)..	N/D		
AUTO-IGNITION TEMPERATURE.....	N/D		
HAZARDOUS COMBUSTION PRODUCTS....	CO ₂ , CO, FUMES		
EXPLOSION DATA.....	N/D		
SENSITIVITY TO STATIC DISCHARGE...	N/D		
SPECIAL FIRE FIGHTING PROCEDURES....	Wear standard fire fighting gear with self-contained breathing apparatus.		

Reactivity Data

CHEMICAL STABILITY.....	STABLE
INCOMPATIBLE MATERIALS.....	STRONG ACIDS, STRONG BASES & STRONG OXIDISING AGENTS.
CONDITIONS TO AVOID.....	NONE KNOWN.
HAZARDOUS DECOMPOSITION PRODUCTS..	BURNING MAY PRODUCE CO AND/OR CO ₂ .
HAZARDOUS POLYMERIZATION.....	WILL NOT OCCUR.

FLEXTECH 310 CLEAR SET FLOORING ADHESIVE

Toxicological Properties of Product

ROUTES OF ENTRY	
SKIN CONTACT.....	MAY CAUSE IRRITATION ON PROLONGED CONTACT
SKIN ABSORPTION.....	NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION.
EYE.....	MAY CAUSE IRRITATION
INHALATION.....	MAY CAUSE HEADACHE, NAUSEA, VOMITING AND IRRITATION OF THE RESPIRATORY TRACT.
INGESTION.....	MAY CAUSE ABDOMINAL DISCOMFORT OR PAIN, NAUSEA AND VOMITING. MAY BE FATAL IF LARGE VOLUMES ARE SWALLOWED. REFER TO ROUTE OF ENTRY.
EFFECTS OF ACUTE EXPOSURE ...	
EFFECTS OF CHRONIC EXPOSURE..	REPEATED CONTACT WITH SKIN MAY CAUSE DERMATITIS IN SENSITIVE INDIVIDUALS. PROLONGED INHALATION MAY PRODUCE SIGN OF CENTRAL NERVOUS SYSTEM INVOLVEMENT, PARTICULARLY DIZZINESS AND NYSTAGMUS.
IRRITANCY OF PRODUCT.....	N/D
CARCINOGENICITY, REPRODUCTIVE EFFECTS:	SENSITIZATION TO MATERIAL..... N/D
TERATOGENICITY, MUTAGENICITY.....	MINIMAL EVIDENCE OF TERATOGENICITY.
TOXICOLOGICALLY SYNERGISTIC PRODUCTS.....	N/D

Preventive Measures

PERSONAL PROTECTIVE EQUIPMENT:-

GLOVES/ TYPE.....	PVC, NEOPRENE OR RUBBER.
RESPIRATORY/TYPE..	NIOSH OR MSHA APPROVED BREATHING AIR EQUIPMENT.
EYE/TYPE.....	FACE SHIELD.
ENGINEERING CONTROLS...	GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT FOR MOST CONDITIONS.
LEAK AND SPILL.....	ABSORB WITH PAPER, SAND OR SAWDUST.
WASTE DISPOSAL.....	IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL & FEDERAL REGULATIONS
HANDLING PROCEDURES....	AVOID EYE CONTACT, REPEATED OR PROLONGED SKIN AND EQUIPMENT CONTACT AND INHALING VAPOURS.
STORAGE REQUIREMENTS...	STORE AT 60-95°F (15-35°C) AND OUT OF THE SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOURS WHEN COVER IS REMOVED.
SPECIAL SHIPPING INFORMATION.....	NOT REGULATED

First Aid Measures

FIRST AID PROCEDURES...

IMMEDIATELY FLUSH EYES WITH ABUNDANT WATER FOR AT LEAST 15 MINUTES, FORCIBLY HOLDING EYELIDS APART. SEEK MEDICAL ATTENTION. IN CASE OF INHALATION, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF SKIN CONTACT, REMOVE ANY CONTAMINATED CLOTHING AND WASH AFFECTED AREA WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN CASE OF INGESTION, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

Preparation Date of Material Safety Data Sheet

PREPARED BY.....	CHIEF CHEMIST
PHONE NUMBER OF PREPARER.....	416 - 255-1111 FAX: 416 -255-1729
DATE PREPARED.....	3 Feb., 2014

Flextile Ltd. assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Flextile Ltd., assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

FLEX TILE LTD.

N/D = NOT DETERMINED