

SAFETY DATA SHEET

2259

Product Name **5 COMPONENT MIXTURE (CO, CO₂, O₂, SO₂, BALANCE NITROGEN)**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)
Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA
Telephone 131 262, (02) 8874 4400
Fax 132 427 (24 hours)
Emergency 1800 653 572 (24/7) (Australia only)
Web site <http://www.boc.com.au/>
Synonym(s) 2259 - MSDS NUMBER • PRODUCT CODE: 292-980
Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS
SDS date 01 February 2013

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS (GHS) ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN number 1956 **DG division** 2.2
Packing group None Allocated **Subsidiary risk(s)** None Allocated
Hazchem code 2TE

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
OXYGEN	CAS: 7782-44-7 EC: 231-956-9	O;R8	5%
SULPHUR DIOXIDE	CAS: 7446-09-5 EC: 231-195-2	T;R23 C;R34	0.15%
CARBON MONOXIDE	CAS: 630-08-0 EC: 211-128-3	T;R23 Repr.;R61 T;R48/23 F+;R12	0.1%
CARBON DIOXIDE	CAS: 124-38-9 EC: 204-696-9	Not Available	12%
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	Remainder

4. FIRST AID MEASURES

Eye Cold burns: Immediately flush with tepid water or with sterile saline solution. Hold eyelids apart and irrigate for 15 minutes. Seek medical attention.

Product Name 5 COMPONENT MIXTURE (CO, CO2, O2, SO2, BALANCE NITROGEN)

Inhalation	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
Skin	Cold burns: Remove contaminated clothing and gently flush affected areas with warm water (30°C) for 15 minutes. Apply sterile dressing and treat as for a thermal burn. For large burns, immerse in warm water for 15 minutes. DO NOT apply any form of direct heat. Seek immediate medical attention.
Ingestion	Due to product form and application, ingestion is considered unlikely.
Advice to doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability	Non flammable.
Fire and explosion	Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.
Extinguishing	Use water fog to cool containers from protected area.
Hazchem code	2TE 2 Water Fog (or fine water spray if fog unavailable) T Self Contained Breathing apparatus and protective gloves. E Evacuation of people in the vicinity of the incident should be considered.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment as detailed in Section 8 of this SDS.
Environmental precautions	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Methods of cleaning up	Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.
References	See Sections 8 and 13 for exposure controls and disposal.

7. STORAGE AND HANDLING

Storage	Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
Handling	Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement. The uncontrolled release of a gas under pressure may cause physical harm. When handling gas cylinders, the use of appropriate mechanical handling devices is recommended.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Carbon monoxide	SWA (AUS)	30	34	--	--
Nitrogen	SWA (AUS)	Asphyxiant			
Sulphur dioxide	SWA (AUS)	2	5.2	5	13

Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end-exhaled air	End of shift	20 ppm

Engineering controls In poorly ventilated areas, mechanical extraction ventilation is recommended.

PPE

- Eye / Face** Wear safety glasses.
- Hands** Wear leather gloves.
- Body** Wear safety boots.
- Respiratory** Where an inhalation risk exists, wear an Air-line respirator or a Full-face Type B (Inorganic and Acid gas) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURLESS GAS
Odour	SLIGHT PUNGENT SULPHUR DIOXIDE ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT APPLICABLE
Boiling point	NOT APPLICABLE
Melting point	NOT APPLICABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	1.08 (Air = 1)
Specific gravity	NOT APPLICABLE
Solubility (water)	NOT AVAILABLE
Vapour pressure	NOT APPLICABLE
Upper explosion limit	NOT APPLICABLE
Lower explosion limit	NOT APPLICABLE
Autoignition temperature	NOT APPLICABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
% Volatiles	100 %

10. STABILITY AND REACTIVITY

Chemical stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.
Material to avoid	Moist carbon dioxide and sulphur dioxide are corrosive, hence acid resistant materials are required (stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide, ie. embrittlement, leaching of plasticisers, etc. Incompatible with acrylaldehyde, aziridine, metal acetylides, sodium peroxide.
Hazardous Decomposition Products	May evolve toxic gases if heated to decomposition.
Hazardous Reactions	Polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Asphyxiant gas - irritant. The sulphur dioxide level has the potential to cause adverse health effects

Product Name 5 COMPONENT MIXTURE (CO, CO2, O2, SO2, BALANCE NITROGEN)

Summary	with prolonged exposure. Chronic exposure to sulphur dioxide levels above 1 ppm can lead to a decline in respiratory function. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes. Sulphur dioxide at 5 ppm causes dryness to the mouth & throat and slight breathing difficulties. Exposure at 50 ppm causes strong eye, nose, throat and respiratory tract irritation as well as changes in breathing volume.
Eye	Irritant. Contact may result in irritation, lacrimation, pain and redness. Contact with liquid or vapour may result in corneal burns and frost-bite.
Inhalation	Irritant - asphyxiant. Over exposure may result in irritation of the nose and throat, coughing, loss of taste and smell, headache, nausea, vomiting, drowsiness, weakness, lack of coordination, and asphyxiation and pulmonary oedema at very high levels. Individuals with pre-existing respiratory problems (eg. asthma) should avoid exposure.
Skin	Irritant. Direct contact with the liquefied material or escaping compressed gas may cause frost-bite injury.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity data	SULPHUR DIOXIDE (7446-09-5) LC50 (inhalation) 2520 ppm/1 hour (rat) LCLo (inhalation) 1000 ppm/10 minutes (human) TCLo (inhalation) 3 ppm/5 days (human) CARBON MONOXIDE (630-08-0) LC50 (inhalation) 1807 ppm/4H (rat) LCLo (inhalation) 5000 ppm/5M (human) CARBON DIOXIDE (124-38-9) LC50 (inhalation) 470000 ppm/30M (rat) LCLo (inhalation) 9 pph/5M (human)

12. ECOLOGICAL INFORMATION

Toxicity	No information provided.
Persistence and degradability	No information provided.
Bioaccumulative potential	No information provided.
Mobility in soil	No information provided.
Other adverse effects	No information provided.

13. DISPOSAL CONSIDERATIONS

Waste disposal	Return cylinder and contents to manufacturer or supplier for recycling. Contact the manufacturer for additional information.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



Product Name 5 COMPONENT MIXTURE (CO, CO2, O2, SO2, BALANCE NITROGEN)

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN number	1956	-	-
Proper shipping name	COMPRESSED GAS, N.O.S.	-	-
DG class/ Division	2.2	-	-
Subsidiary risk(s)	None Allocated	-	-
Packing group	None Allocated	-	-
GTEPG	2C1		
Hazchem code	2TE		
Other information	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.		

15. REGULATORY INFORMATION

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)
Inventory Listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information	The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.
-------------------------------	--

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m ³	Milligrams per Cubic Metre
	PEL	Permissible Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	TLV	Threshold Limit Value
	TWA/OEL	Time Weighted Average or Occupational Exposure Limit

Product Name **5 COMPONENT MIXTURE (CO, CO2, O2, SO2, BALANCE NITROGEN)**

Revision history

Revision	Description
2.0	Standard SDS Review.
1.0	Initial SDS creation

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Revision: 2
SDS Date: 01 February 2013

End of SDS