

# **SAFETY DATA SHEET**

# 2376

Product Name SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name BOC LIMITED (AUSTRALIA)

Address 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA

**Telephone** 131 262, (02) 8874 4400 **Fax** 132 427 (24 hours)

**Emergency** 1800 653 572 (24/7) (Australia only)

http://www.boc.com.au

Synonym(s) 2376 - SDS NUMBER • PRODUCT CODES: 2921133G • SPECIAL GAS MIXTURE

Use(s) CALIBRATION • INDUSTRIAL APPLICATIONS

SDS date 13 November 2014

## 2. HAZARDS IDENTIFICATION

## CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

**Risk Phrases** 

R12 Extremely Flammable.

**Safety Phrases** 

S9 Keep container in a well ventilated place.

Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

#### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number1954Transport Hazard Class2.1Packing GroupNone AllocatedHazchem Code2SE

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	EC Number	Content (v/v)
METHYL MERCAPTAN	74-93-1	200-822-1	0.0016%
HYDROGEN SULPHIDE	7783-06-4	231-977-3	0.0007%
CARBONYL SULPHIDE	463-58-1	207-340-0	0.0002%
PROPANE	74-98-6	200-827-9	Remainder
NITROGEN	7727-37-9	231-783-9	20%

## 4. FIRST AID MEASURES

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self

Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.

**Skin** None required.

**Ingestion** Due to product form and application, ingestion is considered unlikely.

ChemAlert.

Page 1 of 6

SDS Date: 13 Nov 2014

#### **Product Name** SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

Advice to doctor Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing **Flammability** 

switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.

Fire and explosion Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be

activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming

explosive mixtures with air.

Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve. If the gas source **Extinguishing** 

cannot be isolated, do not extinguish the flame, since re-ignition and explosion could occur. Await arrival of emergency services or manufacturer's advisor. Drench and cool cylinders with water spray from protected area at a safe distance. If it is absolutely necessary to extinguish the flame, use only a dry chemical powder extinguisher. Do not move cylinders for at least 24 hours. Avoid shock and

bumps to cylinders.

2SE Hazchem code

> 2 Water Fog (or fine water spray if fog unavailable)

S Self Contained Breathing apparatus and protective gloves.

Е Evacuation of people in the vicinity of the incident should be considered.

## 6. ACCIDENTAL RELEASE MEASURES

**Spillage** If the cylinder is leaking, eliminate all potential ignition sources and evacuate area of personnel. Prevent spreading of vapours through drains and ventilation systems. Inform manufacturer/supplier

then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

# 7. STORAGE AND HANDLING

Do not store near sources of ignition or incompatible materials. Cylinders should be stored below Storage

45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor

of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area,

(preferably concrete), away from areas of heavy traffic and emergency exits.

Handling Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll

cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a

suitable hand truck for cylinder movement.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure standards**

Ingredient	Reference	TWA		STEL	
mgredient		ppm	mg/m³	ppm	mg/m³
Hydrogen sulfide	SWA (AUS)	10	14	15	21
Methyl mercaptan	SWA (AUS)	0.5	0.98		
Nitrogen	SWA (AUS)		Asph	yxiant	
Propane	SWA (AUS)		Asph	yxiant	

**Biological limits** No biological limit allocated.

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (e.g. tanks) should be **Engineering controls** 

adequately ventilated or gas tested. Maintain vapour levels below the recommended exposure

standard.



Page 2 of 6 SDS Date: 13 Nov 2014

#### Product Name SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

**PPE** 

Eye / FaceWear safety glasses.HandsWear leather gloves.BodyWear safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line

respirator.







## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance COLOURLESS GAS** Odour ROTTEN EGG ODOUR **Flammability** HIGHLY FLAMMABLE Flash point **NOT AVAILABLE Boiling** point NOT AVAILABLE **Melting** point NOT AVAILABLE **Evaporation rate** NOT APPLICABLE Ηq **NOT APPLICABLE** Vapour density 1.523 (Methane) (Air = 1) Specific gravity **NOT APPLICABLE** Solubility (water) **INSOLUBLE** Vapour pressure NOT AVAILABLE **Upper explosion limit** 9.5 % (Propane) Lower explosion limit 2.1 % (Propane) **Explosive properties** NOT AVAILABLE **Oxidising properties** NOT AVAILABLE

% Volatiles 100 %

## 10. STABILITY AND REACTIVITY

Chemical stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Material to avoid Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), heat and ignition

sources. Do not use natural rubber flexible hoses. Also incompatible (potentially violently) with

oxygen, halogens and metal halides.

**Hazardous Decomposition** 

**Products** 

This material will not decompose to form hazardous products other than that already present.

Hazardous Reactions Polymerization will not occur.

# 11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Asphyxiant gas. Symptoms of exposure are directly related to displacement of oxygen. As the amount of oxygen inhaled is reduced from 21-14% volume, the pulse rate may accelerate and the rate and volume of breathing may increase. The ability to maintain attention and think clearly is diminished, muscular co-ordination is somewhat disturbed. As oxygen decreases from 14-10% volume, judgement becomes faulty, severe injuries may result in no pain. Muscular effort may lead to rapid fatigue. Further reduction to 6% may result in nausea and vomiting. Ability to move may be lost. Permanent brain damage may result even after resuscitation from exposure to this low level of oxygen. Below 6% breathing is in gasps and convulsions may occur. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes.

Eye Non irritant

**Inhalation** Asphyxiant. Effects are proportional to oxygen displacement.

**Skin** Non irritant.

**Ingestion** Ingestion is considered unlikely due to product form.

ChemAlert.

Page 3 of 6 SDS Date: 13 Nov 2014

#### Product Name SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

Toxicity data METHYL MERCAPTAN (74-93-1)

LC50 (inhalation) 675 ppm (rat)

TCLo (inhalation) 17 ppm/7 hours/13 weeks intermittently (rat)

HYDROGEN SULPHIDE (7783-06-4)

LC50 (inhalation) 444 ppm (rat)

CARBONYL SULPHIDE (463-58-1)

LC50 (inhalation) 1070 ppm/4 hours (rat)

LD50 (intraperitoneal) 23 mg/kg (rat)

TCLo (inhalation) 162 ppm/6 hours/14 weeks intermittently (rat)

PROPANE (74-98-6)

LC50 (inhalation) > 800000 ppm/15M (rat)

# 12. ECOLOGICAL INFORMATION

**Toxicity** No information provided.

Persistence and degradability No information provided.

Bioaccumulative potential No information provided.

Mobility in soil No information provided.

## 13. DISPOSAL CONSIDERATIONS

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation** Dispose of in accordance with relevant local legislation.

# 14. TRANSPORT INFORMATION

# CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1954	-	-
Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S. (Contains Methane)	-	-
Transport Hazard Class	2.1	-	-
Packing Group	None Allocated	-	-

Environmental hazards No information provided

Special precautions for user

Hazchem code 2SE GTEPG 2A1

**Other information** Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.

# 15. REGULATORY INFORMATION



SDS Date: 13 Nov 2014

Page 4 of 6

#### **Product Name** SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

Poison schedule

A poison schedule number has not been allocated to this product using the criteria in the Standard

for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Inventory Listing(s)

**AUSTRALIA: AICS (Australian Inventory of Chemical Substances)** All components are listed on AICS, or are exempt.

# 16. OTHER INFORMATION

#### Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

#### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

#### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

#### **Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS#	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System

**IARC** International Agency for Research on Cancer LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m<sup>3</sup> Milligrams per Cubic Metre

**OEL** Occupational Exposure Limit **PEL** Permissible Exposure Limit

relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly pН alkaline).

Parts Per Million ppm

**REACH** Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals

Short-Term Exposure Limit STFL

STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure)

**SUSMP** Standard for the Uniform Scheduling of Medicines and Poisons

**SWA** Safe Work Australia TLV Threshold Limit Value TWA Time Weighted Average

# **Revision history**

Revision	Description
2.0	Included Risk Phrase.
1.0	Initial SDS creation



Page 5 of 6

13 Nov 2014 SDS Date:

#### Product Name SPECTRA SEAL 6 COMPONENT MIXTURE BALANCE PROPANE

#### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

## Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au

Web: www.rmt.com.au.

Revision: 2

SDS Date: 13 November 2014

**End of SDS** 



Page 6 of 6

SDS Date: 13 Nov 2014