

## SAFETY DATA SHEET

# 2400

Product Name **LESS THAN 0.25% CARBON DIOXIDE BALANCE NITROGEN**

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name** BOC LIMITED (AUSTRALIA)  
**Address** 10 Julius Avenue, North Ryde, NSW, AUSTRALIA, 2113  
**Telephone** 131 262, (02) 8874 4400  
**Fax** 132 427 (24 hours)  
**Emergency** 1800 653 572 (24/7) (Australia only)  
**Web Site** <http://www.boc.com.au/>  
**Synonym(s)** 2400 - SDS NUMBER • 285 - 288 - 292 - SPECIAL GAS MIXTURE  
**Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS  
**SDS Date** 27 Oct 2011

### 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

**UN No.** 1956                      **DG Class** 2.2                      **Subsidiary Risk(s)** None Allocated  
**Packing Group** None Allocated                      **Hazchem Code** 2TE

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
CARBON DIOXIDE	C-O2	124-38-9	<0.25%
NITROGEN	N2	7727-37-9	remainder

### 4. FIRST AID MEASURES

**Eye** None required.  
**Inhalation** If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.  
**Skin** None required.  
**Ingestion** Due to product form and application, ingestion is considered unlikely.  
**Advice to Doctor** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**Flammability** Non flammable.  
**Fire and Explosion** Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot.  
**Extinguishing** Use water fog to cool containers from protected area.  
**Hazchem Code** 2TE

## 6. ACCIDENTAL RELEASE MEASURES

**Spillage** If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use personal protective equipment. Carefully move material to a well ventilated remote area, then allow to discharge. Do not attempt to repair leaking valve or cylinder safety devices.

## 7. STORAGE AND HANDLING

**Storage** Do not store near incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

**Handling** Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

### Exposure Stds

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Carbon dioxide	SWA (AUS)	5000 ppm	9000 mg/m <sup>3</sup>	30000 ppm	54000 mg/m <sup>3</sup>
Carbon dioxide in coal mines	SWA (AUS)	12500 ppm	22500 mg/m <sup>3</sup>	30000 ppm	54000 mg/m <sup>3</sup>
Nitrogen	SWA (AUS)	Asphyxiant			

**Biological Limits** No biological limit allocated.

**Engineering Controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

**PPE** Wear safety boots, leather gloves and safety glasses. Where an inhalation risk exists, wear: self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	COLOURLESS GAS	<b>Solubility (water)</b>	NOT AVAILABLE
<b>Odour</b>	ODOURLESS	<b>Specific Gravity</b>	0.97
<b>pH</b>	NOT APPLICABLE	<b>% Volatiles</b>	NOT AVAILABLE
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	NON FLAMMABLE
<b>Vapour Density</b>	NOT AVAILABLE	<b>Flash Point</b>	NOT RELEVANT
<b>Boiling Point</b>	NOT AVAILABLE	<b>Upper Explosion Limit</b>	NOT RELEVANT
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	NOT RELEVANT
<b>Evaporation Rate</b>	NOT APPLICABLE		
<b>Autoignition Temperature</b>	NOT AVAILABLE	<b>Decomposition Temperature</b>	NOT AVAILABLE
<b>Partition Coefficient</b>	NOT AVAILABLE	<b>Viscosity</b>	NOT AVAILABLE

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid contact with incompatible substances.

**Material to Avoid** Moist carbon dioxide is corrosive, hence acid resistant materials are required (stainless steel). Certain properties of some plastics and rubbers may be affected by carbon dioxide, ie. embrittlement, leaching of plasticisers, etc.

**Hazardous Decomposition Products** May evolve toxic gases if heated to decomposition.

**Product Name**      **LESS THAN 0.25% CARBON DIOXIDE BALANCE NITROGEN**

**Hazardous Reactions**      Polymerization will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

**Health Hazard Summary**      Asphyxiant gas - non irritant. When released into air the concentration of carbon dioxide is diluted. Carbon dioxide concentrations of 3-5 % in air cause increased respiration and headache. Concentrations of 8-15% cause headache, nausea and vomiting which may lead to unconsciousness if not moved to open air and given oxygen. Inhalation of a mixture containing no oxygen may result in unconsciousness from the first breath and death may follow in minutes. Adverse health affects to long term exposure to carbon dioxide have not been reported. However, in environments such as submarines where exposure to levels of 0.5-1.0% may occur, specialist medical opinion should be sought on the effects of long term exposure.

**Eye**      Non irritant.

**Inhalation**      Non irritant - Asphyxiant. Effects are proportional to oxygen displacement.

**Skin**      Non irritant.

**Ingestion**      Ingestion is considered unlikely due to product form.

**Toxicity Data**      CARBON DIOXIDE (124-38-9)  
LC50 (Inhalation): 470000 ppm/30M (rat)  
LCLo (Inhalation): 9 pph/5M (human)

---

## 12. ECOLOGICAL INFORMATION

---

**Environment**      When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Waste Disposal**      Cylinders should be returned to the manufacturer or supplier for disposal of contents.

**Legislation**      Dispose of in accordance with relevant local legislation.

---

## 14. TRANSPORT INFORMATION

---

**Transport**      Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.



### CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

<b>Shipping Name</b>	COMPRESSED GAS, N.O.S.			<b>Subsidiary Risk(s)</b>	None Allocated
<b>UN No.</b>	1956	<b>DG Class</b>	2.2	<b>GTEPG</b>	2C1
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	2TE		

---

## 15. REGULATORY INFORMATION

---

**Poison Schedule**      A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

**AICS**      All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

---

## 16. OTHER INFORMATION

---

**Additional Information**      The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

**Product Name**      **LESS THAN 0.25% CARBON DIOXIDE BALANCE NITROGEN**

HSNO - Hazardous Substances and New Organisms.  
IARC - International Agency for Research on Cancer.  
mg/m<sup>3</sup> - Milligrams per Cubic Metre.  
NOS - Not Otherwise Specified.  
pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).  
ppm - Parts Per Million.  
RTECS - Registry of Toxic Effects of Chemical Substances.  
STEL - Short Term Exposure Limit.  
SWA - Safe Work Australia.  
TWA - Time Weighted Average.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this ChemAlert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared By**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: info@rmt.com.au  
Web: www.rmt.com.au

**SDS Date** 27 Oct 2011

**End of Report**