

## SAFETY DATA SHEET

# 2713

Product Name **14 COMPONENT MIXTURE (BALANCE ARGON) (# 2713)**

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier name** BOC LIMITED (AUSTRALIA)  
**Address** 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA  
**Telephone** 131 262, (02) 8874 4400  
**Fax** 132 427 (24 hours)  
**Emergency** 1800 653 572 (24/7) (Australia only)  
**Web site** <http://www.boc.com.au/>  
**Synonym(s)** 2713 - SDS NUMBER • SPECIAL GAS MIXTURE  
**Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS  
**SDS date** 18 February 2014

### 2. HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA**

#### RISK PHRASES

R12 Extremely Flammable.  
R23 Toxic by inhalation.  
R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.  
R61 May cause harm to the unborn child.

#### SAFETY PHRASES

S16 Keep away from sources of ignition - No smoking.  
S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).  
S53 Avoid exposure - obtain special instructions before use.

**CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

<b>UN number</b>	1954	<b>DG division</b>	2.1
<b>Packing group</b>	None Allocated	<b>Subsidiary risk(s)</b>	None Allocated
<b>Hazchem code</b>	2SE		

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
CARBON MONOXIDE	CAS: 630-08-0 EC: 211-128-3	F+;R12 T;R23 T;R48/23 Repr.;R61	10 to 30%
HYDROGEN	CAS: 1333-74-0 EC: 215-605-7	F+;R12	10 to 30%
METHANE	CAS: 74-82-8 EC: 200-812-7	F+;R12	10 to 30%
BUTANE	CAS: 106-97-8 EC: 203-448-7	F+;R12	<5%
ETHANE	CAS: 74-84-0 EC: 200-814-8	F+;R12	<5%

**Product Name 14 COMPONENT MIXTURE (BALANCE ARGON) (# 2713)**

ETHYLENE	CAS: 74-85-1 EC: 200-815-3	F+;R12 Xn;R67	<5%
ISOBUTANE	CAS: 75-28-5 EC: 200-857-2	F+;R12	<5%
OXYGEN	CAS: 7782-44-7 EC: 231-956-9	O;R8	<5%
PENTANE	CAS: 109-66-0 EC: 203-692-4	F+;R12 N;R51/53 Xn;R65 Xi;R66 Xn;R67	<5%
PROPANE	CAS: 74-98-6 EC: 200-827-9	F+;R12	<5%
PROPYLENE	CAS: 115-07-1 EC: 204-062-1	F+;R12	<5%
CARBON DIOXIDE	CAS: 124-38-9 EC: 204-696-9	Not Available	10 to 30%
NITROGEN	CAS: 7727-37-9 EC: 231-783-9	Not Available	<5%
ARGON	CAS: 7440-37-1 EC: 231-147-0	Not Available	Remainder

---

**4. FIRST AID MEASURES**

---

<b>Eye</b>	None required.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing Apparatus (SCBA). Be aware of possible explosive atmospheres. Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
<b>Skin</b>	None required.
<b>Ingestion</b>	Due to product form and application, ingestion is considered unlikely.
<b>Advice to doctor</b>	Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

<b>Flammability</b>	Highly flammable. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones etc. when handling.
<b>Fire and explosion</b>	Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. This material is capable of forming explosive mixtures in air.
<b>Extinguishing</b>	Stop flow of gas if safe to do so, such as by slowly closing the cylinder valve.
<b>Hazchem code</b>	2SE 2 Water Fog (or fine water spray if fog unavailable) S Self Contained Breathing apparatus and protective gloves. E Evacuation of people in the vicinity of the incident should be considered.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

<b>Personal precautions</b>	If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Eliminate ignition sources. Consider the risk of potentially explosive atmospheres.
<b>Environmental precautions</b>	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
<b>Methods of cleaning up</b>	Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.
<b>References</b>	See Sections 8 and 13 for exposure controls and disposal.

## 7. STORAGE AND HANDLING

<b>Storage</b>	Do not store near sources of ignition or incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.
<b>Handling</b>	Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Argon	SWA (AUS)	Asphyxiant			
Butane	SWA (AUS)	800	1900	--	--
Carbon dioxide	SWA (AUS)	5000	9000	30000	54000
Carbon dioxide in coal mines	SWA (AUS)	12500	22500	30000	54000
Carbon monoxide	SWA (AUS)	30	34	--	--
Ethane	SWA (AUS)	Asphyxiant			
Ethylene	SWA (AUS)	Asphyxiant			
Hydrogen	SWA (AUS)	Asphyxiant			
Isobutane	SWA (AUS)	1000	--	--	--
Methane	SWA (AUS)	Asphyxiant			
Nitrogen	SWA (AUS)	Asphyxiant			
Pentane	SWA (AUS)	600	1770	750	2210
Propane	SWA (AUS)	Asphyxiant			
Propylene	SWA (AUS)	Asphyxiant			

### Biological limits

Ingredient	Reference	Determinant	Sampling Time	BEI
CARBON MONOXIDE	ACGIH BEI	Carboxyhemoglobin in blood	End of shift	3.5% of hemoglobin
	ACGIH BEI	Carbon monoxide in end-exhaled air	End of shift	20 ppm

### Engineering controls

Provide suitable ventilation to minimise or eliminate exposure. Confined areas (eg. tanks) should be adequately ventilated or gas tested. Flammable/explosive vapours may accumulate in poorly ventilated areas. Maintain vapour levels below the recommended exposure standard. Maintain vapour levels below the recommended exposure standard.

### PPE

<b>Eye / Face</b>	Wear safety glasses.
<b>Hands</b>	Wear leather gloves.
<b>Body</b>	Wear safety boots.
<b>Respiratory</b>	Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	COLOURLESS GAS
<b>Odour</b>	ODOURLESS

**Product Name      14 COMPONENT MIXTURE (BALANCE ARGON) (# 2713)**

Flammability	HIGHLY FLAMMABLE
Flash point	NOT AVAILABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT APPLICABLE
Solubility (water)	NOT AVAILABLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

---

**10. STABILITY AND REACTIVITY**

---

Chemical stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Carbon monoxide can react with iron, nickel and other metals. Below 3,500 kPa corrosion is negligible and common materials can be used. Incompatible with acrylaldehyde, aziridine, sodium peroxide. Corrosive when moist.
Hazardous Decomposition Products	This material will not decompose to form hazardous products other than that already present.
Hazardous Reactions	Polymerization will not occur.

---

**11. TOXICOLOGICAL INFORMATION**

---

Health Hazard Summary	Asphyxiant gas - toxic. Carbon monoxide effects depend on the percentage of carboxyhaemoglobin: 10-20% mild headache and breathlessness on mild exertion; 20-30% headache, irritability, rapid fatigue and impaired memory; 30-40% severe headache, weakness, nausea, vomiting, dizziness, visual impairment and confusion; 40-50% increasing confusion, ataxia and collapse; 50-60% coma; >80% rapid death. Chronic exposure to carbon monoxide may result in an increase in cardiovascular problems. Can aggravate some diseases of the cardiovascular system such as coronary artery disease. The effect is enhanced by cigarette smoking. Adverse behavioural effects have been noted including impairment of vigilance, co-ordination, timing, behaviour, visual perception and certain cognitive functions. Some adaptation occurs in individuals repeatedly exposed to moderate concentrations. Developmental defects on foetuses can occur without maternal symptoms.															
Eye	Non irritant.															
Inhalation	Toxic. Over exposure to carbon monoxide may result in rapid breathing, nausea, lack of coordination, unconsciousness and coma. Carbon monoxide reacts with haemoglobin in the blood to prevent oxygen uptake and release.															
Skin	Non irritant.															
Ingestion	Ingestion is considered unlikely due to product form.															
Toxicity data	<div>CARBON MONOXIDE (630-08-0)</div> <table><tr><td>LC50 (inhalation)</td><td>1807 ppm/4H (rat)</td></tr><tr><td>LCLo (inhalation)</td><td>5000 ppm/5M (human)</td></tr></table> <div>METHANE (74-82-8)</div> <table><tr><td>LC50 (inhalation)</td><td>326 gm/m3/2h (mouse)</td></tr></table> <div>BUTANE (106-97-8)</div> <table><tr><td>LC50 (inhalation)</td><td>658000 mg/m3/4H (rat)</td></tr></table> <div>PENTANE (109-66-0)</div> <table><tr><td>LC50 (inhalation)</td><td>364 g/m³/4 hours (rat)</td></tr><tr><td>LCLo (inhalation)</td><td>325 g/m³/2 hours (mouse)</td></tr><tr><td>LD50 (intravenous)</td><td>446 mg/kg (mouse)</td></tr></table>		LC50 (inhalation)	1807 ppm/4H (rat)	LCLo (inhalation)	5000 ppm/5M (human)	LC50 (inhalation)	326 gm/m3/2h (mouse)	LC50 (inhalation)	658000 mg/m3/4H (rat)	LC50 (inhalation)	364 g/m³/4 hours (rat)	LCLo (inhalation)	325 g/m³/2 hours (mouse)	LD50 (intravenous)	446 mg/kg (mouse)
LC50 (inhalation)	1807 ppm/4H (rat)															
LCLo (inhalation)	5000 ppm/5M (human)															
LC50 (inhalation)	326 gm/m3/2h (mouse)															
LC50 (inhalation)	658000 mg/m3/4H (rat)															
LC50 (inhalation)	364 g/m³/4 hours (rat)															
LCLo (inhalation)	325 g/m³/2 hours (mouse)															
LD50 (intravenous)	446 mg/kg (mouse)															

PROPANE (74-98-6)	
LC50 (inhalation)	> 800000 ppm/15M (rat)
CARBON DIOXIDE (124-38-9)	
LC50 (inhalation)	470000 ppm/30M (rat)
LCLo (inhalation)	9 pph/5M (human)

## 12. ECOLOGICAL INFORMATION

<b>Toxicity</b>	No information provided.
<b>Persistence and degradability</b>	No information provided.
<b>Bioaccumulative potential</b>	No information provided.
<b>Mobility in soil</b>	No information provided.
<b>Other adverse effects</b>	When discharged to the atmosphere, carbon dioxide may contribute to the greenhouse effect. Carbon monoxide is slowly oxidised in the atmosphere to carbon dioxide. When discharged into the atmosphere, methane and carbon dioxide may contribute to the greenhouse effect. Methane has a global warming potential of 21 (CO <sub>2</sub> = 1).

## 13. DISPOSAL CONSIDERATIONS

<b>Waste disposal</b>	Cylinders should be returned to the manufacturer or supplier for disposal of contents.
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>UN number</b>	1954	1954	1954
<b>Proper shipping name</b>	COMPRESSED GAS, FLAMMABLE, N.O.S.		
<b>DG class/ Division</b>	2.1	2.1	2.1
<b>Subsidiary risk(s)</b>	None Allocated	None Allocated	None Allocated
<b>Packing group</b>	None Allocated	None Allocated	None Allocated
<b>GTEPG</b>	2A1		
<b>Hazchem code</b>	2SE		
<b>EMS</b>	F-D, S-U		
<b>Other information</b>	Ensure cylinder is separated from driver and that outlet of relief device is not obstructed. Refer to Commonwealth, State and Territory Dangerous Goods Legislation which contain requirements which affect gas storage and transport.		

## 15. REGULATORY INFORMATION

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Inventory Listing(s)</b>	<b>AUSTRALIA: AICS (Australian Inventory of Chemical Substances)</b> All components are listed on AICS, or are exempt.

## 16. OTHER INFORMATION

**Additional information** The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

### Revision history

Revision	Description
1.0	Initial SDS Creation.

### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

### Prepared by

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmt.com.au](http://www.rmt.com.au).

**Product Name**      **14 COMPONENT MIXTURE (BALANCE ARGON) (# 2713)**

**Revision:** 1  
**SDS Date:** 18 February 2014

**End of SDS**