MATERIAL SAFETY DATA SHEET

Marianna Industries, Inc. 11222 "I" Street Omaha, Nebraska 68137-1296

Non-Emergency (402) 593-0211 EMERGENCY: Infotrac (800) 457-4280

I. PRODUCT IN	FORMATION	·		<u></u>		Page 1
PRODUCT NAME:	Marianna Ac	etone Nail Po	olish Remover			
CHEMICAL NAME: CHEMICAL TYPE: CAS NUMBER: N/A CHEMICAL STATE:		Pure	X_M	ixture		
INGREDIENTS:		OSHA Z1 PEL 1000 ppm	OSHA Z1A TWA 750 ppm	STEL		GIH CEL 50 ppm
CAS No. 67-64-1	Chemical Na Acetone	me %	by Weight/Wei 75%	ght		
II B. HAZARDOUS Haard Category:	IDENTIFICA	TION:				
X Acute	x c	hronic	_X Fire _	Pressure	1	Reactive
Hazardous Identification Harmful: May cause in itemating to eyes. Safety Hazards: Extremely ground and reach remove generated during property in the interest of the interest in the interest	lung damage i emely Flamma ote ignition so	f swallowed. ble. Vapors urces causing	are heavier thar g flashback fire	air, Vapors m danger, Electro	ay travel acro	ss the

NAME

ACETONE _	CAS NO.	Concentration		
<75%	64-64-1	100.00%		
CHEMICAL NAME		Toxicity Data		
(ACETONE) LD 50		LC 50		

IV. FIRST AID MEASURES:

EYE CONTACT: Irritating to eyes. Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.

SKIN CONTACT: Repeated exposure may cause skin dryness or cracking. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. Call a physician if irritation persists.

INHALATION: Vapors may cause drowsiness and dizziness. Slightly irritating to respiratory system. Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to nearest medical facility.

INGESTION: HARMFUL: May cause lung damaged if swallowed. Do Not Delay. Do not induce vomiting. If victim is alert, rinse mouth and drink ½ to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to the nearest medical facility for additional treatment. If vomiting occurs spontaneously, deep head below hips to prevent aspiration.

V. EXPOSURE CONTROL MEASURES:

EYE PROTECTION: Wear safety glasses or full face shield if splashes are likely to occur.

SKIN PROTECTION: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant. Gloves should be chemical resistant.

OTHER PROTECTIVE EQUIPMENT: Eyewash station and Safety Shower.

RESPIRATORY PROTECTION: Where air-filtering respirators are unsuitable use appropriate positive pressure breathing apparatus.

VI B: FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT: -18 C / 0 F (IP 170)

Explosion / Flammability: ca. 2.1-13% (V)

Auto Ignition Temperature: 540 C / 1,004 F (ASTM D - 2155

EXTINGUISHING MEDIA for ACETONE: Alcohol -resistant foam, water spray or fog. Dry Chemical Powder, Carbon Dioxide, Sand or Earth may be used for small fires only.

VII: Physical and Chemical Properties:

Boiling Point: -95 C / -139 F

Flashpoint: -18 C / 0 F (IP 170)

Melting Point: N/A

Vapor Pressure: 24.7 kzps @ 20 C / 68 F

SPECIFIC GRAVITY:

Sol. IN WATER: @ 20 C / 68 F Completely Miscible.

pH: N/A

Specific Gravity: 0.788 – 0.792 @ 22° C

Vapor Density: 2 @ 20 C / 68 F

Evaporation Rate: 5.6 ASTM D 3539, nBuAc=1)

Appearance of Acetone: Clear Liquid

Appearance/Odor of the Finished Product: Clear liquid purple in color with a sweet

slight aromatic bitter odor.

STABILITY AND REACTIVITY DATA:

STABILITY: Stable under normal conditions.

INCOMPATABILITY: Strong Oxidizing Agents

DECOMPOSITION: None expected under normal conditions.

ACTION TO TAKE FOR MATERIAL DISPOSAL: Recover or recycle if possible. It is the responsibility of the wate generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

ACTION TAKEN FIR CONTAINER DISPOSAL: Drain container thoroughly. After draining, vent in a safe place away from fire and sparks. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer

X. PRECAUTIONS FOR SAFE HANDLING, STORAGE AND USE:

Avoid breathing of or contact with material. Only use in a well ventilated area. Wash thoroughly after handling.

Storage: Keep away from flammables, oxidizing agents, and corrosives. Vapor is heavier than air. Beware of accumulation in pits and confined spaces.

Product Transfer: Ensure electrical continuity by bonding and grounding all equipment.

XI. SHIPPING INFORMATION:

THE SHIPPING CARTON
IDENTIFICATION MUST
BE LISTED THE SAME AS
THE DESCRIPTION ON

THE MSDS !!

Proper Shipping Name: (Acetone)

Hazard Class: 3 (Flammable Liquid)

UN Number: UN 1090

Packing Group: II

Emergency Response Guide # 127

XII: ECOLOGICAL INFORMATION:

Mobility: Recover or recycle if possible. Dissolves in water/ Readily biodegradable. Not expected to bio-accumulate significantly.

DISCLAIMER

The information in this MSDS was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond this company's control, it is the users responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising out of the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this MSDS. Various government agencies (e.g. DOT, EPA and FDA) may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this MSDS. The user should review these regulations to ensure full compliance.