

MATERIAL SAFETY DATA SHEET

(Prepared According to 29 CFR 1910.1200)

HMIS HAZARDOUS MATERIALS

IDENTIFICATION SYSTEM

A = Safety Glasses
B = A + Gloves
C = B + Apron
D = C + Face Shield
E = B + Dust Mask

F = C + Dust Mask
G = B + Respirator
H = F + Goggles
I = B + Respirator
X = Ask Supervisor

4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

Health.... 1
Flammability.... 0
Physical Hazard.... 0
Protection.... A

SECTION I - PRODUCT IDENTIFICATION

Product Code: 0354

Supersedes date: April 26, 2004

Section(s) changed: I, II

Effective date: October 11, 2011

PRODUCT NAME: INTERTHANE

CHEMICAL FAMILY: Floor Finish

GENERIC NAME: High Speed Finish with Urethane

FORMULA: Proprietary Mixture

DISTRIBUTORS NAME:

DISTRIBUTORS ADDRESS:

INFORMATION PHONE NUMBER: 314-771-6600

EMERGENCY PHONE NUMBER IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE OR ACCIDENT: CHEMTREC 800-424-9300

PROPER SHIPPING DESCRIPTION: Polishing Compound, Not Regulated

LABEL: None

SECTION II -HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS No.	Wt%	OSHA PEL	ACGIH TLV	OTHER
Diethylene Glycol Methyl Ether	111-77-3	<10	NE	NE	

The information & recommendations set forth herein are presented in good faith & believed to be current & reliable. The manufacturer makes no representation as to the completeness or accuracy thereof & supplies information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will the manufacturer be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which it refers.

SECTION III - PHYSICAL/CHEMICAL DATA

Boiling Point (°F): 212	Specific Gravity: 1.025	FLASH POINT (Method Used): None	LIMITS: LEL: NA UEL: NA
Vapor Pressure (mm Hg): 17	Lbs/Gal Density: 8.6	EXTINGUISHING MEDIA: Water spray or fog, foam, dry chemical, carbon dioxide, if product is involved.	
Vapor Density (Air=1): 0.62	pH Concentrate: 9	SPECIAL FIRE FIGHTING PROCEDURES: Avoid exposure to fumes or vapors. Wear self-contained positive pressurized breathing apparatus MSHA/NIOSH Approved or equivalent to maintain TLV.	
Evaporation Rate: (Water=1): GT 1.00	pH Use Dilution: 9	UNUSUAL FIRE & EXPLOSION HAZARD: Use water spray to cool adjacent fire exposed containers. Product will not burn but may splatter if temperature exceeds boiling point.	
Solubility in Water: Complete			
Physical Description: Opaque White Thin Liquid			
Characteristic Polymer Odor			

SECTION V - REACTIVITY DATA

Stability: Stable.	SECTION VI - STORAGE & HANDLING INFORMATION
Hazardous Polymerization: Will not occur.	KEEP OUT OF REACH OF CHILDREN. CAUTION.
Incompatibility (Materials to Avoid): Acids.	Store upright in original closed container.
Hazardous Decomposition Products: If burned, normal combustion products:	Other Precautions: Do not get in eyes, on skin or on clothing. Remove & wash contaminated clothing before reuse.
Carbon Dioxide, Carbon Monoxide; Nitrous Oxides.	

SECTION VII - HEALTH HAZARDS AND FIRST AID

Carcinogenicity: NE	NTP? NE	IARC Monographs? NE	OSHA REGULATED? NO
EFFECTS OF OVEREXPOSURE:			
SKIN: Irritation			
EYES: Irritation			
INHALATION: Irritation			
EMERGENCY FIRST AID PROCEDURES:			
SKIN: Wash with soap & water for 15 minutes. See physician if irritation persists.			
EYES: Flush with flowing water for 15 minutes & see physician.			
INHALATION: Remove to fresh air.			
INGESTION: Give milk or water to dilute material; DO NOT induce vomiting. Avoid alcohol. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.			

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: (Specify type) Normal room ventilation

VENTILATION: Avoid breathing vapor or spray.

PROTECTIVE GLOVES: N/A.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: N/A.

SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Mop up & flush to sewer with plenty of water. Floors may be slippery. Use care to avoid falls.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State & Local regulations.

SECTION X - ADDITIONAL FEDERAL REGULATIONS

SARA TITLE III (EPCRA) NOTIFICATION: GLYCOL ETHERS

COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT (CERCLA) NOTIFICATION: GLYCOL ETHERS

For more information, consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68.

NE - Not Established NA - Not Applicable GT - Greater Than