



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-1471-3	Version Number:	2.00
Issue Date:	18/07/2016	Supersedes Date:	17/06/2015

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ High Power Brake Cleaner, PN 08880

Product Identification Numbers

60-4550-8249-9 60-4550-8252-3

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1.
Gas Under Pressure: Liquefied gas.
Acute Toxicity (oral): Category 4.
Serious Eye Damage/Irritation: Category 2.
Skin Corrosion/Irritation: Category 2.
Aspiration Hazard: Category 1.
Reproductive Toxicity: Category 2.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H320	Causes eye irritation.
H315	Causes skin irritation.
H304	May be fatal if swallowed and enters airways.
H361	Suspected of damaging fertility or the unborn child.
H351	Suspected of causing cancer.
H370	Causes damage to organs: cardiovascular system sensory organs
H371	May cause damage to organs: sensory organs
H372	Causes damage to organs through prolonged or repeated exposure: nervous system
H373	May cause damage to organs through prolonged or repeated exposure: sensory organs

Precautionary statements

General:

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P281	Use personal protective equipment as required.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.

3M™ High Power Brake Cleaner, PN 08880

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Storage:

P410 + P412
P403
P405

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
Store in a well-ventilated place.
Store locked up.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

May cause drowsiness or dizziness.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Heptane, branched, cyclic and linear	426260-76-6	30 - 60
Propane	74-98-6	10 - 30
Xylene	1330-20-7	10 - 30
Ethylbenzene	100-41-4	1 - 10
Methyl Alcohol	67-56-1	5 - 10
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8	0 0.604
DO NOT DISCLOSE ON SDS - ISOBUTANE	75-28-5	0 0.604
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0	0 0.0755

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration

with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management. Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg.

chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Protect from sunlight. Store in a well-ventilated place. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Ethylbenzene	100-41-4	CMRG	TWA:25 ppm;STEL:75 ppm	
Ethylbenzene	100-41-4	Malaysia OELs	TWA(8 hours):434 mg/m3(100 ppm)	
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8	ACGIH	STEL:1000 ppm	
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8	Malaysia OELs	TWA(8 hours):1900 mg/m3(800 ppm)	
Natural gas	106-97-8	ACGIH	Limit value not established:	
Xylene	1330-20-7	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcin
Xylene	1330-20-7	CMRG	TWA:50 ppm;STEL:75 ppm	
Xylene	1330-20-7	Malaysia OELs	TWA(8 hours):434 mg/m3(100 ppm)	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	SKIN
Methyl Alcohol	67-56-1	Malaysia OELs	TWA(8 hours):262 mg/m3(200 ppm)	SKIN
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0	ACGIH	Limit value not established:	
Propane	74-98-6	ACGIH	Limit value not established:	
Propane	74-98-6	Malaysia OELs	TWA(8 hours):2500 ppm	
DO NOT DISCLOSE ON SDS - ISOBUTANE	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CELL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Appearance/Odor	Clear colorless; Solvent odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	<i>No Data Available</i>
Flash Point	≥ -104.4 °C
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	275,789.4 Pa [@ 21.1 °C]
Vapor Density	≥ 1 [Ref Std: AIR=1]
Density	0.699 g/ml
Relative Density	0.699 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	699 g/l [Test Method: calculated SCAQMD rule 443.1]
Volatile Organic Compounds	100 % weight [Test Method: calculated per CARB title 2]
Percent volatile	100 % weight
VOC Less H2O & Exempt Solvents	699 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. May cause additional health effects (see below).

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Harmful if swallowed. Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking,

burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE 20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE 300 - 2,000 mg/kg
Heptane, branched, cyclic and linear	Dermal	Rabbit	LD50 > 2,000 mg/kg
Heptane, branched, cyclic and linear	Inhalation-Vapor (4 hours)	Rat	LC50 > 73.5 mg/l
Heptane, branched, cyclic and linear	Ingestion	Rat	LD50 > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l

3M™ High Power Brake Cleaner, PN 08880

	Vapor (4 hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
DO NOT DISCLOSE ON SDS - ISOBUTANE	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
DO NOT DISCLOSE ON SDS - ETHANE	Inhalation-Gas		LC50 estimated to be > 50,000 ppm

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Propane	Rabbit	Minimal irritation
Methyl Alcohol	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Mild irritant
DO NOT DISCLOSE ON SDS - ISOBUTANE	Professional judgment	No significant irritation
DO NOT DISCLOSE ON SDS - BUTANE	Professional judgment	No significant irritation
DO NOT DISCLOSE ON SDS - ETHANE	Professional judgment	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Propane	Rabbit	Mild irritant
Methyl Alcohol	Rabbit	Moderate irritant
Ethylbenzene	Rabbit	Moderate irritant
DO NOT DISCLOSE ON SDS - ISOBUTANE	Professional judgment	No significant irritation
DO NOT DISCLOSE ON SDS - BUTANE	Rabbit	No significant irritation
DO NOT DISCLOSE ON SDS - ETHANE	Professional judgment	No significant irritation

Skin Sensitization

Name	Species	Value
Methyl Alcohol	Guinea pig	Not sensitizing
Ethylbenzene	Human	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value

3M™ High Power Brake Cleaner, PN 08880

Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Propane	In Vitro	Not mutagenic
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
DO NOT DISCLOSE ON SDS - ISOBUTANE	In Vitro	Not mutagenic
DO NOT DISCLOSE ON SDS - BUTANE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Xylene	Inhalation	Some positive female reproductive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	during gestation
Methyl Alcohol	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
Ethylbenzene	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 4.3 mg/l	premating & during gestation

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Does not cause effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

3M™ High Power Brake Cleaner, PN 08880

						Duration
Heptane, branched, cyclic and linear	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg	not applicable
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
DO NOT DISCLOSE ON SDS - ISOBUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
DO NOT DISCLOSE ON SDS - ISOBUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
DO NOT DISCLOSE ON SDS - ISOBUTANE	Inhalation	respiratory irritation	All data are negative	Mouse	NOAEL Not available	
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	heart	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 5,000 ppm	25 minutes
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	respiratory irritation	All data are negative	Rabbit	NOAEL Not available	
DO NOT DISCLOSE ON SDS - ETHANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	

3M™ High Power Brake Cleaner, PN 08880

DO NOT DISCLOSE ON SDS - ETHANE	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 150,000 ppm	not available
---------------------------------	------------	-----------------------	--	-----	-------------------	---------------

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system hematopoietic system muscles kidney and/or bladder respiratory system	All data are negative	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	All data are negative	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Methyl Alcohol	Inhalation	liver	All data are negative	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	All data are negative	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl Alcohol	Ingestion	liver nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	90 days
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	All data are negative	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	All data are negative	Multiple animal species	NOAEL 3.3 mg/l	2 years

3M™ High Power Brake Cleaner, PN 08880

Ethylbenzene	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 680 mg/kg/day	6 months
DO NOT DISCLOSE ON SDS - ISOBUTANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 4,500 ppm	13 weeks
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 4,489 ppm	90 days
DO NOT DISCLOSE ON SDS - BUTANE	Inhalation	blood	All data are negative	Rat	NOAEL 4,489 ppm	90 days

Aspiration Hazard

Name	Value
Heptane, branched, cyclic and linear	Aspiration hazard
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
DO NOT DISCLOSE ON SDS - ISOBUTANE	75-28-5		Data not available or insufficient for classification			
Xylene	1330-20-7		Data not available or insufficient for classification			
Methyl Alcohol	67-56-1	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	22,300 mg/l
Methyl Alcohol	67-56-1	Water flea	Experimental	48 hours	Effect Concentration 50%	22,200 mg/l
Methyl Alcohol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	Effect Concentration 50%	16.9 mg/l

3M™ High Power Brake Cleaner, PN 08880

Methyl Alcohol	67-56-1	Algae or other aquatic plants	Experimental	96 hours	No obs Effect Conc	9.96 mg/l
Ethylbenzene	100-41-4	Green Algae	Experimental	96 hours	Effect Concentration 50%	3.6 mg/l
Ethylbenzene	100-41-4	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	24 hours	Effect Concentration 50%	1.81 mg/l
Propane	74-98-6		Data not available or insufficient for classification			
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0		Laboratory		Lethal Concentration 50%	>100 mg/l
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0		Data not available or insufficient for classification			
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8		Data not available or insufficient for classification			
Heptane, branched, cyclic and linear	426260-76-6		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	Other methods
DO NOT DISCLOSE ON SDS - ISOBUTANE	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.7 days (t 1/2)	Other methods
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Other methods
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	Other methods
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0	Laboratory Photolysis		Photolytic half-life (in air)	119.74 days (t 1/2)	Other methods
Heptane, branched, cyclic and linear	426260-76-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M™ High Power Brake Cleaner, PN 08880

Xylene	1330-20-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methyl Alcohol	67-56-1	Experimental Biodegradation	14 days	Biological Oxygen Demand	92 % weight	OECD 301C - MITI (I)
Ethylbenzene	100-41-4	Laboratory Biodegradation	14 days	Biological Oxygen Demand	81 % weight	Other methods

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Heptane, branched, cyclic and linear	426260-76-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane	74-98-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Xylene	1330-20-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methyl Alcohol	67-56-1	Experimental BCF-Carp	3 days	Bioaccumulation Factor	1	Other methods
DO NOT DISCLOSE ON SDS - ISOBUTANE	75-28-5	Experimental BCF - Other		Bioaccumulation Factor	1.97	Other methods
Ethylbenzene	100-41-4	Experimental BCF - Other		Bioaccumulation Factor	15	Other methods
DO NOT DISCLOSE ON SDS - BUTANE	106-97-8	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	2.89	Other methods
DO NOT DISCLOSE ON SDS - ETHANE	74-84-0	Laboratory Bioaccumulation		Log of Octanol/H ₂ O part. coeff	1.81	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed

premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: None assigned.

Hazard Class/Division: 2.1

Subsidiary Risk: None assigned.

Packing Group: None assigned.

Limited Quantity: Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: None assigned.

Hazard Class/Division: 2.1

Subsidiary Risk: None assigned.

Packing Group: None assigned.

Limited Quantity: None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my