

# Safety Data Sheet

Copyright,2021, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	25-1630-0	Version number:	6.00
Issue Date:	22/09/2021	Supersedes date:	30/03/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

### 1.1. Product identifier

3M(TM) Rubber & Vinyl 80 Spray Adhesive

**Product Identification Numbers** 62-4996-4955-6

### 1.2. Recommended use and restrictions on use

### **Recommended use**

Adhesive aerosol.

For Industrial or Professional use only.

### 1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

**1.4. Emergency telephone number** EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Gas Under Pressure: Dissolved gas. Serious Eye Damage/Irritation: Category 2. Reproductive Toxicity: Category 1. Specific Target Organ Toxicity (repeated exposure): Category 2.

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

### Signal word

Danger

### Symbols

Flame |Gas cylinder |Exclamation mark |Health Hazard |

### Pictograms



Hazard statements			
H222	Extremely flammable aerosol.		
H229	Pressurised container: may burst if heated.		
H280	Contains gas under pressure; may explode if heated.		
H319	Causes serious eye irritation.		
H360	May damage fertility or the unborn child.		
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   sensory organs.		
Precautionary statements General:			
P102	Keep out of reach of children.		
Prevention:			
P201	Obtain special instructions before use.		
P202	Do not handle until all safety precautions have been read and understood.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P211	Do not spray on an open flame or other ignition source.		
P251	Do not pierce or burn, even after use.		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P264	Wash thoroughly after handling.		
P280F	Wear respiratory protection.		
Response:			
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308 + P313	IF exposed or concerned: Get medical advice/attention.		
P314	Get medical advice/attention if you feel unwell.		
P337 + P313	IF eye irritation persists: Get medical advice/attention.		
Storage:			
P405	Store locked up.		
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.		
Disposal:			

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. Aspiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to prevent formation of a stream during usage. May displace oxygen and cause rapid suffocation.

### 2.4. Other hazards which do not result in classification

Causes mild skin irritation. May be harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight	
Methyl acetate	79-20-9	30 - 40	
Dimethyl ether	115-10-6	25 - 35	
Cyclohexane	110-82-7	< 20	
Trade Secret components	Trade Secret	5 - 20	
Toluene	108-88-3	1 - 6	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	< 5	
Synthetic Resin	Trade Secret	< 5	
Acetone	67-64-1	< 2	
4-Methylpentan-2-one	108-10-1	<= 0.5	
Rosin	8050-09-7	< 0.5	
Zinc Oxide	1314-13-2	< 0.2	

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

### Hazchem Code: 2YE

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. WARNING ! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

# SECTION 8: Exposure controls/personal protection

# 8.1 Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
4-Methylpentan-2-one	108-10-1	ACGIH	TWA:20 ppm;STEL:75 ppm	A3: Confirmed animal
				carcinogen.
4-Methylpentan-2-one	108-10-1	Australia OELs	TWA(8 hours): 205 mg/m3	
			(50 ppm); STEL(15	
			minutes): 307 mg/m3 (75 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcinogen, Ototoxicant
Toluene	108-88-3	Australia OELs	TWA(8 hours):191 mg/m3(50	SKIN
			ppm);STEL(15 minutes):574	
			mg/m3(150 ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	Australia OELs	TWA(8 hours):350	
-			mg/m3(100 ppm);STEL(15	
			minutes):1050 mg/m3(300	
			ppm)	
Dimethyl ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Dimethyl ether	115-10-6	Australia OELs	TWA(8 hours):760	
5			mg/m3(400 ppm);STEL(15	
			minutes):950 mg/m3(500 ppm)	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2	
			mg/m3;STEL(respirable	
			fraction):10 mg/m3	
Zinc Oxide	1314-13-2	Australia OELs	TWA(Inspirable dust)(8	
			hours):10 mg/m3;TWA(as	
			fume)(8 hours):5	
			mg/m3;STEL(as fume)(15	
			minutes):10 mg/m3	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human
				carcin
Acetone	67-64-1	Australia OELs	TWA(8 hours):1185	
			mg/m3(500 ppm);STEL(15	
			minutes):2375 mg/m3(1000	
			ppm)	
Methyl acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl acetate	79-20-9	Australia OELs	TWA(8 hours):606	
, <del>.</del>			mg/m3(200 ppm);STEL(15	
			minutes):757 mg/m3(250 ppm)	
Rosin	8050-09-7	ACGIH	TWA(as Resin, inhalable	Dermal/Respiratory
			fraction):0.001 mg/m3	Sensitiser
Rosin	8050-09-7	Australia OELs	TWA(as formaldehyde)(8	
			hours):0.1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Select and use gloves according to AS/NZ 2161.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Half facepiece or full facepiece supplied-air respirator.

Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.	
Colour	Clear Yellow	
Odour	Sweet Odour, Fruity Odour	
Odour threshold	No data available.	
рН	Not applicable.	
Melting point/Freezing point	Not applicable.	
Boiling point/Initial boiling point/Boiling range	Not applicable.	
Flash point	-41.1 °C [Test Method: Tagliabue Open Cup]	

	10  [D  CC, I  TTUED  1]	
Evaporation rate	1.9 [ <i>Ref Std</i> :ETHER=1]	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	Not applicable.	
Vapor Density and/or Relative Vapor Density	> 1  [ <i>Ref Std</i> :AIR=1]	
Density	0.835 g/ml	
Relative density	0.835 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Negligible	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	Not applicable.	
Viscosity/Kinematic Viscosity	Not applicable.	
Volatile organic compounds (VOC)	<=714 g/l [Details: EU VOC content]	
Percent volatile	85.5 % weight	
VOC less H2O & exempt solvents	<=631 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]	
VOC less H2O & exempt solvents	<=5.27 lb/gal [ <i>Test Method</i> :calculated SCAQMD rule 443.1]	
VOC less H2O & exempt solvents	<=53.6 % [ <i>Test Method</i> :calculated per CARB title 2]	
Molecular weight	No data available.	
Solids content	10 - 20 %	

### Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

# 10.2 Chemical stability

Stable.

## 10.3. Conditions to avoid

Heat. Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## **10.5 Incompatible materials**

Strong oxidising agents.

## 10.6 Hazardous decomposition products

Substance

None known.

Condition

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

May be harmful if inhaled. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### **Additional Health Effects:**

### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

### Prolonged or repeated exposure may cause target organ effects:

Ocular effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

### **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000
			mg/kg
Overall product	Inhalation-Vapour(4		No data available; calculated ATE20 - 50
-	hr)		mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000
_	-		mg/kg

Methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 49 mg/l
Methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Dimethyl ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapour (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Trade Secret components	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Trade Secret components	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Synthetic Resin	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Synthetic Resin	Ingestion	Rat	LD50 > 2,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 5,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
4-Methylpentan-2-one	Dermal	Rabbit	LD50 > 16,000 mg/kg
4-Methylpentan-2-one	Inhalation-Vapour (4 hours)	Rat	LC50 >8.2,<16.4 mg/l
4-Methylpentan-2-one	Ingestion	Rat	LD50 3,038 mg/kg
Rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
Rosin	Ingestion	Rat	LD50 7,600 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### **Skin Corrosion/Irritation**

Name	Species	Value
	_	
Methyl acetate	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Toluene	Rabbit	Irritant
Acetone	Mouse	Minimal irritation
Synthetic Resin	In vitro data	No significant irritation
Naphtha (petroleum), hydrotreated heavy	Rabbit	Mild irritant
4-Methylpentan-2-one	Rabbit	Mild irritant
Rosin	Rabbit	No significant irritation
Zinc Oxide	Human and animal	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Methyl acetate	Rabbit	Moderate irritant

# 3M(TM) Rubber & Vinyl 80 Spray Adhesive

Cyclohexane	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Acetone	Rabbit	Severe irritant
Synthetic Resin	In vitro data	No significant irritation
Naphtha (petroleum), hydrotreated heavy	Rabbit	Mild irritant
4-Methylpentan-2-one	Rabbit	Mild irritant
Rosin	Rabbit	Mild irritant
Zinc Oxide	Rabbit	Mild irritant

### **Skin Sensitisation**

Name	Species	Value
Methyl acetate	Human	Not classified
Toluene	Guinea pig	Not classified
Synthetic Resin	Multiple animal species	Not classified
Naphtha (petroleum), hydrotreated heavy	Guinea pig	Not classified
4-Methylpentan-2-one	Guinea pig	Not classified
Rosin	Guinea pig	Sensitising
Zinc Oxide	Guinea pig	Not classified

## **Respiratory Sensitisation**

Name	Species	Value
Rosin	Human	Not classified

# Germ Cell Mutagenicity

Name	Route	Value
Methyl acetate	In Vitro	Not mutagenic
Methyl acetate	In vivo	Not mutagenic
Dimethyl ether	In Vitro	Not mutagenic
Dimethyl ether	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Synthetic Resin	In Vitro	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
4-Methylpentan-2-one	In Vitro	Not mutagenic
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification

# Carcinogenicity

Name	Route	Species	Value
Dimethyl ether	Inhalation	Rat	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Acetone	Not specified.	Multiple animal	Not carcinogenic
		species	
Naphtha (petroleum), hydrotreated heavy	Not specified.	Not available	Not carcinogenic
4-Methylpentan-2-one	Inhalation	Multiple animal species	Carcinogenic.

# **Reproductive Toxicity**

## **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	<b>Exposure Duration</b>
Dimethyl ether	Inhalation	Not classified for	Rat	NOAEL	during
		development		40,000 ppm	organogenesis
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 24	2 generation
		female reproduction		mg/l	
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 24	2 generation
-				mg/l	
Cyclohexane	Inhalation	Not classified for	Rat	NOAEL 6.9	2 generation
		development		mg/l	-
Toluene	Inhalation	Not classified for	Human	NOAEL Not	occupational
		female reproduction		available	exposure
Toluene	Inhalation	Not classified for	Rat	NOAEL 2.3	1 generation
		male reproduction		mg/l	
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during gestation
		-		mg/kg/day	
Toluene	Inhalation	Toxic to development	Human	NOAEL Not	poisoning and/or
		-		available	abuse
Acetone	Ingestion	Not classified for	Rat	NOAEL	13 weeks
	0	male reproduction		1,700	
				mg/kg/day	
Acetone	Inhalation	Not classified for	Rat	NOAEL 5.2	during
		development		mg/l	organogenesis
Naphtha (petroleum),	Not specified.	Not classified for	Rat	NOAEL Not	premating & during
hydrotreated heavy	·	female reproduction		available	gestation
Naphtha (petroleum),	Not specified.	Not classified for	Rat	NOAEL Not	28 days
hydrotreated heavy	·	male reproduction		available	-
Naphtha (petroleum),	Not specified.	Not classified for	Rat	NOAEL Not	during gestation
hydrotreated heavy	·	development		available	
4-Methylpentan-2-	Inhalation	Not classified for	Multiple animal	NOAEL 8.2	2 generation
one		female reproduction	species	mg/l	
4-Methylpentan-2-	Ingestion	Not classified for	Rat	NOAEL	13 weeks
one	e	male reproduction		1,000	
				mg/kg/day	
4-Methylpentan-2-	Inhalation	Not classified for	Multiple animal	NOAEL 8.2	2 generation
one		male reproduction	species	mg/l	-
4-Methylpentan-2-	Inhalation	Not classified for	Mouse	NOAEL 12.3	during
one		development		mg/l	organogenesis
Zinc Oxide	Ingestion	Not classified for	Multiple animal	NOAEL 125	premating & during
		reproduction and/or	species	mg/kg/day	gestation
		development			-

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target	Value	Species	Test result	Exposure
		Organ(s)				Duration
Methyl acetate	Inhalation	central nervous system	May cause drowsiness or	Human and animal	NOAEL Not available	
		depression	dizziness			

Methyl acetate	Inhalation	respiratory irritation	May cause respiratory	Human and animal	NOAEL Not available	
			irritation	ammai		
Methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl	Ingestion	central nervous	May cause		NOAEL Not	
acetate		system depression	drowsiness or dizziness		available	
Dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
4- Methylpentan -2-one	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL 0.1 mg/l	2 hours
4- Methylpentan -2-one	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL 0.9 mg/l	7 minutes

# 3M(TM) Rubber & Vinyl 80 Spray Adhesive

4- Methylpentan -2-one	Inhalation	vascular system	Not classified	Dog	NOAEL Not available	not available
4- Methylpentan -2-one	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 900 mg/kg	not applicable

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure

		vascular system				
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Synthetic Resin	Ingestion	heart   gastrointestinal tract   hematopoietic system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days
4- Methylpentan -2-one	Inhalation	liver	Not classified	Rat	NOAEL 0.41 mg/l	13 weeks
4- Methylpentan -2-one	Inhalation	heart	Not classified	Multiple animal species	NOAEL 0.8 mg/l	2 weeks
4- Methylpentan	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 0.4 mg/l	90 days

-2-one						
4- Methylpentan -2-one	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 4.1 mg/l	14 weeks
4- Methylpentan -2-one	Inhalation	endocrine system   hematopoietic system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	90 days
4- Methylpentan -2-one	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 0.41 mg/l	13 weeks
4- Methylpentan -2-one	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4- Methylpentan -2-one	Ingestion	heart   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 1,040 mg/kg/day	120 days
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months

### **Aspiration Hazard**

Name	Value
Cyclohexane	Aspiration hazard
Toluene	Aspiration hazard
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
4-Methylpentan-2-one	Some positive data exist, but the data are not sufficient
	for classification

### Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

### **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

Acute aquatic hazard: GHS Acute 2: Toxic to aquatic life.

### Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Methyl acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	EC50	>120 mg/l
Methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
Dimethyl ether	115-10-6	Bacteria	Experimental		EC10	>1,600 mg/l
Dimethyl ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead	Experimental	96 hours	LC50	4.53 mg/l
Cyclonexule	110 02 /	minnow	Experimental	50 110015	LC30	4.55 mg/1
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Trade Secret	Trade Secret		Data not	10 110 010		n/a
components			available or			n, u
· · · · P · · · · · ·			insufficient for			
			classification			
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated	Experimental	12 hours	IC50	292 mg/l
Toruene	100-00-5	sludge	Experimental	12 110013	10.50	272 mg/1
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of
						bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry
						Weight)
Naphtha	64742-48-9	Green Algae	Experimental	72 hours	EL50	>1,000 mg/l
(petroleum),						
hydrotreated						
heavy		D 1	<b>F</b>	0.61	1.1.50	1.000 /1
Naphtha	64742-48-9	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
(petroleum),						
hydrotreated						
heavy	(1710 10 0	117 / Cl	<b>D</b> 1	40.1		. 1 000 /1
Naphtha	64742-48-9	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
(petroleum),						
hydrotreated						
heavy	(4742 49 0	Current 1	Francis (1	72 1	NOFI	> 1.000 m s /l
Naphtha	64742-48-9	Green Algae	Experimental	72 hours	NOEL	>1,000 mg/l
(petroleum),						
hydrotreated						
heavy	(4742 49 0	Weter C	E	21.1-	NOFI	<1
Naphtha	64742-48-9	Water flea	Experimental	21 days	NOEL	<1 mg/l

(petroleum),		1				
hydrotreated heavy						
Synthetic Resin	Trade Secret	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
Synthetic Resin	Trade Secret	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Synthetic Resin	Trade Secret	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustecea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
4- Methylpentan- 2-one	108-10-1	Green Algae	Experimental	96 hours	EC50	400 mg/l
4- Methylpentan- 2-one	108-10-1	Water flea	Experimental	48 hours	EC50	>200 mg/l
4- Methylpentan- 2-one	108-10-1	Zebra Fish	Experimental	96 hours	LC50	>179 mg/l
4- Methylpentan- 2-one	108-10-1	Fathead minnow	Experimental	32 days	NOEC	56.2 mg/l
4- Methylpentan- 2-one	108-10-1	Water flea	Experimental	21 days	NOEC	78 mg/l
4- Methylpentan- 2-one	108-10-1	Activated sludge	Experimental	30 minutes	EC50	>1,000
Rosin	8050-09-7	Bacteria	Experimental		EC50	76.1 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	EL50	>100 mg/l
Rosin	8050-09-7	Water flea	Experimental	48 hours	EL50	911 mg/l
Rosin	8050-09-7	Zebra Fish	Experimental	96 hours	LL50	>1 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	NOEL	100 mg/l
Zinc Oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
Zinc Oxide	1314-13-2	Green Algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc Oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc Oxide	1314-13-2	Green Algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl acetate	79-20-9	Experimental	28 days	BOD	70 % weight	OECD 301D - Closed
		Biodegradation				bottle test
Dimethyl ether	115-10-6	Experimental		Photolytic half-	12.4 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Dimethyl ether	115-10-6	Experimental	28 days	BOD	5 % weight	OECD 301D - Closed

		Biodegradation				bottle test
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half- life (in air)	1/2)	Non-standard method
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 % BOD/ThBOD	OECD 301F - Manometric respirometry
Trade Secret components	Trade Secret	Data not available- insufficient			N/A	
Toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Experimental Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Synthetic Resin	Trade Secret	Experimental Biodegradation	28 days	BOD	4 % BOD/ThBOD	OECD 301D - Closed bottle test
Acetone	67-64-1	Experimental Photolysis		Photolytic half- life (in air)	147 days (t 1/2)	
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % BOD/ThBOD	OECD 301D - Closed bottle test
4- Methylpentan- 2-one	108-10-1	Experimental Photolysis		Photolytic half- life (in air)	2.3 days (t 1/2)	
4- Methylpentan- 2-one	108-10-1	Experimental Biodegradation	28 days	BOD	83 % BOD/ThBOD	OECD 301F - Manometric respirometry
Rosin	8050-09-7	Experimental Biodegradation	28 days	CO2 evolution	64 % weight	OECD 301B - Modified sturm or CO2
Zinc Oxide	1314-13-2	Data not available- insufficient			N/A	

# **12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl acetate	79-20-9	Experimental Bioconcentrati on		Log Kow	0.18	Non-standard method
Dimethyl ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cyclohexane	110-82-7	Experimental BCF-Carp	56 days	Bioaccumulatio n factor	129	OECD 305E - Bioaccumulation flow- through fish test
Trade Secret components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulatio n factor	90	

Toluene	108-88-3	Experimental Bioconcentrati on		Log Kow	2.73	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Estimated Bioconcentrati on		Log Kow	>4	Non-standard method
Synthetic Resin	Trade Secret	Experimental Bioconcentrati on		Log Kow	7.41	Non-standard method
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulatio n factor	0.65	
Acetone	67-64-1	Experimental Bioconcentrati on		Log Kow	-0.24	
4- Methylpentan- 2-one	108-10-1	Experimental Bioconcentrati on		Log Kow	1.9	OECD 117 log Kow HPLC method
Rosin	8050-09-7	Estimated BCF - Rainbow Trout	20 days	Bioaccumulatio n factor	129	Non-standard method
Zinc Oxide	1314-13-2	Experimental BCF-Carp	56 days	Bioaccumulatio n factor	≤217	OECD 305E - Bioaccumulation flow- through fish test

## 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport UN No.: UN1950 Proper shipping name: AEROSOLS Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable. Special Instructions: Limited quantity may apply Hazchem Code: 2YE IERG: 49

International Air Transport Association (IATA) - Air Transport UN No.: UN1950 Proper shipping name: AEROSOLS, FLAMMABLE Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1950 Proper shipping name: AEROSOLS Class/Division: 2.1 Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable. Special Instructions: Limited quantity may apply

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Australian Inventory Status:

The chemical components contained within this product are listed on the Australian Inventory of Chemical Substances and are in compliance with the requirements of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

# **SECTION 16: Other information**

### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

### 3M Australia SDSs are available at www.3m.com.au