

Issuing date 14-Jan-2015

Revision Date 08-Jul-2019

Version 1.03

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**Product identifier****Product name** 80-769 POWER & AIR TOOL CONDITIONER**Recommended use of the chemical and restrictions on use****Product code** 80-769**Product Type** Non-flammable aerosol
Synonyms None**Supplier's details****Recommended Use** Power/Air Tool Conditioner.**Uses advised against** **No information available****Manufactured For:**
Kimball Midwest
4800 Roberts Rd.
Columbus, OH 43228
800-233-1294**Emergency telephone number**
Chemical Emergency Phone Number CHEMTREC : 1-800-424-9300
Company Emergency Phone Number 1-800-233-1294


2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER		
Hazard Statements Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Contains gas under pressure; may explode if heated		
		
Appearance Clear	Physical state Aerosol	Odor Solvent

Precautionary Statements - Prevention

Wash hands and face thoroughly after handling
 Wear protective gloves, eye protection, face protection.
 Avoid breathing fumes, gas, mist, vapors, spray.
 Use only outdoors or in a well-ventilated area.

Precautionary Statements - Response

Specific treatment (see first aid on this label).
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice, attention
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice, attention.
 Take off contaminated clothing and wash it before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor, physician if you feel unwell.
 IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician.
 Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents, container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

None

Other information

0.00638% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	50-60
PETROLEUM DISTILLATES	64742-89-8	20-30
ISOPROPYL ALCOHOL	67-63-0	1-10
PETROLEUM HYDROCARBON MIXTURE	MIXTURE	1-10
CARBON DIOXIDE	124-38-9	1-10
ETHYL BENZENE	100-41-4	<0.1
BENZENE	71-43-2	<0.1
XYLENE	1330-20-7	<0.1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing.
Eye contact	In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.
Skin contact	Rinse with plenty of water. Consult a physician if irritation persists.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause dizziness or drowsiness. Harmful and may be fatal if swallowed and enters airways.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**Water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition.

Explosion Data**Sensitivity to Mechanical Impact** none.**Sensitivity to Static Discharge** Yes.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand, or other non-combustible material and transfer to containers . Prevent further leakage if safe to do so.

Methods for cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth, or other noncombustible absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition .Keep in properly labeled containers. Keep out of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³

CARBON DIOXIDE 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m ³ (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
BENZENE 71-43-2	STEL: 2.5 ppm TWA: 0.5 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028 TWA: 1 ppm (vacated) TWA: 10 ppm unless specified in 1910.1028 (vacated) STEL: 50 ppm 10 min unless specified in 1910.1028 (vacated) Ceiling: 25 ppm unless specified in 1910.1028 Ceiling: 25 ppm STEL: 5 ppm see 29 CFR 1910.1028	IDLH: 500 ppm TWA: 0.1 ppm STEL: 1 ppm
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	Not Established

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Clear	Odor Threshold	
Color	Red		

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range		
Flash Point	12 °C / 54 °F	Based on lowest flashpoint of the products constituents.
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit		
lower flammability limit		
Vapor pressure		
Vapor density		
Specific Gravity	0.842	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	
Decomposition temperature		
Viscosity	No information available	
Explosive properties		
<u>Other information</u>		
VOC Content(%)	39.12	

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, oxidizing agents.

Hazardous Decomposition Products

Carbon oxides , Hydrocarbons, Fumes.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Avoid inhaling vapors or mists. Harmful if inhaled. May cause irritation to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Causes skin irritation.
Ingestion	Harmful and may be fatal if swallowed and enters airways.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
PETROLEUM DISTILLATES 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
ISOPROPYL ALCOHOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
ETHYL BENZENE 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
BENZENE 71-43-2	= 810 mg/kg (Rat)	> 8200 mg/kg (Rabbit)	= 44.66 mg/L (Rat) 4 h
XYLENE 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Causes skin and eye irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Harmful and may be fatal if ingested and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.
Eye damage/irritation Irritating to eyes.
Irritation Causes skin and eye irritation. May cause respiratory irritation.
Sensitization No information available.
Germ cell mutagenicity Not a germ cell mutagen.
Carcinogenicity . The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.
 Ethyl Benzene and Benzene are in the product at <0.1 % reportable levels.

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHYL BENZENE 100-41-4	A3	Group 2B	-	X
BENZENE 71-43-2	A1	Group 1	Known	X
XYLENE 1330-20-7	-	Group 3	-	-

Reproductive toxicity The ingredients are not reproductive hazards.
Specific target organ systemic toxicity (single exposure) May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ systemic toxicity (repeated exposure) No information available.
Chronic toxicity Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest.
Target Organ Effects Skin, Eyes, Respiratory System, and Central Nervous System.
Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.00638% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
PETROLEUM DISTILLATES 64742-89-8	4700 mg/L EC50 Pseudokirchneriella subcapitata 72h	-	-	-

ISOPROPYL ALCOHOL 67-63-0	1000 mg/L EC50 Desmodesmus subspicatus 96h 1000 mg/L EC50 Desmodesmus subspicatus 72h	9640 mg/L LC50 Pimephales promelas 96h flow-through 11130 mg/L LC50 Pimephales promelas 96h static 1400000 µg/L LC50 Lepomis macrochirus 96h	-	13299 mg/L EC50 Daphnia magna 48h
CARBON DIOXIDE 124-38-9	-	0.46 mg/L LC50 Oncorhynchus mykiss	-	-
ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 32 mg/L LC50 Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
BENZENE 71-43-2	29 mg/L EC50 Pseudokirchneriella subcapitata 72h	10.7 - 14.7 mg/L LC50 Pimephales promelas 96h flow-through 5.3 mg/L LC50 Oncorhynchus mykiss 96h flow-through 22.49 mg/L LC50 Lepomis macrochirus 96h static 28.6 mg/L LC50 Poecilia reticulata 96h static 22330 - 41160 µg/L LC50 Pimephales promelas 96h static 70000 - 142000 µg/L LC50 Lepomis macrochirus 96h static	-	8.76 - 15.6 mg/L EC50 Daphnia magna 48h Static 10 mg/L EC50 Daphnia magna 48h
XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h

Persistence and degradability

.

Bioaccumulation

.

Chemical Name	log Pow
ISOPROPYL ALCOHOL 67-63-0	0.05
ETHYL BENZENE 100-41-4	3.2
BENZENE 71-43-2	2.1
XYLENE	3.15

1330-20-7

Other adverse effects No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state, and local regulations.**Contaminated packaging** Do not re-use empty containers.**14. TRANSPORT INFORMATION****DOT Ground** CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY**IATA** UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, LTD. QTY**IMDG** UN1950, AEROSOLS, 2.2,LTD. QTY.**15. REGULATORY INFORMATION****International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	Not listed	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	Not listed	X	X	X	X
ISOPROPYL ALCOHOL	X	X	X	X	X	X	X	X
CARBON DIOXIDE	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
BENZENE	X	X	X	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X

Legend:**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**CHINA** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does contain a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
ISOPROPYL ALCOHOL - 67-63-0	67-63-0	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	<0.1	0.1
BENZENE - 71-43-2	71-43-2	<0.1	0.1
XYLENE - 1330-20-7	1330-20-7	<0.1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Star Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product does contain the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
BENZENE 71-43-2	10 lb	X	X	X
XYLENE 1330-20-7	100 lb			X

CERCLA

This material, as supplied, does contain substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
BENZENE 71-43-2	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	California Prop. 65
ETHYL BENZENE - 100-41-4	Cancer /<0.1%
BENZENE - 71-43-2	Cancer Developmental (Male) /<0.1%

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PETROLEUM DISTILLATES 64742-89-8			X
ISOPROPYL ALCOHOL 67-63-0	X	X	X
CARBON DIOXIDE 124-38-9	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
BENZENE 71-43-2	X	X	X
XYLENE 1330-20-7	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 2	Physical Hazard 1	Personal protection B

Prepared By Regulatory Affairs
 Issuing date 14-Jan-2015
 Revision Date 08-Jul-2019
 Revision Note

(M)SDS sections updated 2 3 11 15 16

Disclaimer

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that the supplier believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of the supplier's control, the supplier makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

End of Safety Data Sheet