

SAFETY DATA SHEET

2401

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER**1.1 Product identifier****Product name** 40% OXYGEN BALANCE NITROGEN**Synonym(s)** 2401 - SDS NUMBER • 285 - 288 - 292 - SPECIAL GAS MIXTURE • DIV14116DIV16 - MATERIAL NUMBER**1.2 Uses and uses advised against****Use(s)** CALIBRATION • INDUSTRIAL APPLICATIONS**1.3 Details of the supplier of the product****Supplier name** BOC LIMITED (AUSTRALIA)**Address** 10 Julius Avenue, North Ryde, NSW, 2113, AUSTRALIA**Telephone** 131 262, (02) 8874 4400**Fax** 132 427 (24 hours)**Website** <http://www.boc.com.au>**1.4 Emergency telephone number(s)****Emergency** 1800 653 572 (24/7) (Australia only)**2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Oxidizing Gases: Category 1
Gases Under Pressure: Compressed gas**2.2 Label elements****Signal word** DANGER**Pictogram(s)****Hazard statement(s)**

H270 May cause or intensify fire; oxidizer.
H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

P220 Keep/Store away from clothing/incompatible materials/combustible materials.
P244 Keep reduction valves free from grease and oil.

Response statement(s)

P370 + P376 In case of fire: Stop leak if safe to do so.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content (v/v)
OXYGEN	7782-44-7	231-956-9	40%
NITROGEN	7727-37-9	231-783-9	Remainder

4. FIRST AID MEASURES**4.1 Description of first aid measures**

Eye	Adverse effects not expected from this product.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor.
Skin	Adverse effects not expected from this product.
Ingestion	Due to product form and application, ingestion is considered unlikely.
First aid facilities	No information provided.

4.2 Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

4.3 Immediate medical attention and special treatment needed

Treatment for hyperoxia.

5. FIRE FIGHTING MEASURES**5.1 Extinguishing media**

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable - oxidising agent. Supports combustion and may cause fire/explosion in contact with incompatible substances, strong acids, reducing agents, combustibles and flammables. Materials which burn in air, will burn more vigorously in oxygen enriched atmospheres.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture and internal pressure relief devices to be activated. Cool cylinders or containers exposed to fire by applying water from a protected location. Do not approach cylinders or containers suspected of being hot. Remove cool cylinders from the path of the fire if safe to do so. Ensure working area is well ventilated before re-use. Notify the manufacturer that you will be returning a faulty cylinder. Residual product will be disposed of when the cylinder is returned.

5.4 Hazchem code

2S	
2	Fine Water Spray.
S	Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

7.2 Conditions for safe storage, including any incompatibilities

Do not store near sources of ignition or incompatible materials. Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters**Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Nitrogen	SWA (AUS)			Asphyxiant	

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls No special precautions are normally required when handling this product.

PPE

Eye / Face	Wear safety glasses.
Hands	Wear leather gloves.
Body	Wear safety boots.
Respiratory	Not required under normal conditions of use.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	COLOURLESS GAS
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT APPLICABLE
pH	NOT APPLICABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT APPLICABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT

9.1 Information on basic physical and chemical properties

Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	OXIDISING GAS
Odour threshold	NOT AVAILABLE

9.2 Other information

% Volatiles	100 %
Cylinder pressure (when full)	13000 kPa @ 15°C

10. STABILITY AND REACTIVITY

10.1 Reactivity

Unreactive under normal conditions.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Combustible materials such as oil and grease can spontaneously ignite at low temperatures in oxygen enriched atmospheres. Materials which burn in air, will burn more vigorously in oxygen enriched atmospheres.

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Information available for the product: Based on available data, the classification criteria are not met.
Skin	Not classified as a skin irritant.
Eye	Not classified as an eye irritant.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin.
STOT – single exposure	Not classified as causing organ damage from single exposure.
STOT – repeated exposure	Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No ecological damage caused by this product.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION**CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3156	3156	3156
14.2 Proper Shipping Name	COMPRESSED GAS, OXIDIZING, N.O.S. (Contains oxygen)	COMPRESSED GAS, OXIDIZING, N.O.S. (Contains oxygen)	COMPRESSED GAS, OXIDIZING, N.O.S. (Contains oxygen)
14.3 Transport Hazard Classes	2.2, 5.1	2.2, 5.1	2.2, 5.1
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

Hazchem code 2S

GTEPG 2B1

EMS F-C, S-W

Other information Ensure cylinder is separated from driver and foodstuffs.

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.	
The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].		
Hazard codes	O	Oxidising
Risk phrases	R8	Contact with combustible material may cause fire.
Safety phrases	S2 S17	Keep out of reach of children. Keep away from combustible material.
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

16. OTHER INFORMATION

Additional information	<p>The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders.</p> <p>Application Method: Gas regulator of suitable pressure and flow rating fitted to cylinder valve or manifold with low pressure gas distribution to equipment.</p>
	<p>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p>
	<p>HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>
Abbreviations	<p>ACGIH American Conference of Governmental Industrial Hygienists CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds CNS Central Nervous System EC No. EC No - European Community Number EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) GHS Globally Harmonized System GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer LC50 Lethal Concentration, 50% / Median Lethal Concentration LD50 Lethal Dose, 50% / Median Lethal Dose mg/m³ Milligrams per Cubic Metre OEL Occupational Exposure Limit pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). ppm Parts Per Million STEL Short-Term Exposure Limit STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure) SUSMP Standard for the Uniform Scheduling of Medicines and Poisons SWA Safe Work Australia TLV Threshold Limit Value TWA Time Weighted Average</p>
Report status	<p>This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').</p> <p>It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.</p> <p>While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.</p>
Prepared by	<p>Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au</p>

[End of SDS]