# Chase

# MATERIAL SAFETY DATA SHEET

# **CHAMP CLEAR LACQUER**

## 1. Product And Company Identification

**Supplier** 

Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA

Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923

**E-Mail:** sales@chaseproducts.com **Web Site:** www.chaseproducts.com

**Supplier Emergency Contacts & Phone Number** 

Chem-Tel: 1-800-255-3924

**Issue Date:** 04/08/2002

Product Name: CHAMP CLEAR LACQUER

Chemical Name: 6-5325-1 CAS Number: Not Established

MSDS Number: 1535 Product Code: 419-0989-1

Product/Material Uses - Spray Paint

Manufacturer

Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA

Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com

Manufacturer Emergency Contacts & Phone Number

Chem-Tel: 1-800-255-3924

#### 2. Composition/Information On Ingredients

·		
Ingredient Name	CAS Number	Percent Of Total Weight
2-BUTOXYETHANOL	111-76-2	1 - 5
ACETONE	67-64-1	
BUTANE	106-97-8	
BUTYL ACETATE	123-86-4	
DIACETONE ALCOHOL	123-42-2	
ISOBUTYL ALCOHOL	78-83-1	
ISOPROPYL ALCOHOL	67-63-0	
METHYL ETHYL KETONE	78-93-3	1 - 5
PROPANE	74-98-6	
TOLUENE	108-88-3	10 - 15

The ingredients listed on this section are the hazardous components present at 1.0% or greater. Carcinogenic ingredients are listed if present at 0.1% or greater.

#### 3. Hazards Identification

Primary Routes(s) Of Entry - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation.

**Eye Hazards** - Causes eye irritation.

**Skin Hazards** - Causes skin irritation.

<u>Ingestion Hazards</u> - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately.

<u>Inhalation Hazards</u> - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea...

# **CHAMP CLEAR LACQUER**

#### 3. Hazards Identification - Continued

<u>Chronic/Carcinogenicity Effects</u> - Toluene has been associated with kidney and liver disorders. Overexposure to solvents have been associated with nervous system damage.

Epidemiology - None known

<u>Teratogenicity (Birth Defects)</u> - California's Proposition 65: "Warning: this product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm".

<u>Reproductive Effects</u> - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene.

**Neurotoxicity** - None known

Mutagenicity (Genetic Effect) - None known

<u>Signs And Symptoms</u> - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Prolonged contact with the skin causes irritation. Irritant to eyes.

Conditions Aggravated By Exposure - Pre-existing skin, respiratory, liver and kidney disorders.

Conditions Aggravated By Overexposure - Pre-existing skin, respiratory, liver and kidney disorders.

## First Aid (Pictograms)





## 4. First Aid Measures

**Eye** - Flush from eyes with plenty of water. If irritation develops, consult a physician.

**Skin** - Wash skin with soap and water. If irritation develops, consult a physician.

<u>Ingestion</u> - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

<u>Inhalation</u> - If overcome by vapor move victim to fresh air. Provide artificial respiration if necessary. Consult a physician if injury develops.

## 5. Fire Fighting Measures

Flash Point: Not available °F Not available °C

Flash Point Method: Not available Lower Explosive Limit: Not available Upper Explosive Limit: Not available

Fire And Explosion Hazards - This product is an aerosol product for which Flame Projection is 18 in, with

flashback. Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

#### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

#### Handling & Storage (Pictograms)



## 7. Handling And Storage

<u>Handling And Storage Precautions</u> - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

# **CHAMP CLEAR LACQUER**

#### 7. Handling And Storage - Continued

Handling Precautions - Avoid getting spray into eyes. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**AEROSOL STORAGE LEVEL III (NFPA-30B)** 

Work/Hygienic Practices - Wash hands thoroughly after using this product.

#### **Protective Clothing (Pictograms)**





## 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

**Skin Protection** - Rubber, vinyl or household type gloves.

Respiratory Protection - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

#### Ingredient(s) - Exposure Limits

2-BUTOXYETHANOL

ACGIH TLV-TWA 20 ppm (Skin); OSHA PEL-TWA 50 ppm (Skin)

**ACETONE** 

ACGIH TLV-STEL 750 ppm; ACGIH TLV-TWA 500 ppm; OSHA PEL-TWA 1,000 ppm

**BUTANE** 

ACGIH TLV-TWA 800 ppm

**BUTYL ACETATE** 

ACGIH TLV-STEL 200 ppm; ACGIH TLV-TWA 150 ppm; OSHA PEL-TWA 150 ppm

DIACETONE ALCOHOL

ACGIH TLV-TWA 50 ppm; OSHA PEL-TWA 50 ppm

ISOBUTYL ALCOHOL

ACGIH TLV-TWA 50 ppm; OSHA PEL-TWA 100 ppm

ISOPROPYL ALCOHOL

ACGIH TLV-STEL 500 ppm (Notice of Intended Change); ACGIH TLV-STEL 400 ppm (Proposed); ACGIH TLV-TWA 400 ppm (Notice of Intended Change)

ACGIH TLV-TWA 200 ppm (Proposed); OSHA PEL-TWA 400 ppm

METHYL ETHYL KETONE

ACGIH TLV-STEL 300 ppm; ACGIH TLV-TWA 200 ppm; OSHA PEL-TWA 200 ppm

**PROPANE** 

ACGIH TLV-TWA 2500 ppm; OSHA PEL-TWA 1,000 ppm

**TOLUENE** 

ACGIH TLV-TWA 50 ppm (Skin); OSHA PEL-CEILING 300 ppm; OSHA PEL-PEAK 500 ppm

OSHA PEL-TWA 200 ppm

## 9. Physical And Chemical Properties

Appearance - Appearance of paint.

Odor - Paint odor.

# **CHAMP CLEAR LACQUER**

#### 9. Physical And Chemical Properties - Continued

Chemical Type: Mixture Physical State: Liquid

**Melting Point:** Not applicable °F Not applicable °C **Boiling Point:** Acetone 113 °F Acetone 56 °C

Specific Gravity: 0.862 Percent VOCs: 52.05 Solubility: Insoluble

Evaporation Rate: Faster than butyl acetate

#### 10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

Incompatible Materials - Avoid heat, open flame and contact with strong oxidizers.

<u>Hazardous Decomposition Products</u> - Thermal decomposition may yield gases like carbon monoxide and carbon

dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

#### 11. Toxicological Information

No Data Available...

## 12. Ecological Information

No Data Available...

#### 13. Disposal Considerations

Wrap empty container in newspaper and dispose of it in non-incinerated trash only.

## 14. Transport Information

<u>Proper Shipping Name</u> - ORM-D Consumer Commodity

#### **DOT Identification Number**

UN1950

## **DOT Shipping Label**

Aerosol Consumer Commodity

## 15. Regulatory Information

<u>U.S. Regulatory Information</u> - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### **SARA Hazard Classes**

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

<u>SARA Section 313 Notification</u> - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material. 2-Butoxyethanol, Methyl ethyl ketone, Toluene. See section 2 for % amounts in the product.

# **CHAMP CLEAR LACQUER**

#### 15. Regulatory Information - Continued

## Ingredient(s) - U.S. Regulatory Information

## 2-BUTOXYETHANOL

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard: SARA - Fire Hazard

#### METHYL ETHYL KETONE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

#### **TOLUENE**

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

#### Ingredient(s) - State Regulations

#### 2-BUTOXYETHANOL

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **ACETONE**

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **BUTANE**

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **BUTYL ACETATE**

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### DIACETONE ALCOHOL

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### ISOBUTYL ALCOHOL

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### ISOPROPYL ALCOHOL

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### METHYL ETHYL KETONE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### **PROPANE**

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance


#### **TOLUENE**

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

## CHAMP CLEAR LACQUER

15. Regulatory Information - Continued

Ingredient(s) - State Regulations - Continued





#### 16. Other Information

Revision/Preparer Information
MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supercedes A Previous MSDS Dated: 04/16/2001

#### **Disclaimer**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### Chase Products Co.

Printed Using MSDS Generator™ 2000