

**SECTION I-MATERIAL IDENTIFICATION AND USE**

Material Name/Identifier:	Red Oxide Surface Primer	Stock No.	4401
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd	Street Address:	75 Advance Blvd.
City:	Brampton	Province:	Ontario
Postal Code:	L6T 4N1	Emergency Phone #:	CANUTEC:- 613-996-6666 (24HR)
Chemical Name:	N/Av. (mixture)	Chemical Family:	Modified resin solution
Chemical Formula:	N/Av. (mixture)	Trade Names & Synonyms:	none
Material Use:	AEROSOLIZED PAINT	Molecular Weight:	N/Av. (mixture)

**SECTION II-HAZARDOUS INGREDIENTS OF MATERIAL**

Hazardous Ingredients	C.A.S.	Approximate % Concentration	LD50 Species & Route	LC50 Species & Route
Acetone	67-64-1	30 -60	> 9750 mg/kg rat-oral	> 16000 ppm (4hr) rat-inhl.
xylene	1330-20-7	1 -5	4.3 g/kg rat-oral	6350 (4hr) rat-inhl.
Methyl Isobutyl Ketone	108-10-1	1 -5	2080 mg/kg rat-oral	2000 ppm (4hr) rat- inhl.
Propylene Glycol methyl ether acetate	108-65-6	5- 10	8500 mg/kg rat-oral	> 4345 ppm (6hr) rat-ihl.
Toluene	108-88-3	1 -5	5000 mg/kg rat-oral	8000 ppm (4hr) rat-inhl.
n-butyl acetate	123-86-4	1-5	13100 mg/kg rat oral	2000 ppm (4hr) rat- inhl.
Ferric oxide	1309-37-1	1-5	4000 mg/kg rat-oral	N/Av.
Isobutane (propellant)	75-28-5	5-10	N/Ap	142,500 ppm (4 hr). Rat - inhl.
Propane(propellant)	74-98-6	7-13	>5000 mg/kg rabbits-Dermal	N/Av.

**SECTION III-PHYSICAL DATA FOR MATERIAL**

Physical State:	Aerosol	Odour/Appearance:	Ketone odour/ red colour
Specific Gravity:	0.90-0.94	Odour Threshold(p.p.m.):	N/Av.
Boiling Point:	57 to 150°C	Evaporation Rate:	> 1
Freezing Point:	N/A	Solubility in Water:	N/Av.
% Volatile(by volume):	83- 84	Vapour Pressure,	55 -65
Vapour Density(Air=1):	>1	Coefficient of Water/Oil Distribut:	N/Av.
pH	N/Av.		

**SECTION IV-FIRE AND EXPLOSION HAZARD OF MATERIAL**

Flammability Yes/No	Yes	If yes under which conditions?:	Excessive heat, open flame or sparks
Auto Ignition Temperature:	272-527 °C	Means of Extinction:	Water, Carbon dioxide, dry chemical, foam
Flashpoint and Method:	> -18°C Tag. C.C	Hazardous Combustion Products:	Hydrocarbon fumes & smoke. Carbon monoxide where combustion is incomplete.
Aerosol Flame Projection	> 15 cm But < 100 cm	Lower Flammable Limit (% by volume):	2.6
Upper Flammable limit( % vol)	15.1	Sensitivity to Mechanical Impact:	N.Ap.
Explosion Data:	Sensitivity to Static Discharge:		N.Ap.

**SECTION V-REACTIVITY DATA**

Chemical Stability Yes/No:	Yes	If NO under which conditions?	N.Ap.
Incompatibility to Other Substances Yes/No:	Yes	If so which ones?	Strong oxidizers
Reactivity and under what conditions?	N/E		
Hazardous Decomposition Products:	Hydrocarbon fumes & smoke. Carbon monoxide where combustion incomplete.		

N/E: not established N.Ap.: Not applicable N/Av.: not available

**SECTION VI-TOXICOLOGICAL PROPERTIES OF PRODUCT**

Route of Entry: ALL Routes	--SKIN CONTACT --SKIN ABSORPTION --EYE CONTACT --INHALATION --INGESTION		
Effects of Acute Exposure:	Dizziness and nausea. Irritation to skin and eyes.		
Effects of Chronic Exposure:	Solvents may cause defatting dermatitis.		
Irritancy of Product:	Skin/Eye Irritant		
Sensitization of Product:	Presently Unknown	Toxicologically Synergistic Materials:	Unknown
--CARCINOGENICITY --REPRODUCTIVE EFFECTS --TERATOGENICITY --MUTAGENICITY			
<p>Toluene- prolonged and repeated exposure of pregnant animals to toluene (levels greater than approximately 1500 ppm) has been reported to cause adverse fetal development effects. Xylene: High exposures to Xylene in some animal studies, often at levels toxic to the mother, affected embryo/fetal development. The Significance of this finding to Human is not known</p> <p>Xylene- this product contains EthylBenzene (EthylBenzene is in Xylene). Ethylbenzene has been shown to cause cancer in laboratory animals. Toxicity tests carried out for chronic effects and mutagenicity have been negative. The Relevance of this finding to human is uncertain. IARC has Classified EthylBenzene as a possible human carcinogen.</p>			

**SECTION VII-PREVENTIVE MEASURES**

Personal Protective Equipment to be used:

Gloves(specify):	Wear chemical Resistant gloves	Eye (specify):	Safety Glasses
Respiratory(specify):	NIOSH organic vapor mask	Clothing:	Not required
Respiratory Protection:	If used indoors or on a continuous basis, use of NIOSH approved cartridge type respirator is recommended		
Engineering Controls:	Ventilation - Local (Mechanical if used indoors on continuous basis)		
Leak and Spill Procedure:	Remove all sources of ignition. Use inert absorbent material, and non-sparking tools. Avoid breathing fumes. Ventilate area. Prevent from entering a watercourse.		
Waste Disposal:	Do not Puncture or incinerate containers even when empty. Dispose of in accordance with local, provincial and federal regulations. Aerosol cans to be disposed of at local recycling depots.		
Storage Requirements:	Store in a cool, well ventilated area not to exceed 50°C		
NFPA/CNFC 3.3.5	Level 2		
Handling Procedures	Keep away from heat, sparks and open flames. Keep away from children. Donot inhale or ingest.		
TDG Classification:	Consumer Commodity (Aerosols, UN1950, Class 2.1)		
WHMIS Classification:	A, B5, D2A, D2B	Complies with CCCR 2001	

**SECTION VIII-FIRST AID MEASURES**

Eye:	Flush immediately with plenty of water for at least 15 minutes and get immediate medical attention.
Skin:	Wash thoroughly with soap and water. If irritation and rash persists seek medical attention.
Inhalation	Remove to fresh air. Restore breathing if required. Seek immediate medical attention if discomfort persist.
Ingestion:	DO NOT INDUCE VOMITING. Get immediate medical attention.

**SECTION IX-PREPARATION DATE OF M.S.D.S.**

Additional Info/Comments:		Source Used: Supplier's data
Phone Number:	(905) 793-4311	Prepared By: Quality Control Laboratory
Date Prepared:	January 2, 2015	Kleen-Flo Tumbler Industries Limited

**THIS SHEET SUPERSEDES ANY OTHER M.S.D.S. PREVIOUSLY PREPARED**