Myers Order Nos. 46430, 46431, 46491

MATERIAL SAFETY DATA SHEET

MSDS Name: NOVOC W/B BLACK TIRE PAINT

MSDS Number: P-9217

Version Number
MSDS Date: MAR-04-2014
Page Number: 1 of 5

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: NOVOC W/B BLACK TIRE PAINT
CAS Number MIXTURE
Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPI: H

Company Identification: Akron Paint & Varnish, Inc.

DBA APV Engineered Coatings

1390 Firestone Parkway

Akron OH 44301

Telephone/Fax: James K. Mosey
Telephone/Fax: (330) 773-8911 (330) 773-8911 (330) 773-1028

Emergency Phone (24 Hour): EVENING ADMINISTRATOR

(330) 773-8911

Chemtrec (24 Hour): (800) 424-9300

Product Class W/B PAINT

Product Class W/B PAINT
Trade Name NOVOC W/B BLACK TIRE PAINT
Product Code P-9217

DOT Hazard Class

N/A UN Number UN Pack Group N/A N/A UN Class

Shipping Name Technical Name

ADDITIONAL INFORMATION

SECTION II - INGREDIENT AND HAZARD INFORMATION

CAS Number Percent TSCA Ingredient Name (No hazardous ingredients known at this time.)

ADDITIONAL INFORMATION

SECTION 313 SUPPLIER NOTIFICATION: THIS PRODUCT MAY CONTAIN TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND 40 CFR 372.

MSDS Name: NOVOC W/B BLACK TIRE PAINT

MSDS Number: P-9217

Version Number

MSDS Date: MAR-04-2014 Page Number: 2 of 5

CAUTION: THIS PRODUCT MAY BECOME A DUST NUISANCE WHEN REMOVED BY SANDING, ABRADING OR SANDBLASTING. DUST MASKS SHOULD BE WORN DURING

THESE OPERATIONS.

NA = not available NE = not established

NR = not regulated.

ALL COMPONENTS OF THIS MIXTURE ARE LISTED ON THE TSCA INVENTORY.

SECTION III - PHYSICAL DATA

LIQUID BLACK Form: Appearance/Color: SLIGHT Odor:

Odor:

pH Value:

Boiling Range:

Vapor Pressure (mmHg):

Melting Point:

Evaporation Rate:

Vapor Density:

Partition Coefficient

Volatile Weight

Volatile Volume

Specific Gravity:

VOC

SLIGHT

8-10

8-10

100.°C)

Not Available

Not Applicable

0.33 times Slower than n-Butyl Acetate

Heavier than air

Not Applicable

85.91%

80.91%

103184

VOC

0.1 W / 0.76D

VOC 0. Molecular Weight: Heavy Elements (ppm) 0.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class IIIB
Flash Range: >200 F
Setaflash

0.2%

Explosive Range: 3.5%

EXTINGUISHING MEDIA:

Carbon Dioxide --- Dry Chemical --- Foam --- Water Fog

MSDS Name: NOVOC W/B BLACK TIRE PAINT

MSDS Number: P-9217

Version Number

MSDS Date: MAR-04-2014 Page Number: 3 of 5

Use water for cooling material stored in vicinity of fire.

SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode.

UNUSUAL FIRE & EXPLOSION HAZARDS:

During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SECTION V - HEALTH HAZARD DATA

Exposure and Dose Route Species

PERMISSIBLE EXPOSURE LEVEL:

Refer to Section II

EFFECTS OF OVEREXPOSURE:

EYES: Can cause redness, irritation, swelling and blurred

vision.

SKIN: Prolonged or repeated contact can cause slight irrit-

ation, or dermatitis.

BREATHING: Not normally affected

SWALLOWING: Can cause gastrointestional irritation, nausea,

vomiting & diarrhea.

FIRST AID:

EYES: Flush with large amounts of water.

SKIN: Wash thoroughly with soap and water.

SWALLOWING: The decision to induce vomiting or not must be

made by a physician after careful consideration of all

materials ingested.

SECTION VI - REACTIVITY DATA

Stability: This product is stable Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY

NONE

CONDITIONS TO AVOID:

MSDS Name: NOVOC W/B BLACK TIRE PAINT

MSDS Number: P-9217

Version Number

MSDS Date: MAR-04-2014 Page Number: 4 of 5

HAZARDOUS DECOMPOSITION PRODUCTS:

May form carbon monoxide and dioxide, various hydrocarbons, etc.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Dike area of spill to prevent spreading---- pump liquid into salvage tank---- remaining liquid may be taken up with; sand, floor absorbent or other absorbent material and shoveled into containers--- prevent run-off to sewers and bodies of water---notify proper authorities as required by local, state and federal regulations. WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Occupational Exposure Limits

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

RESPIRATORY PROTECTION:

None normally required

VENTILATION:

General ventilation

PROTECTIVE GLOVES:

None normally required.

EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses. (Consult your safety equipment supplier) OTHER PROTECTIVE EQUIPMENT:
Normal protective clothing.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not drop containers. KEEP FROM FREEZING.

MSDS Name: NOVOC W/B BLACK TIRE PAINT

MSDS Number: P-9217

Version Number

MSDS Date: MAR-04-2014 Page Number: 5 of 5

OTHER PRECAUTIONS:

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

SECTION X - ADDITIONAL REGULATORY INFORMATION

SARA TITLE III SECTION 313: CONTAINS NO SARA TITLE III SECTION 313 REPORTABLE CONCENTRATION.

PROP 65 (CARCINOGEN):

PROP 65 (TERATOGEN):

PROP 65 (BOTH CARCINOGEN AND TERATOGEN):