

MOBIL OIL CORP -- MOBIL 1 SYNTHETIC GEAR LUBRICANT -- 9150-01-363-1192

=====
Product Identification
=====

Product ID:MOBIL 1 SYNTHETIC GEAR LUBRICANT

MSDS Date:12/30/1992

FSC:9150

NIIN:01-363-1192

MSDS Number: BPRRX

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-227-0707 X3265 S. CASTILLO

Emergency Phone Num:609-737-4411/CHEMTREC 800-424-9300

CAGE:6G112

=== Contractor Identification ===

Company Name:MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ

ZIP:08540

Country:US

Phone:609-737-4411

CAGE:6A687

Company Name:MOBIL OIL CORP

Address:3225 GALLOWS RD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525, 856-224-4644

CAGE:6G112

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE: 0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS (INERT)
Fraction by Wt: >85%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: SLIGHT IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SLIGHT SKIN IRRITATION.
Medical Cond Aggravated by Exposure:NONE KNOWN

=====
First Aid Measures
=====

First Aid:EYES- FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS,
CALL A PHYSICIAIN. SKIN- WASH CONTACT AREAS WITH SOAP AND WATER.
INHALATION AND INGESTION: NOT EXPECTED TO BE A PROBLEM.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>325F,>163C
Lower Limits:0.6%
Upper Limits:7.0%
Extinguishing Media:CO2, FOAM, DRY CHEMICAL & WATER FOG.
Fire Fighting Procedures:WATER AND FOAM MAY CAUSE FROTHING.
FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:USE WATER TO KEEP FIRE EXPOSED
CONTAINERS
COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

=====
Accidental Release Measures
=====

Spill Release Procedures:ADSORB ON FIRE RETARDANT TREATED SAWDUST,
DIATOMACEOUS EARTH, ETC. SHOVEL UP & SAVE IN A CONTAINER FOR
DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED.
Other Precautions:UNUSED PRODUCT IS NOT A HAZARDOUS WASTE. USED
PRODUCT
MAY BE REGULATED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE
AND WITH ADEQUATE VENTILATION.
Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED
Eye Protection:NO SPECIAL EQUIPMENT REQUIRED
Other Protective Equipment:EYE WASH.
Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS
BE FOLLOWED.
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Vapor Pres:<.1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT AMBER LIQUID, MILD ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:CARBON MONOXIDE.

=====
Disposal Considerations
=====

Waste Disposal Methods:SEND FOR RECYCLING., OR DISPOSE OF IN
ACCORDANCE
WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling
agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.